

Centrifugal Upblast & Sidewall Exhaust

- General Clean Air • Restaurant Grease
- High Wind • Seismic • Smoke Control • Contaminants

Models CUBE, CUE, CWB, CW, S-CUBE and USGF



BUILDING VALUE IN AIR.



May
2009

Centrifugal Exhaust Fans: Roof Upblast and Sidewall

When you buy a Greenheck roof upblast or sidewall exhaust fan, you'll receive a fan with the industry's best performance and durability for general clean air, restaurant grease, smoke control, light contaminants, seismic, high wind, and hurricane applications. Both roof upblast and sidewall configurations are specifically designed to discharge air directly away from the mounting surface.

- Performance as cataloged is assured. All fan sizes are tested in our AMCA Accredited Laboratory and all models are licensed to bear the AMCA Sound and Air Performance seal.
- UL/cUL Listed for electrical, grease and smoke control.
- Greenheck subjects these products to extensive life testing, assuring you the fans will provide many years of reliable performance.



- CUBE, CUE, CWB, CW, USGF, and S-CUBE models are listed for electrical (UL/cUL 705) File no. E40001
- CUBE, CUE, CWB, CW, and USGF models are listed for grease removal (UL/cUL 762) File no. MH11745
- S-CUBE and USGF models are listed for Emergency Smoke Control Systems (UL/cUL Listed for 500°F (260°C) for 4 hours and 1,000°F (538°C) for 15 minutes) File no. MH17511

***UL/cUL is optional and must be specified**



Greenheck Fan Corporation certifies that the Models CUBE, CUE, CWB, CW, USGF, and S-CUBE fans shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and Publication 311 and comply with the requirements of the AMCA Certified Ratings Program. The certified ratings for Models CUBE, CUE, CWB, CW, USGF, and S-CUBE are shown on pages 18 to 81.

Table of Contents

Model Comparison.....	3
Codes & Certifications.....	4
Applications:	
General Clean Air.....	4
Seismic.....	5
Vari-Green Motors.....	5
Emergency Smoke Control.....	6
Restaurant Grease.....	6
Heavy-Grease.....	6
High Wind & Hurricane.....	7
Roof Curbs.....	8

Standard Construction Features.....	9-10
Options & Accessories.....	11-12
Typical Installations.....	13-14
Roof Curb Installations.....	15-16
Performance and Dimensions:	
Model Number Code.....	17
Roof Upblast, Belt Drive (by size).....	18-44
Roof Upblast, Direct Drive (by size).....	45-53
Sidewall, Belt Drive (by size).....	54-72
Sidewall, Direct Drive (by size).....	73-81
Typical Specifications.....	82-87
Quick Build Programs.....	88
Warranty.....	88

Model Comparison													
Model	Mounting		Application							Drive Type		Performance	
	Roof Curb	Wall	General/Clean Air	Contaminated Air	Spark-Resistant	Grease (UL 762)	Smoke Control (UL)	High Wind (150 mph)	High Temperature (above 200°F)	Belt	Direct	Volume Range cfm (m ³ /hr)	Maximum Static Pressure in. wg (Pascals)
	CUBE	✓		✓	✓	✓	✓		✓	✓	✓	200 - 30,000 (340-50,970)	5.0 (1245)
	CUE	✓		✓	✓	✓	✓		✓	✓		70 - 6,400 (119-10,874)	3.0 (747)
	CWB		✓	✓	✓	✓					✓	200 - 12,500 (340-21,238)	2.75 (685)
	CW		✓	✓	✓	✓					✓	70 - 6,400 (119-10,874)	3.0 (747)
	USGF	✓					✓	✓	✓	✓	✓	330 - 6,800 (561-11,553)	2.0 (498)
	S-CUBE	✓						✓	✓	✓	✓	180 - 30,000 (306-50,970)	2.75 (685)

Codes and Certifications

UL 705 - Power Ventilators

Intended to assure the buyer of the safety of electrical components and connections within power ventilators and duct fans. Limited to fans connected to permanently installed wiring that meet NFPA 70 and the National Electric Code. Tests under this standard relate to extremes of current, temperature, fuses, motor windings, bearing temperatures, and water that a fan could be subject to.

UL Power Ventilators for Smoke Control Systems

Ventilators or duct fans have been investigated with respect to their operation during exposure to elevated temperatures. Installed as part of a smoke control system and in accordance NFPA 92A and 92B. Requirements also include UL 705 and if applicable UL 793. Meets the IRI and SBCCI "Standard Fire Prevention Code" requirements.

UL 762 - Power Ventilators for Restaurant Exhaust Appliances

UL 762 is for exhausting grease in the airstream as found in restaurant or kitchen applications. Basic testing is the same as for UL 705 and additional testing includes operating the fan in a high temperature airstream without warpage,

deterioration or damage that would cause the fan to operate unsafely plus grease flare-up tests. Greenheck products with UL 762 include most centrifugal roof upblast and centrifugal sidewall fans, utility fans and housed centrifugal fans.

AMCA Certified Ratings Program

Ensures that all data is accurate. The 211 seal for air performance certifies that the fan has been tested to the appropriate AMCA standards in a licensed test facility and that the air performance displayed in catalogues and selection software is accurate. The 311 seal for air and sound performance certifies that the fan has been tested to the appropriate AMCA sound standards in a licensed facility and that the sound performance displayed in catalogues and selection software is accurate. The AMCA Certified Ratings Program is designed to ensure that the products perform as stated and that a third-party organization has verified all published data for accuracy and consistency.

NFPA 96

Standard for Ventilation Control and Fire Protection of Cooking Operations. This standard outlines the appropriate installation methods and required equipment to ensure a safe and effective kitchen or cooking installation of HVAC equipment.

Clean Air Applications

Models CUBE, CUE, CWB, and CW

These spun aluminum fans are specifically designed for roof mounted or wall mounted applications. General clean or lightly contaminated exhaust air can be discharged directly upward, away from the roof surface or discharged out and away from building walls.

- Most advanced motor cooling of any fan in its class.
- Greenheck pioneered leakproof construction for the entire life of the fan utilizing a one-piece windband continuously welded to the curb cap.
- Performance as cataloged is assured. All fan sizes are tested in our AMCA Accredited Laboratory and all models are licensed to bear the AMCA Sound and Air Performance seal.
- Greenheck subjects these products to extensive life testing, assuring you the fans will provide many years of reliable performance.



Seismic Applications

Models CUBE, CUE, S-CUBE, USGF

The International Building Code has been adopted on the state and local level throughout most of the fifty states. The adoption of this code has resulted in the adherence of buildings, along with electrical and mechanical components to new provisions in the code. In particular, there is an emphasis on seismic compliance. As an industry leader, Greenheck introduces the first seismic compliant centrifugal roof exhaust fan available for general clean air applications.

Greenheck offers products certified for the worst plausible seismic event that would be found on the IBC Spectral Response Map. Models CUBE, CUE, S-CUBE, and USGF are rated for all soil site classes A-F, which allows Greenheck to provide a seismic ventilation solution regardless of the location.

Rigorous Testing

- Third-party FEA (Finite Element Analysis) by licensed Professional Engineers
- Tested in Accordance with ICC ES AC-156 acceptance criteria

State P.E. Calculations

Models have been reviewed by state licensed Professional Engineers to ensure they conform to



Seattle, WA, 03/05/01 -- Damage in Pioneer Square from the 02/28 earthquake. FEMA/Photo by: Liz Roll/FEMA News Photo

the requirements of ASCE 7-05 Minimum Design Loads for Buildings and Other Structures and the International Building Code.

How Can Greenheck Provide a Seismic Solution?

While adhering to rigorous testing standards, Greenheck Fan Corporation is striving to provide a comprehensive selection of equipment to address the HVAC industry's seismic needs. The offerings cover all soil site classes. For the simplification of the submittal process, the consulting engineer simply needs to specify seismic compliant equipment.


Vari-Green Motor Applications

Models CUE and CW Available in sizes thru 161

The Greenheck Vari-Green motor blends technology, controllability and energy-efficiency into a low maintenance package changing the way the industry designs, specifies and operates air movement equipment.

The Vari-Green motor is the industry's first fully controllable fractional horsepower (hp) motor available in 1/4 hp, 1/2 hp and 3/4 hp. The Vari-Green motor is cost-effective with less than one-year payback. The motor is available with a potentiometer speed control dial mounted right on the motor to make system balancing a breeze. It can also be provided with 0-10 volt control wire inputs for easy integration into a Building Automation System (BAS) or any controller that can output a 0-10 volt signal.

Greenheck is leading the charge in the LEED and Green Building initiative. Greenheck became one of the first manufacturers in the Air Movement and Control industry to join the LEED/green movement when



they joined the United States Green Building Council (USGBC) in 2005. Greenheck has been actively researching qualification requirements for our products to meet LEED credits and prerequisites. The Vari-Green motor significantly helps qualification efforts for the Energy & Atmosphere credits and prerequisites; specifically credit one, Optimize Energy Performance and prerequisite two, Minimum Energy Performance.

Emergency Smoke Control Applications

Models S-CUBE and USGF

When you buy a Greenheck model S-CUBE or USGF, you receive a fan with the industry's best performance and durability for Smoke Control Applications (as found in emergency smoke control systems).

- The first spun aluminum (steel for USGF model) UL/cUL Listed fan for Emergency Smoke Control Systems in the industry.
- UL/cUL Listed for 500°F (260°C) for 4 hours and 1,000°F (538°C) for 15 minutes.
- Half the weight of traditional smoke control fans, ideal choice for roof load concerns.
- Low profile, height is less than half of traditional smoke control fans, maximum of 48 inches (1200 mm) from curb cap to top of fan.
- Multiple applications, capable of exhausting general clean air and satisfying emergency smoke control regulations.



Restaurant and Grease Applications

Models CUBE, CUE, CWB, and CW

When you choose a Greenheck fan, you have selected a fan with the industry's best performance and durability for restaurant and grease applications (as stated in NFPA 96 Vapor Removal from Cooking Equipment). Models CUBE, CUE, CWB, and CW fans are specifically designed for use in restaurant applications to discharge air directly away from the mounting surface.

- Most advanced motor cooling of any fan in its class.
- Greenheck pioneered leakproof construction for the entire life of the fan utilizing a one-piece windband continuously welded to the curb cap.
- UL/cUL 762 Listed for exhausting grease.



Ultimate Steel Grease Fan for Heavy-Grease Applications

Model USGF

When you choose a Greenheck model USGF fan, you have selected a fan with the industry's best performance and durability for heavy-grease applications (as stated in NFPA 96 Vapor Removal from Cooking Equipment). The USGF fan is specifically designed for severe grease applications to remove high amounts of grease and/or solid fuels and to discharge air directly away from the mounting surface.

- Only spun steel fan in the industry.
- Withstands the most severe cleaning conditions.
- Most advanced motor cooling of any grease fan. Capable of continuously handling 400°F (204°C) airstream temperatures.
- UL/cUL 762 Listed for exhausting grease.
- Only kitchen specific exhaust fan to meet Miami-Dade Test protocols for Large Missile Impact Test



High Wind & Hurricane

Models CUBE, CUE and USGF



Greenheck is leading the High Wind Standard for roof top fans and ventilators. Forceful winds and wind-borne debris are the cause of most hurricane damage. Hurricane winds start at 75 mph. At speeds over 150 mph, wind can exert a force of 130 pounds per square foot pressure or over 900 pounds on a fan and curb. Forceful winds are not the only problem; wind-borne debris can also cause detrimental effects to objects and structures. High winds and extreme forces are the cause of most storm damage. By analyzing calculations, computer simulations, actual testing, and other standards — Greenheck developed the High Wind Standard.

Protocols designed to protect against wind-borne debris and severe wind loads:


Structural Performance Load	A static load that is 1.5 times the design load (195 pounds per square foot pressure) is applied both positive and negative to simulate wind force loads in each direction. Structural Performance per Dade County Protocol TAS-202 (ASTM E-330).
Large Missile Impact Test	Large Missile Impact Testing is required when objects are located 30 feet or less from the ground. The test is per Dade County Protocol TAS-201. The test unit is impacted three times with a piece of lumber (2 in. x 4 in. x 6 ft.) weighing approximately nine pounds and traveling at 34 mph. This simulates wind-borne debris striking the fan.
Miami-Dade County Test Protocols	Greenheck has gone the extra mile and worked with Miami-Dade County to design a High Velocity Hurricane Zone standard for rooftop fans. The USGF has become the first rooftop fan certified and approved by the Miami-Dade Building Code Compliance office and Texas Department of Insurance for use in hurricane zones.
Miami-Dade NOA Numbers	The certifications can be viewed on the Miami-Dade County web site under the NOA numbers listed below. Models CUBE, CUE and USGF are the first upblast aluminum/steel fans in the industry that have received a Miami-Dade NOA for high wind (150 mph) and hurricane zones. CUBE: 08-0519.02, CUE: 08-0519.02 and USGF: 08-0519.01
Texas Department of Insurance	The certifications can be viewed on the Texas Department of Insurance Windstorm web site under TDI number RV-42.
State Licensed P.E. Calculations	Structural calculations performed by a state licensed Professional Engineer (P.E.) on models CUBE, CUE and USGF include Finite Element Analysis (FEA) and a stamped P.E. report of the fans compliance to ASCE 7-02 Minimum Design Loads for Buildings and Other Structures Standard and the Florida Building Code. The ASCE 7-02 Standard meets the IBC, Florida and Miami-Dade codes. The models have been proven to withstand winds in excess of 150 mph (61 psf).
Certified Independent Third-Party Testing	Each of the Greenheck models have been subjected to extensive testing procedures. The CUBE, CUE and USGF have been certified by an independent third party to the ASTM E-330 Static Pressure Difference Standard, Florida Building Code Test Protocols TAS-202 Static Pressure Difference and TAS-201 Large Missile Impact. All tests are video taped for documentation of test method and results.
Computational Fluid Dynamics (CFD)	All Greenheck high wind models have been analyzed using Computational Fluid Dynamics (CFD). CFD is computer software designed to simulate the flow of high speed (150 mph) winds over the surface of objects. The software records the force profile exerted on the fan, so it can be utilized in Finite Element Analysis (FEA).
Finite Element Analysis (FEA)	Utilizing the results from CFD analysis Greenheck can accurately predict the stress, strain, and deflection resulting from high wind loads. Greenheck high wind units have been proven to withstand 150 mph winds through Finite Element Analysis utilizing CFD results.

Applications: Severe-Duty Roof Curbs for High Wind and Hurricane

High wind and severe-duty roof curbs are available on CUBE, CUE and USGF models with high wind certification. The severe-duty roof curb models can ship separate to allow for final finishing of the roof prior to the fan arrival and installation.

Model GPF — This roof curb is specifically designed for high wind applications up to 150 mph, used on fan models CUBE and CUE. Standard height is 12 inches (305 mm), fully-welded straight sides with a 5-inch flashing flange. GPF is available up to 18-inches (460 mm) in height to meet greater height requirements.

Models SD and SDP — The severe-duty curbs are specifically designed for high wind applications up to 150 mph and used on models CUBE, CUE and USGF fans. Model SD is for use on flat roofs and model SDP for pitched roofs. They are attached directly to the building structure with extremely high structural design load requirements. Maximum design load is 140 psf. The severe-duty curbs are 12-gauge coated steel with a 1.75-inch lip on the top and a 4-inch flange on the bottom. SD curbs are available in heights of 12-24 inches. Heights greater than 18 inches are reinforced in the interior with 12-gauge by 2-inch angles. SDP curbs available in heights 14-18 inches and are reinforced in the interior with 12-gauge by 2-inch angles.



Large missile impact test on a model USGF fan.




Standard Construction Features


Standard Construction Features		CUE CUBE	CW CWB	USGF	S-CUBE
Wheel	An aluminum, backward-inclined, non-overloading centrifugal wheel is utilized to generate high-efficiency and minimal sound. Wheel cones are carefully matched to the venturi for maximum efficiency. Each wheel is statically and dynamically balanced for long life and quiet operation.	✓	✓	✓ *Non-Stick, Steel	✓ *Steel
Disconnect Switch	NEMA-1 switch is factory mounted and wiring is provided from the motor as standard (other switches are available). All wiring and electrical components comply with the National Electric Code (NEC) and are either UL/cUL Listed or Recognized.	✓	✓		
	NEMA-3R switch is factory mounted and wired as standard. All wiring and electrical components comply with the National Electric Code (NEC) and are either UL/cUL Listed or Recognized.			✓	✓
Fan Shaft	Precisely sized, ground and polished so the first critical speed is at least 25% over the maximum operating speed. Where the shaft makes contact with bearings, close tolerances result in longer bearing life.	✓	✓	✓	✓
Bearings	100% factory tested and designed specifically for air handling applications with a minimum L ₁₀ life in excess of 100,000 hours (L ₅₀ life of 500,000 hours).	✓	✓	✓	✓
Motor	Carefully matched to the fan load and is mounted out of the airstream.	✓	✓	✓	✓
Motor Cover	Constructed of aluminum. Attached with stainless steel fasteners for easy removal and access to the motor compartment and drive assembly.	✓	✓	✓ *Steel	✓
Motor Cooling Tube	Cooling fins located on top of fan wheel draw outside air through a large breather tube directly into the motor compartment. Positive motor cooling with fresh air results in maximum motor life.	✓	✓	✓	✓
Stainless Steel Fasteners	Allow easy removal and access to the motor compartment and drive assembly.	✓	✓	✓	✓
Lifting Points	Various lifting points located on the drive frame and bearing plate.	✓	✓	✓	✓
Vibration Isolation	True vibration isolators consist of two independent studs separated by a neoprene (rubber) center. Reduces vibration and noise transfer between drive system and fan housing. (No steel to steel contact. Factory mounted ground wire used to ground system).	✓	✓	✓	✓
Drive Assembly	Belts, pulleys and keys are oversized 150% of driven horsepower. Machined cast pulleys are adjustable for final system balancing. Belts are static-free and oil-resistant.	✓	✓	✓	✓
Dual Drives	Oversized 150%, adjustable, static-free and oil-resistant.			✓	
Windband	One-piece, heavy-gauge aluminum with a rolled bead for extra strength directs exhaust air away from the mounting surface.	✓	✓	✓ *Steel	✓
Leakproof Construction	One-piece windband is continuously welded to the curb cap and drain trough for leakproof protection on models CUE, and CUBE sizes 98 through 300 and all sizes with UL/cUL 762.	✓	✓	✓	✓
Curb Cap with Mounting Holes	One-piece for a weather-tight fit. Constructed of aluminum with an integral deep spun venturi. Aluminum curb cap has pre-punched mounting holes to ensure correct attachment to the roof.	✓	✓	✓ *Steel	✓
Drain Trough	Allows for one-point drainage of water, grease and other residues.	✓		✓	✓
Internal Conduit Chase	For easy internal electrical wiring in applications, not subject to NFPA.	✓	✓		
Nameplate	Permanent stamped aluminum nameplate for exact model and serial number identification.	✓	✓	✓	✓
Galvanized Birdscreen	Rigid wire protects the fan discharge from birds and small objects. Standard on all sidewall fan models.		✓		
Galvanized Mounting Plate	Allows mounting and sealing to the wall prior to mounting the entire unit. The remainder of the unit is attached to the mounting plate without locating and fastening problems associated with mounting a heavy sidewall unit to a wall.		✓		
Heat Baffle	Extends motor life by reducing the amount of heat that penetrates through the bottom of the motor support pan.			✓	✓
Internal Supports	Heavy-gauge supports and bracing are added for additional strength to withstand winds of 150 mph.				
Hinged Curb Cap with Cables	Allows maintenance personnel to hinge the entire fan up to gain access to wheel and ductwork for regular inspection and cleaning.			✓	
Permatector™ Coating	Typically used for applications that require corrosion resistance in indoor and outdoor environments.			✓	

*Differences from the standard construction feature.


Standard Construction Features




Models CUBE and CUE




Models CUBE and CUE



Models CWB & CW



Model USGF



Options and Accessories

Roof Curbs — Wide variety of roof curbs are available for mounting the fan to the roof, including: vented, flanged, pitched, and sound-absorbing. For more information on severe-duty curbs refer to the information on page 8.



Hinged Curb Cap Kit with Cables — The hinged curb cap allows the entire fan to swing open to allow maintenance personnel access to the wheel and ductwork for regular inspection and cleaning. Hinged curb cap kit with cables is an option on all upblast models. A factory mounted option is available on all upblast models size 220-480.



Hinged Base — Allows for easy maintenance. Hinge and restraining cables are factory mounted to a subbase attached directly to curb without additional height added. Mounted hinged base with cables standard on all USGF fans.

Drain Connection — Allows for single-point drainage of grease, water or other residues.



Grease Trap — Aluminum trap designed to collect grease residue to avoid drainage onto roof surface.

Grease Trap with Absorbent Material — Same as above with an absorbent material to collect grease residue for easy disposal.



Curb Seal — Rubber seal between fan and curb to assure proper sealing when attached to a curb.

Curb Extensions — Models GPE and GPEX are available for model S-CUBE. Mounts between roof curb and fan for additional height from roof top.

Vented Curb Extensions — Mounts between roof curb and roof mounted fan to meet NFPA requirements of 40-inch (1016 mm) minimum discharge above the roof when mounted on a minimum 8-inch (203 mm) high roof curb.



Non-Stick Aluminum Wheel — Patented coating helps prevent wheel imbalance in heavy-grease applications and allows buildup on wheel to be easily removed. Patent No. 5,809,993 standard non-stick steel wheel on model USGF.



Clean-Out Port — Patented removable plug allows for easy spray or steam cleaning of wheel through the windband. Available on select models. Patent No. 5,809,993



Disconnect Switches — Assorted NEMA rated switches are available for positive electrical shutoff and safety, including: dust-tight, rainproof and corrosion-resistant.



Windband Extension — Aluminum tube raising the fan discharge an additional 36-inch (914 mm) minimum for special code requirements.



Birdscreen — Galvanized or aluminum rigid wire to protect the fan discharge from birds or small objects. Galvanized is standard on models CWB and CW models.




Dampers — Designed to prevent outside air from entering back into the building when fan is off. Includes backdraft and motorized dampers. (Not available with UL/cUL 762 or USGF fans)



Tie-Down Points — Four brackets located on the windband for securing the fan in heavy-wind applications.



Speed Controllers — Available for use with shaded pole and permanent split capacitor open motors on direct drive fans. They provide an economical means of system balancing.



UL/cUL 705 — Models CUBE, CUE, CWB, and CW, may be listed for electrical. Model S-CUBE comes standard with UL 705.


UL/cUL 762 — Models CUBE, CUE, CWB, and CW, may be listed for grease removal. Model USGF comes standard with UL 762.

UL/cUL Emergency Smoke Control — Models S-CUBE and USGF may be listed for emergency smoke control.

The following chart shows which options and accessories are available on Greenheck’s roof upblast and sidewall exhaust fans.

Options and Accessories	CUBE	CUE	CWB	CW	S-CUBE	USGF
Roof Curbs	Option	Option			Option	Option
Hinged Curb Cap with Cables	Option	Option			Option	Standard
Hinged Base	Option	Option			Option	Standard
Drain Connection	Option	Option				Option
Grease Trap	Option	Option				Option
Grease Trap with Absorbent Material	Option	Option				Option
Curb Seal	Option	Option			Option	Option
Curb Extensions	Option	Option			Option	Option
Non-Stick Wheel	Option	Option	Option	Option		Standard
Clean-Out Port	Option	Option				Standard
Disconnect Switches	Standard	Standard	Standard	Standard	Standard	Standard
Windband Extension	Option	Option			Option	
Birdscreen	Option	Option	Standard	Standard	Option	
Dampers	Option	Option	Option	Option		
Tie-Down Points	Option	Option			Option	Option
Speed Controllers		Option		Option		
UL 705	Option	Option	Option	Option	Standard	
UL 762	Option	Option	Option	Option		Standard
UL Emergency Smoke Control Systems					Standard	Option
Coatings	Option	Option	Option	Option	Option	Standard

Coatings — Wide variety of coatings and colors are available for decorative to protective applications.



Primer is applied at the factory to allow for final finish in the field. Not available on model USGF.



Permatector™ is our standard coating. Typically used for applications that require corrosion resistance in indoor and outdoor environments.



Hi-Pro Polyester is resistant to salt water, chemical fumes and moisture in more corrosive atmospheres. Typically used for applications that require superior chemical resistance, excellent abrasion and outdoor UV protection. This coating exceeds protective qualities of Air Dried Heresite and Air Dry Phenolic.




Baked Enamel Decorative Coatings are heat cured enamels applied either as wet paints or electrostatic powders. Customers can choose from 16 standard decorative colors or color match any color. *Note: colors are subject to change. See Performance Coatings for Commercial & Industrial Fans brochure for more details.*

Typical Installations by Application


General Clean Air/Fume Hood (Non Grease)

All CUBE, CUE, CWB and CW, exhaust fans are designed for applications ranging from clean air to contaminated air. A typical installation is shown. Sizes 95 and smaller can handle temperatures up to 130°F (54°C).


- When roofing materials extend to the top of the curb, roof curbs should be 1½-inches (¾-inch on a side) less than the unit curb cap to allow for roofing and flashing.
- For recommended duct size, damper size and roof opening dimensions, refer to the performance data pages.
- Installation must include a means for inspecting, cleaning and servicing the exhaust fan.



Models CUBE and CUE



Models CUBE and CUE




Models CWB and CW

Emergency Smoke Control

The S-CUBE is specifically designed for Emergency Smoke Control applications. These fans are UL/cUL Listed for Electrical and Power Ventilators for Smoke Control Systems for 500°F (260°C) for 4 hours and 1,000°F (538°C) for 15 minutes.

- Due to the varying airstreams encountered in commercial ventilation, system designers must be aware of national, state, and local codes and guidelines governing these installations. Local code authorities should be consulted before proceeding with any ventilation project.
- When roofing materials extend to the top of the curb, roof curbs should be 1.5-inches (¾-inch on a side) less than the unit curb cap to allow for roofing and flashing.
- For recommended duct size, damper size and roof opening dimensions, refer to the performance data pages.
- Installation must include a means for inspecting, cleaning and servicing the exhaust fan.
- Exhaust fans used in emergency smoke applications must have external wiring. (Wiring must not be installed in the airstream).




Models S-CUBE


Commercial Kitchen (Grease)

Models CUBE, CUE, CWB and CW, and sizes 098 and larger and all USGF fans are designed to meet restaurant and food service applications. These fans are UL/cUL Listed for grease removal and have been tested under high temperature [400°F (204°C)] and abnormal flare-up [600°F (316°C)] conditions.


- Due to high temperatures and grease-laden airstreams in commercial kitchen ventilation, system designers must be aware of governing codes and guidelines. The National Fire Protection Association (NFPA) is the primary source which governs many codes for commercial kitchen ventilation. Selected information from NFPA 96 is shown below. Local code authorities should be consulted before proceeding with any kitchen ventilation project.
- Exhaust fans used in kitchen ventilation applications must have external wiring. (Wiring must not be installed in the airstream).
- Installation must include a means for inspecting, cleaning and servicing the exhaust fan. Greenheck offers a Hinged Curb Cap option for upblast exhaust fans and the Hinged Base is standard on model USGF.
- No dampers are to be installed in the system.



**Models CUBE & CUE
Vented Installation**



**Models CUBE & CUE
Fire Wrapped Installation**





Models CWB & CW

Note: The typical installations shown on these two pages are recommendations based on national codes. Local authority may supersede these recommendations.




Severe-Duty Curbs Anchoring: for Hurricane and Seismic Fans

Concrete Deck Anchoring




Metal Building/Steel Deck Anchoring



Corner Detail for
all Severe-Duty
Deck Anchoring

Wood Deck Anchoring




Required Severe-Duty Curb to Roof Anchoring

Seismic Models		Hurricane	Square Dimensions			Concrete	Metal/ Steel	Wood
CUE Size	CUBE Size	*USGF Size	Fan Curb Cap	Roof Opening	Outside Flange	Fasteners Per Side		
060 - 075			17 (432)	10½ (267)	26 (660)	5	5	5
080 - 095			19(483)	12½ (318)	28 (711)	5	5	5
098 - 131	098 - 131		19 (483)	14½ (368)	28 (711)	5	5	5
141 - 161	141 - 161		22 (559)	18½ (470)	31 (787)	5	5	5
		140 - 160	26 (660)	18½ (470)	33 (838)	5	5	5
		180 - 200	30 (762)	20½ (521)	37 (940)	7	7	7
180 - 200	180 - 200		30 (762)	20½ (521)	39 (991)	7	7	7
	220 - 240		34 (864)	26½ (673)	43 (1092)	7	7	7
	300		40 (1016)	32½ (826)	49 (1245)	7	7	9
	360		46 (1168)	38½ (978)	55 (1397)	7	7	9
	420		52 (1321)	44½ (1130)	61 (1549)	7	7	9
	480		58 (1473)	50½ (1283)	67 (1702)	7	7	9

All dimensions in inches (millimeters). *The outside flange dimension shown above is for the GPF curbs. Subtract 2 inches (51mm) if the SD Curb is being used.

Required Severe-Duty Fan to Curb Mounting


Models CUBE, CUE and USGF



Seismic		Hurricane	Fasteners	
CUE Size	CUBE Size	USGF Size	Fasteners Per Side	Total Fasteners
060 - 161	098 - 161		3	12
180 - 200	180 - 240	140 - 200	5	20
			9	36
	300 - 480		5	20

Fasteners on each side of the fan are to be installed with one fastener 4 inches (102 mm) from each edge and one fastener centered. The remaining fasteners are to be equally spaced.

The Model number system is designed to completely identify the fan. The correct code letters must be specified to designate belt or direct drive. The remainder of the model number is determined by the size and performance.





Performance & Dimension Page Number by Model Size

Size	Belt Drive				Size	Direct Drive	
	CUBE	S-CUBE	USGF	CWB		CUE	CW
098	p. 18			p. 54	060		
101	p. 19	p. 19		p. 55	065	p. 45	p. 73
101HP	p. 20	p. 20		p. 56	070		
121	p. 21	p. 21		p. 57	075	p. 46	p. 74
131	p. 22	p. 22		p. 58	080		
140			p. 23		085	p. 47	p. 75
140HP			p. 24		090	p. 48	p. 76
141	p. 23	p. 23		p. 59	095	p. 49	p. 77
141HP	p. 24	p. 24		p. 60	098	p. 50	p. 78
160			p. 25		101		
160HP			p. 26		121	p. 51	p. 79
160XP			p. 27		131		
161	p. 25	p. 25		p. 61	141		
161HP	p. 26	p. 26		p. 62	141HP	p. 52	p. 80
161XP	p. 27				161		
180	p. 28		p. 28	p. 63	161HP		
180HP	p. 29		p. 29	p. 64	180		
200	p. 30	p. 30	p. 30	p. 65	180HP	p. 53	p. 81
200HP	p. 31		p. 31	p. 66	200		
220	p. 32			p. 67			
220HP	p. 33			p. 68			
240	p. 34	p. 34		p. 69			
240HP	p. 35			p. 70			
240XP	p. 36						
300	p. 37	p. 37		p. 71			
300HP	p. 38			p. 72			
300XP	p. 39						
360	p. 40	p. 40					
360HP	p. 41						
360XP	p. 42						
420	p. 43	p. 43					
480	p. 44	p. 44					

Roof Upblast - Belt Drive

Size-098: CUBE



CUBE

Damper Size = 12 x 12 (305 x 305)
 Roof Opening = 14 1/2 x 14 1/2 (368 x 368)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 58 lb (26 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																							
			0	0.05	0.1	0.125	0.2	0.25	0.375	0.5	0.625	0.75														
098-4	1/4	650	CFM	445	357	239																				
			BHP	0.01	0.01	0.01																				
			Sones	8.1	8.5	9.9																				
		755	CFM	516	442	352	301																			
			BHP	0.02	0.02	0.02	0.02																			
			Sones	8.3	8.4	8.9	9.3																			
		860	CFM	588	523	453	409	258																		
			BHP	0.02	0.02	0.02	0.02	0.02																		
			Sones	8.4	8.4	8.5	8.7	9.1																		
		965	CFM	660	600	543	509	392	294																	
			BHP	0.03	0.03	0.03	0.04	0.04	0.04																	
			Sones	8.7	8.6	8.6	8.5	8.6	8.6																	
		1070	CFM	732	677	627	600	500	428																	
			BHP	0.04	0.04	0.04	0.05	0.05	0.05																	
			Sones	8.9	8.8	8.6	8.6	8.4	8.4																	
		1175	CFM	804	752	708	684	603	537	350																
			BHP	0.06	0.06	0.06	0.06	0.06	0.06	0.06																
			Sones	9.3	9.2	9.0	8.9	8.7	8.6	8.2																
		1280	CFM	875	828	787	766	696	642	488																
			BHP	0.07	0.07	0.07	0.07	0.08	0.08	0.08																
			Sones	10.2	10.1	9.9	9.8	9.7	9.5	9.3																
		1385	CFM	947	903	864	845	785	738	603	448															
			BHP	0.09	0.09	0.09	0.09	0.10	0.10	0.10	0.10															
			Sones	11.2	11.1	10.9	10.8	10.7	10.6	10.4	10.3															
1490	CFM	1019	978	940	923	868	829	710	578	409																
	BHP	0.12	0.12	0.12	0.12	0.12	0.13	0.13	0.13	0.13																
	Sones	12.3	12.2	11.9	12.0	11.8	11.8	11.5	11.5	11.6																
1595	CFM	1091	1053	1016	1000	950	914	813	692	560																
	BHP	0.14	0.14	0.14	0.14	0.14	0.15	0.16	0.16	0.16																
	Sones	13.2	13.1	12.8	12.8	12.5	12.5	12.3	12.1	12.2																
1725	CFM	1180	1144	1109	1094	1049	1017	929	824	712	586															
	BHP	0.18	0.18	0.18	0.18	0.18	0.18	0.20	0.20	0.20	0.20															
	Sones	13.8	13.6	13.5	13.4	13.1	13.0	12.7	12.2	12.1	12.3															

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-101: CUBE • S-CUBE



CUBE • S-CUBE

Damper Size = 12 x 12 (305 x 305)
 Roof Opening = 14½ x 14½ (368 x 368)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 58 lb (26 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1	1.25										
101-4	1/4	860	CFM	732	625	481																
			BHP	0.03	0.04	0.04																
			Sones	4.6	2.4	0.6																
		958	CFM	815	722	609																
			BHP	0.04	0.05	0.05																
			Sones	5.5	4.5	3.3																
		1056	CFM	899	817	718	593															
			BHP	0.06	0.06	0.07	0.07															
			Sones	6.6	6.3	5.7	5.4															
		1154	CFM	982	910	821	724	574														
			BHP	0.07	0.08	0.09	0.09	0.08														
			Sones	7.3	7.1	6.6	6.1	5.8														
		1252	CFM	1066	1000	920	834	732														
			BHP	0.09	0.10	0.11	0.11	0.11														
			Sones	8.0	8.0	7.6	6.9	6.5														
		1350	CFM	1149	1089	1016	940	856	745													
BHP	0.12		0.13	0.13	0.14	0.14	0.14															
Sones	8.9		8.9	8.6	8.1	7.5	7.0															
1448	CFM	1233	1176	1112	1040	966	886	763														
	BHP	0.14	0.15	0.16	0.17	0.17	0.17	0.17														
	Sones	10.3	10.2	9.9	9.5	9.0	8.3	8.0														
1546	CFM	1316	1264	1206	1139	1072	999	915	820													
	BHP	0.17	0.19	0.20	0.20	0.21	0.21	0.21	0.21													
	Sones	11.8	11.5	11.3	10.9	10.5	9.8	9.3	9.0													
1660	CFM	1413	1365	1313	1251	1189	1125	1056	974	861												
	BHP	0.22	0.23	0.24	0.25	0.26	0.26	0.26	0.26	0.25												
	Sones	12.7	12.3	12.0	11.6	11.3	10.8	10.2	9.6	9.4												
101-3	1/3	1740	CFM	1481	1435	1386	1329	1270	1210	1146	1093	991										
			BHP	0.25	0.26	0.27	0.28	0.29	0.30	0.30	0.30	0.30										
			Sones	13.4	13.0	12.6	12.1	11.8	11.4	10.9	10.5	9.7										
		1820	CFM	1549	1505	1459	1406	1350	1293	1234	1184	1106	900									
			BHP	0.28	0.30	0.31	0.32	0.33	0.34	0.35	0.35	0.35	0.33									
			Sones	14.3	13.7	13.4	12.7	12.4	12.0	11.6	11.3	10.6	10.1									

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-101HP: CUBE • S-CUBE



CUBE • S-CUBE

Damper Size = 12 x 12 (305 x 305)
 Roof Opening = 14 1/2 x 14 1/2 (368 x 368)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 58 lb (26 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																				
			0.5	0.625	0.75	1	1.25	1.5	1.75	2	2.25	2.5											
101HP-4	1/4	1300	CFM	335	182																		
			BHP	0.07	0.06																		
			Sones	6.0	6.3																		
		1420	CFM	419	350	191																	
			BHP	0.09	0.09	0.07																	
			Sones	6.8	6.6	6.9																	
		1540	CFM	491	438	371																	
			BHP	0.11	0.11	0.11																	
			Sones	7.8	7.5	7.3																	
		1660	CFM	560	512	461	262																
			BHP	0.14	0.14	0.14	0.12																
			Sones	8.9	8.6	8.4	8.3																
1780	CFM	627	583	538	430																		
	BHP	0.17	0.17	0.17	0.17																		
	Sones	10.3	9.9	9.6	9.1																		
1900	CFM	688	651	610	520	382																	
	BHP	0.20	0.21	0.21	0.21	0.19																	
	Sones	12.1	11.4	11.0	10.5	10.2																	
2045	CFM	761	729	693	615	522	346																
	BHP	0.24	0.26	0.26	0.26	0.26	0.23																
	Sones	13.9	13.5	12.7	12.1	11.5	11.4																
101HP-3	1/3	2150	CFM	812	782	752	678	600	500														
			BHP	0.28	0.29	0.30	0.30	0.30	0.30														
			Sones	14.1	14.1	13.5	12.5	12.0	11.5														
2250	CFM	860	832	804	737	665	579	456															
	BHP	0.32	0.33	0.34	0.35	0.35	0.35	0.32															
	Sones	14.4	14.4	14.2	13.2	12.5	11.9	11.6															
101HP-5	1/2	2415	CFM	938	914	887	831	765	697	614	498												
			BHP	0.39	0.39	0.41	0.43	0.43	0.43	0.43	0.40												
			Sones	15.1	15.0	15.0	14.5	13.7	12.9	12.2	12.0												
		2580	CFM	1014	992	969	919	861	799	735	655	550	323										
			BHP	0.48	0.48	0.49	0.52	0.53	0.53	0.53	0.53	0.49	0.43										
			Sones	16.8	16.4	16.0	15.7	15.1	14.4	13.7	13.2	12.9	12.5										

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-121: CUBE • S-CUBE



CUBE • S-CUBE

Damper Size = 12 x 12 (305 x 305)
 Roof Opening = 14½ x 14½ (368 x 368)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 66 lb (30 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0	0.125	0.25	0.375	0.5	0.625	0.75	1	1.25	1.5										
121-4	1/4	685	CFM	809	670																	
			BHP	0.02	0.03																	
			Sones	4.4	4.4																	
		798	CFM	942	824	680																
			BHP	0.04	0.04	0.05																
			Sones	5.0	5.2	5.2																
		911	CFM	1076	971	861	703															
			BHP	0.06	0.06	0.07	0.07															
			Sones	5.6	6.0	6.0	6.0															
		1024	CFM	1209	1115	1025	910	755														
			BHP	0.08	0.09	0.10	0.10	0.10														
			Sones	6.4	6.8	7.0	6.9	6.9														
1137	CFM	1343	1257	1176	1087	976	825															
	BHP	0.11	0.12	0.13	0.13	0.14	0.13															
	Sones	7.3	7.8	8.1	8.2	8.0	8.1															
1250	CFM	1476	1397	1323	1250	1159	1053	916														
	BHP	0.15	0.16	0.17	0.17	0.18	0.18	0.18														
	Sones	8.8	9.3	9.9	9.9	10.0	9.8	9.8														
1410	CFM	1665	1595	1528	1463	1398	1315	1224	965													
	BHP	0.21	0.22	0.23	0.24	0.25	0.26	0.26	0.25													
	Sones	11.1	11.6	12.2	12.5	12.6	12.7	12.7	12.3													
121-3	1/3	CFM	1748	1681	1617	1555	1493	1421	1338	1132												
		BHP	0.25	0.26	0.27	0.28	0.29	0.29	0.30	0.30												
		Sones	11.9	12.4	13.1	13.5	13.7	13.8	13.8	13.6												
1545	CFM	1824	1760	1699	1639	1580	1518	1441	1262	990												
	BHP	0.28	0.29	0.30	0.31	0.32	0.33	0.34	0.34	0.33												
	Sones	12.8	13.4	14.0	14.5	14.7	14.8	14.9	14.9	14.6												
121-5	1/2	CFM	1931	1870	1811	1755	1699	1643	1577	1424	1226											
		BHP	0.33	0.34	0.36	0.37	0.38	0.39	0.40	0.41	0.4											
		Sones	14.1	14.7	15.2	15.9	16.2	16.4	16.6	16.7	16.5											
1725	CFM	2037	1979	1923	1869	1816	1763	1710	1571	1406	1176											
	BHP	0.39	0.40	0.41	0.43	0.44	0.45	0.46	0.47	0.48	0.46											
	Sones	15.6	16.1	16.7	17.3	17.9	18.2	18.4	18.7	18.6	18.4											

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-131: CUBE • S-CUBE



CUBE • S-CUBE

Damper Size = 12 x 12 (305 x 305)
 Roof Opening = 14 1/2 x 14 1/2 (368 x 368)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 66 lb (30 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.



Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1	1.25										
131-4	1/4	650	CFM	892	724																	
			BHP	0.03	0.03																	
			Sones	6.2	6.0																	
		780	CFM	1070	935	756																
			BHP	0.05	0.05	0.06																
			Sones	7.5	7.3	6.6																
	910	CFM	1248	1133	1007	819																
		BHP	0.07	0.08	0.09	0.09																
		Sones	9.3	9.1	8.5	7.7																
		1040	CFM	1426	1325	1222	1094	919														
			BHP	0.11	0.12	0.13	0.13	0.13														
			Sones	11.3	11.0	10.5	9.8	9.0														
1170	CFM	1605	1515	1425	1329	1204	1045															
	BHP	0.16	0.17	0.18	0.18	0.19	0.18															
	Sones	12.9	12.6	12.2	11.7	10.8	10.1															
131-3	1/3	1305	CFM	1790	1709	1629	1547	1458	1340	1201	1003											
			BHP	0.22	0.23	0.24	0.25	0.26	0.26	0.26	0.26	0.24										
			Sones	14.6	14.3	13.9	13.5	13.0	12.0	11.5	10.8											
		1435	CFM	1968	1895	1822	1749	1671	1586	1479	1358	1198										
			BHP	0.29	0.30	0.31	0.32	0.33	0.34	0.35	0.34	0.33										
			Sones	15.7	15.5	15.1	14.8	14.3	13.8	13.1	12.5	11.9										
131-5	1/2	1487	CFM	2039	1969	1898	1828	1754	1677	1579	1471	1339										
			BHP	0.32	0.33	0.34	0.36	0.37	0.38	0.38	0.38	0.38										
			Sones	16.2	15.9	15.7	15.4	14.9	14.5	13.9	13.2	12.7										
		1540	CFM	2112	2044	1976	1908	1838	1764	1678	1577	1465										
			BHP	0.35	0.37	0.38	0.39	0.41	0.42	0.42	0.42	0.43	0.43									
			Sones	16.7	16.5	16.2	16.0	15.6	15.2	14.6	14.0	13.4										
	1592	CFM	2183	2117	2052	1986	1920	1848	1774	1678	1578	1301										
		BHP	0.39	0.41	0.42	0.43	0.44	0.46	0.47	0.47	0.47	0.45										
		Sones	17.3	17.0	16.8	16.6	16.2	15.8	15.3	14.8	14.3	13.0										
	1645	CFM	2256	2192	2128	2065	2001	1933	1864	1778	1684	1455										
		BHP	0.43	0.45	0.46	0.47	0.49	0.50	0.51	0.52	0.52	0.51										
		Sones	17.9	17.6	17.4	17.2	16.9	16.5	16.1	15.6	15.1	13.9										

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-140: USGF only

Size-141: CUBE • S-CUBE



CUBE • S-CUBE

Damper Size = 16 x 16 (406 x 406)
 Roof Opening = 18 1/2 x 18 1/2 (470 x 470)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 84 lb (38 kg)

USGF

Roof Opening = 18 1/2 x 18 1/2 (470 x 470)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 125 lb (57 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.



Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0	0.125	0.25	0.375	0.5	0.75	1	1.25	1.5	1.75										
141-4	1/4	590	CFM	1069	851																	
			BHP	0.04	0.04																	
			Sones	5.0	4.5																	
		715	CFM	1295	1130	885																
			BHP	0.06	0.07	0.07																
			Sones	6.0	6.0	5.1																
	840	CFM	1521	1387	1217	969																
		BHP	0.10	0.11	0.11	0.11																
		Sones	7.1	7.3	6.8	6.2																
	965	CFM	1748	1635	1499	1333	1103															
		BHP	0.15	0.16	0.17	0.17	0.17															
		Sones	8.6	8.7	8.5	8.1	7.7															
1105	CFM	2001	1906	1793	1667	1515	998															
	BHP	0.23	0.24	0.25	0.26	0.26	0.23															
	Sones	10.9	10.8	10.6	10.3	10.0	9.6															
141-3	1/3	1210	CFM	2192	2106	2006	1896	1773	1443													
			BHP	0.30	0.31	0.32	0.33	0.34	0.34													
			Sones	12.2	12.2	11.7	11.6	11.2	10.9													
141-5	1/2	1290	CFM	2337	2258	2166	2065	1957	1691	1221												
			BHP	0.36	0.38	0.39	0.40	0.41	0.42	0.37												
			Sones	13.2	13.3	12.7	12.6	12.3	12.0	11.3												
141-7	3/4	1390	CFM	2518	2445	2362	2271	2174	1949	1643												
			BHP	0.45	0.47	0.48	0.50	0.51	0.52	0.51												
			Sones	14.9	14.7	14.2	13.2	12.9	12.1	11.0												
141-7	3/4	1495	CFM	2708	2640	2565	2483	2396	2202	1967	1617											
			BHP	0.56	0.58	0.60	0.61	0.62	0.64	0.65	0.61											
			Sones	17.2	16.5	16.3	15.6	13.9	12.5	12.2	10.8											
141-10	1	1595	CFM	2889	2826	2757	2683	2602	2430	2225	1968	1568										
			BHP	0.69	0.70	0.72	0.74	0.75	0.77	0.79	0.78	0.72										
			Sones	20	19.0	18.5	19.5	16.1	13.3	12.3	12.6	11.6										
141-10	1	1725	CFM	3125	3066	3005	2936	2865	2711	2539	2339	2085	1704									
			BHP	0.87	0.88	0.90	0.92	0.94	0.97	0.99	1.00	0.98	0.91									
			Sones	26	23	22	24	24	15.1	13.4	14.3	13.8	13.8									

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-140HP: USGF only

Size-141HP: CUBE • S-CUBE



CUBE • S-CUBE

Damper Size = 16 x 16 (406 x 406)
 Roof Opening = 18½ x 18½ (470 x 470)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 84 lb (38 kg)

USGF

Roof Opening = 18½ x 18½ (470 x 470)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 125 lb (57 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0.5	0.75	1	1.25	1.5	1.75	2	2.25	2.5	2.75										
141HP-4	1/4	895	CFM	331																		
			BHP	0.06																		
			Sones	6.1																		
		1037	CFM	566																		
			BHP	0.10																		
			Sones	6.7																		
	1179	CFM	733	563																		
		BHP	0.13	0.14																		
		Sones	8.9	9.2																		
		1321	CFM	878	756	591																
			BHP	0.18	0.19	0.19																
			Sones	12.1	11.6	13.6																
1465	CFM	1016	920	798	642																	
	BHP	0.24	0.26	0.26	0.26																	
	Sones	14.2	13.5	13.2	15.5																	
141HP-3	1/3	CFM	1146	1063	965	846	704															
		BHP	0.31	0.33	0.34	0.34	0.34															
		Sones	15.2	14.4	14.2	14.0	15.2															
141HP-5	1/2	1725	CFM	1256	1178	1098	999	879	747													
			BHP	0.38	0.40	0.42	0.43	0.43	0.42													
			Sones	16.1	15.4	15.0	14.9	14.7	15.7													
		1845	CFM	1363	1292	1219	1137	1042	924	800												
			BHP	0.46	0.48	0.50	0.52	0.52	0.52	0.51												
			Sones	17.0	16.6	16.2	16.0	15.9	15.6	16.1												
141HP-7	3/4	1960	CFM	1463	1399	1330	1260	1176	1086	970	854											
			BHP	0.54	0.57	0.59	0.61	0.62	0.63	0.62	0.62											
			Sones	18.1	17.7	17.4	17.2	17.1	17.0	16.8	16.9											
		2035	CFM	1528	1468	1402	1335	1261	1175	1077	965	826										
			BHP	0.60	0.63	0.66	0.68	0.69	0.70	0.70	0.69	0.67										
			Sones	18.9	18.5	18.2	18.0	18.0	17.8	17.7	17.5	17.8										
		2110	CFM	1592	1536	1473	1409	1341	1262	1178	1073	965	804									
			BHP	0.67	0.70	0.72	0.75	0.77	0.78	0.78	0.78	0.77	0.73									
			Sones	19.8	19.3	19.1	19.0	18.9	18.8	18.6	18.5	18.3	20									



MAXIMUM BHP AT A GIVEN RPM = (RPM/2285)³
 MAXIMUM RPM = 2110
 TIP SPEED (ft/min) = RPM x 3.829
 MAXIMUM MOTOR FRAME SIZE = 145T
 AVERAGE DISCHARGE VELOCITY (FPM) = CFM/1.72

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-160: USGF only

Size-161: CUBE • S-CUBE



CUBE • S-CUBE

Damper Size = 16 x 16 (406 x 406)
 Roof Opening = 18½ x 18½ (470 x 470)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 87 lb (39 kg)

USGF

Roof Opening = 18½ x 18½ (470 x 470)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 131 lb (59 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see page 82-87.



Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg														
			0	0.125	0.25	0.375	0.5	0.625	0.75	1	1.25	1.5					
161-4	1/4	730	CFM	2098	1905	1669	1389	MAXIMUM BHP AT A GIVEN RPM = (RPM/1365) ³ MAXIMUM RPM = 1390 TIP SPEED (ft/min) = RPM x 4.352 MAXIMUM MOTOR FRAME SIZE = 145T AVERAGE DISCHARGE VELOCITY (FPM) = CFM/1.72									
			BHP	0.13	0.15	0.15	0.15										
			Sones	8.1	8.0	7.8	7.8										
		778	CFM	2236	2058	1843	1596										
			BHP	0.16	0.18	0.19	0.18										
			Sones	8.9	8.7	8.5	8.4										
	826	CFM	2374	2209	2010	1790	1512										
		BHP	0.20	0.22	0.22	0.22	0.21										
		Sones	9.9	9.6	9.3	9.1	9.0										
875	CFM	2515	2362	2177	1974	1744	1365										
	BHP	0.23	0.26	0.26	0.26	0.26	0.24										
	Sones	11.0	10.6	10.1	9.9	9.7	9.7										
161-3	1/3	965	CFM	2774	2637	2477	2300	2109	1893	1584							
			BHP	0.31	0.34	0.35	0.35	0.35	0.34	0.33							
			Sones	12.4	12.0	11.5	11.2	10.8	10.6	10.5							
161-5	1/2	1038	CFM	2984	2857	2712	2552	2382	2199	1992							
			BHP	0.39	0.42	0.43	0.44	0.44	0.43	0.43							
			Sones	13.7	13.3	12.8	12.4	12.1	11.8	11.6							
		1110	CFM	3191	3072	2941	2796	2641	2475	2297	1770						
			BHP	0.47	0.51	0.53	0.53	0.54	0.53	0.52	0.49						
			Sones	15.0	14.6	14.2	13.8	13.5	13.1	12.9	12.2						
161-7	3/4	1188	CFM	3415	3304	3186	3053	2911	2764	2606	2246						
			BHP	0.58	0.62	0.64	0.65	0.65	0.66	0.65	0.64						
			Sones	16.7	16.3	15.8	15.4	15.0	14.7	14.5	14.0						
		1265	CFM	3636	3532	3426	3301	3172	3036	2894	2583	2163					
			BHP	0.70	0.74	0.77	0.78	0.79	0.79	0.79	0.78	0.75					
			Sones	18.5	18.1	17.7	17.2	16.8	16.5	16.3	15.8	15.2					
161-10	1	1328	CFM	3817	3718	3619	3502	3383	3253	3124	2843	2510					
			BHP	0.81	0.85	0.89	0.90	0.91	0.91	0.92	0.90	0.89					
			Sones	20	19.6	19.2	18.7	18.3	18.0	17.8	17.4	16.9					
		1390	CFM	3996	3901	3806	3698	3584	3464	3340	3078	2785	2394				
			BHP	0.93	0.97	1.01	1.03	1.04	1.04	1.05	1.04	1.03	1.00				
			Sones	22	21	21	20	19.9	19.6	19.4	19.0	18.6	18.0				

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-160HP: USGF only

Size-161HP: CUBE • S-CUBE



CUBE • S-CUBE

Damper Size = 16 x 16 (406 x 406)
 Roof Opening = 18½ x 18½ (470 x 470)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 87 lb (39 kg)

USGF

Roof Opening = 18½ x 18½ (470 x 470)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 131 lb (59 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.



Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																					
			0.5	0.625	0.75	0.875	1	1.25	1.5	1.75	2	2.25												
161HP-4	1/4	825	CFM	889																				
			BHP	0.12																				
			Sones	7.0																				
		910	CFM	1129	956																			
			BHP	0.16	0.16																			
			Sones	8.3	7.8																			
	995	CFM	1331	1208	1042																			
		BHP	0.21	0.21	0.21																			
		Sones	9.6	9.3	8.8																			
1065	CFM	1487	1377	1252	1093																			
	BHP	0.25	0.26	0.26	0.26																			
	Sones	11.0	10.6	10.2	9.8																			
161HP-3	1/3	1165	CFM	1697	1608	1504	1395	1252																
			BHP	0.32	0.33	0.34	0.34	0.34																
			Sones	12.8	12.7	12.2	11.7	11.3																
161HP-5	1/2	1255	CFM	1882	1799	1715	1617	1519	1218															
			BHP	0.40	0.41	0.42	0.43	0.43	0.42															
			Sones	13.1	12.8	12.5	12.0	11.5	10.6															
		1340	CFM	2053	1975	1897	1816	1724	1513															
			BHP	0.48	0.49	0.50	0.51	0.52	0.52															
			Sones	14.4	13.8	13.3	12.8	12.3	11.3															
161HP-7	3/4	1441	CFM	2253	2180	2108	2036	1961	1790	1577														
			BHP	0.59	0.60	0.61	0.63	0.64	0.65	0.65														
			Sones	16.3	15.8	15.2	14.7	14.3	13.5	12.3														
		1535	CFM	2433	2368	2301	2233	2165	2015	1855	1638													
			BHP	0.70	0.72	0.73	0.74	0.76	0.78	0.79	0.78													
			Sones	18.1	17.7	17.2	16.8	16.4	15.7	14.9	13.5													
161HP-10	1	1610	CFM	2573	2516	2452	2387	2322	2190	2037	1863	1651												
			BHP	0.80	0.82	0.83	0.85	0.86	0.89	0.90	0.91	0.90												
			Sones	19.6	19.2	18.8	18.4	18.1	17.5	16.9	15.8	14.3												
		1690	CFM	2722	2671	2611	2550	2488	2365	2228	2082	1899	1664											
			BHP	0.92	0.94	0.95	0.97	0.98	1.01	1.03	1.05	1.05	1.03											
			Sones	21	21	21	20	20	19.5	19.1	18.6	16.9	15.0											

MAXIMUM BHP AT A GIVEN RPM = (RPM/1660)³
 MAXIMUM RPM = 1690
 TIP SPEED (ft/min) = RPM x 4.352
 MAXIMUM MOTOR FRAME SIZE = 145T
 AVERAGE DISCHARGE VELOCITY (FPM) = CFM/1.72

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-180: CUBE • USGF



CUBE

Damper Size = 18 x 18 (457 x 457)
 Roof Opening = 20½ x 20½ (521 x 521)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 126 lb (57 kg)

USGF



Roof Opening = 20½ x 20½ (521 x 521)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 190 lb (86 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0	0.125	0.25	0.5	0.75	1	1.25	1.5	1.75	2										
180-4	1/4	630	CFM	2380	2154	1861																
			BHP	0.13	0.15	0.16																
			Sones	7.1	6.4	5.5																
		745	CFM	2815	2617	2448	1763															
			BHP	0.22	0.24	0.26	0.25															
			Sones	9.2	8.6	8.1	7.1															
180-3	1/3	820	CFM	3098	2916	2759	2257															
			BHP	0.30	0.32	0.34	0.34															
			Sones	11.2	10.4	10.0	9.0															
180-5	1/2	940	CFM	3551	3389	3243	2879	2363														
			BHP	0.45	0.47	0.49	0.52	0.50														
			Sones	13.8	13.5	13.1	12.4	11.2														
180-7	3/4	1010	CFM	3816	3664	3526	3242	2799	2105													
			BHP	0.56	0.58	0.61	0.65	0.64	0.58													
			Sones	15.4	15.2	14.9	14.7	13.7	11.8													
		1075	CFM	4061	3919	3786	3554	3141	2652													
			BHP	0.67	0.70	0.73	0.78	0.78	0.75													
			Sones	16.5	16.2	15.8	15.5	14.7	13.3													
180-10	1	1185	CFM	4477	4348	4224	4005	3703	3336	2841												
			BHP	0.90	0.93	0.96	1.01	1.04	1.04	0.99												
			Sones	18.5	17.9	17.1	16.5	16.0	15.2	14.4												
180-15	1½	1275	CFM	4817	4697	4578	4369	4163	3799	3437	2930											
			BHP	1.12	1.15	1.19	1.24	1.30	1.30	1.28	1.22											
			Sones	21	20	19.5	18.7	18.2	17.5	16.7	15.9											
		1360	CFM	5138	5026	4913	4710	4532	4232	3912	3537	3023										
			BHP	1.36	1.39	1.43	1.49	1.56	1.58	1.58	1.54	1.46										
			Sones	23	23	22	21	21	20	19.2	18.3	17.3										
180-20	2	1430	CFM	5402	5296	5189	4993	4819	4593	4270	3968	3567	3001									
			BHP	1.58	1.62	1.66	1.72	1.79	1.83	1.83	1.83	1.76	1.66									
			Sones	25	25	25	24	23	22	22	21	19.5	18.2									
		1495	CFM	5648	5546	5443	5254	5082	4921	4598	4313	3983	3564									
			BHP	1.80	1.84	1.89	1.96	2.02	2.10	2.10	2.10	2.06	1.99									
			Sones	28	27	27	26	25	25	24	23	22	21									

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive Size-180HP: CUBE • USGF



CUBE

Damper Size = 18 x 18 (457 x 457)
 Roof Opening = 20 1/2 x 20 1/2 (521 x 521)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 126 lb (57 kg)

USGF

Roof Opening = 20 1/2 x 20 1/2 (521 x 521)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 190 lb (86 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0.5	0.75	1	1.25	1.5	1.75	2	2.25	2.5	2.75										
180HP-4	1/4	795	CFM	1570																		
			BHP	0.22																		
			Sones	8.3																		
		845	CFM	1799																		
			BHP	0.26																		
			Sones	9.5																		
180HP-3	1/3	925	CFM	2104	1688																	
			BHP	0.34	0.35																	
			Sones	10.8	9.8																	
180HP-5	1/2	1065	CFM	2581	2323	1933																
			BHP	0.50	0.52	0.53																
			Sones	13.8	12.5	12.4																
180HP-7	3/4	1215	CFM	3063	2868	2626	2286	1854														
			BHP	0.72	0.76	0.78	0.79	0.75														
			Sones	15.0	14.5	14.0	13.4	12.9														
180HP-10	1	1275	CFM	3253	3066	2853	2566	2209														
			BHP	0.82	0.87	0.89	0.91	0.89														
			Sones	16.7	15.8	15.4	14.9	14.3														
		1335	CFM	3441	3261	3075	2839	2523	2156													
			BHP	0.93	0.98	1.02	1.04	1.04	1.04													
			Sones	18.7	17.4	17.0	16.6	16.1	15.6													
180HP-15	1 1/2	1430	CFM	3735	3566	3401	3206	2964	2669	2320												
			BHP	1.13	1.19	1.23	1.26	1.27	1.28	1.24												
			Sones	22	21	19.7	19.3	18.9	18.4	17.9												
		1530	CFM	4005	3853	3696	3538	3338	3089	2807	2479											
			BHP	1.34	1.40	1.46	1.50	1.52	1.53	1.54	1.49											
			Sones	23	22	21	21	20	19.7	19.1	18.4											
180HP-20	2	1610	CFM	4273	4136	3986	3840	3674	3485	3233	2965	2656										
			BHP	1.58	1.64	1.70	1.76	1.79	1.81	1.82	1.82	1.78										
			Sones	25	24	23	23	22	21	21	20	19.2										
		1685	CFM	4495	4369	4226	4085	3945	3768	3575	3325	3061	2766									
			BHP	1.79	1.86	1.93	1.99	2.04	2.07	2.08	2.09	2.08	2.04									
			Sones	27	26	25	26	24	23	22	21	21	20									

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-200: CUBE • S-CUBE • USGF



CUBE • S-CUBE

Damper Size = 18 x 18 (457 x 457)
 Roof Opening = 20½ x 20½ (521 x 521)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 142 lb (64 kg)

USGF

Roof Opening = 20½ x 20½ (521 x 521)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 213 lb (97 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																		
			0	0.125	0.25	0.375	0.5	0.75	1	1.25	1.5	1.75									
200-4	1/4	500	CFM	2812	2386	1822															
			BHP	0.14	0.15	0.15															
			Sones	6.2	5.4	4.6															
		605	CFM	3403	3054	2675	2144														
			BHP	0.25	0.26	0.26	0.25														
			Sones	8.1	7.4	6.7	6.1														
200-3	1/3	665	CFM	3740	3422	3096	2699	2073													
			BHP	0.33	0.34	0.35	0.35	0.33													
			Sones	9.4	8.8	8.1	7.5	7.0													
200-5	1/2	760	CFM	4275	3994	3718	3413	3048													
			BHP	0.49	0.51	0.52	0.52	0.51													
			Sones	12.1	11.7	10.9	10.1	9.4													
200-7	3/4	820	CFM	4612	4350	4098	3828	3523	2606												
			BHP	0.61	0.63	0.65	0.65	0.65	0.61												
			Sones	14.1	14.1	13.0	12.2	11.4	10.7												
		875	CFM	4922	4676	4439	4192	3922	3240												
			BHP	0.75	0.77	0.78	0.79	0.79	0.78												
			Sones	16.3	16.3	15.2	14.7	13.5	12.4												
200-10	1	960	CFM	5400	5176	4958	4742	4508	3985	3169											
			BHP	0.98	1.01	1.03	1.04	1.04	1.04	1.00											
			Sones	18.7	18.4	17.7	17.0	16.4	15.0	14.4											
200-15	1½	1030	CFM	5793	5585	5380	5179	4968	4503	3917	2972										
			BHP	1.22	1.24	1.26	1.28	1.29	1.29	1.27	1.18										
			Sones	21	21	20	19.2	18.7	17.5	16.4	16.8										
		1100	CFM	6187	5992	5798	5610	5421	5006	4529	3861										
			BHP	1.48	1.51	1.53	1.55	1.57	1.57	1.57	1.53										
			Sones	23	23	23	22	21	20	19.3	18.6										
200-20	2	1155	CFM	6496	6311	6125	5946	5767	5383	4948	4410	3629									
			BHP	1.72	1.74	1.77	1.79	1.81	1.81	1.81	1.80	1.71									
			Sones	24	24	23	23	22	21	20	19.2	19.9									
		1210	CFM	6806	6628	6451	6279	6108	5748	5350	4892	4289	3365								
			BHP	1.97	2.00	2.03	2.05	2.07	2.09	2.09	2.08	2.04	1.88								
			Sones	25	24	23	23	22	21	21	19.8	19.7	21								

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-200HP: CUBE • USGF



CUBE

Damper Size = 18 x 18 (457 x 457)
 Roof Opening = 20½ x 20½ (521 x 521)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 142 lb (64 kg)

USGF

Roof Opening = 20½ x 20½ (521 x 521)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 213 lb (97 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.



Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																								
			0.5	0.75	1	1.25	1.5	1.75	2	2.25	2.5	2.75															
200HP-5	1/2	740	CFM	2024																							
			BHP	0.31																							
			Sones	8.1																							
		880	CFM	2779	2317																						
			BHP	0.51	0.52																						
			Sones	10.5	9.5																						
200HP-7	3/4	945	CFM	3094	2711	2092																					
			BHP	0.62	0.64	0.62																					
			Sones	12.2	11.5	10.6																					
		1010	CFM	3397	3067	2637																					
			BHP	0.75	0.78	0.79																					
			Sones	14.5	13.7	13.2																					
200HP-10	1	1110	CFM	3851	3561	3242	2806																				
			BHP	0.98	1.02	1.04	1.04																				
			Sones	16.9	16.2	15.7	15.5																				
200HP-15	1½	1190	CFM	4207	3944	3661	3321	2850																			
			BHP	1.20	1.24	1.27	1.29	1.26																			
			Sones	19.0	18.1	17.5	17.3	17.5																			
		1270	CFM	4558	4312	4055	3789	3433	2944																		
			BHP	1.44	1.49	1.53	1.56	1.56	1.53																		
			Sones	22	21	20	19.7	19.3	19.8																		
200HP-20	2	1335	CFM	4837	4606	4369	4116	3826	3482	2946																	
			BHP	1.67	1.71	1.76	1.79	1.82	1.82	1.75																	
			Sones	23	23	22	21	21	21	22																	
		1400	CFM	5110	4898	4674	4436	4195	3880	3515																	
			BHP	1.91	1.96	2.01	2.05	2.09	2.09	2.08																	
			Sones	24	24	24	23	21	22	23																	
200HP-30	3	1465	CFM	5382	5186	4972	4752	4521	4269	3956	3556																
			BHP	2.18	2.23	2.28	2.33	2.37	2.40	2.40	2.37																
			Sones	26	25	25	25	23	23	24	25																
		1600	CFM	5943	5775	5581	5385	5182	4971	4760	4476	4189	3760														
			BHP	2.81	2.88	2.93	2.99	3.03	3.08	3.13	3.13	3.13	3.06														
			Sones	29	28	29	30	29	26	24	26	28	31														

MAXIMUM BHP AT A GIVEN RPM = (RPM/1093)³
 MAXIMUM RPM = 1600
 TIP SPEED (ft/min) = RPM x 5.595
 MAXIMUM MOTOR FRAME SIZE = 184T
 AVERAGE DISCHARGE VELOCITY (FPM) = CFM/2.92

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-220: CUBE



CUBE

Damper Size = 24 x 24 (610 x 610)
 Roof Opening = 26½ x 26½ (521 x 521)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.051 (1.3)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 174 lb (79 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.



Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg														
			0	0.125	0.25	0.375	0.5	0.625	0.75	1	1.25	1.5					
220-4	1/4	450	CFM	3585	3155	2624											
			BHP	0.19	0.21	0.22											
			Sones	7.3	6.6	6.0											
		475	CFM	3784	3377	2896	2268										
			BHP	0.23	0.25	0.26	0.25										
			Sones	7.9	7.2	6.5	6.1										
220-3	1/3	520	CFM	4142	3771	3357	2845										
			BHP	0.30	0.32	0.34	0.34										
			Sones	9.3	8.4	7.6	7.1										
220-5	1/2	600	CFM	4779	4457	4124	3736	3279									
			BHP	0.46	0.48	0.51	0.52	0.52									
			Sones	12.0	11.0	10.0	9.3	8.8									
220-7	3/4	645	CFM	5138	4838	4539	4194	3811	3346								
			BHP	0.57	0.60	0.63	0.64	0.65	0.64								
			Sones	13.4	12.6	11.8	11.1	10.4	9.9								
		685	CFM	5457	5174	4893	4581	4234	3836	3383							
			BHP	0.68	0.71	0.74	0.76	0.78	0.78	0.77							
			Sones	14.8	14.0	13.4	12.9	12.1	11.6	11.1							
220-10	1	755	CFM	6014	5758	5502	5239	4944	4620	4258							
			BHP	0.91	0.94	0.98	1.01	1.03	1.04	1.04							
			Sones	17.3	16.7	16.3	16.0	15.5	14.8	14.3							
220-15	1½	810	CFM	6452	6213	5975	5737	5470	5185	4883	4156						
			BHP	1.13	1.16	1.20	1.24	1.26	1.28	1.29	1.27						
			Sones	18.7	18.1	17.7	17.3	16.9	16.2	15.6	14.7						
		865	CFM	6890	6667	6443	6220	5987	5729	5453	4835	4111					
			BHP	1.37	1.41	1.45	1.49	1.52	1.54	1.56	1.57	1.53					
			Sones	20	19.9	19.3	18.9	18.5	17.8	17.2	16.3	15.9					
220-20	2	910	CFM	7249	7036	6823	6612	6400	6158	5909	5365	4704					
			BHP	1.60	1.64	1.68	1.72	1.76	1.78	1.81	1.83	1.81					
			Sones	23	22	22	21	21	19.9	19.1	18.0	17.1					
		955	CFM	7607	7405	7202	7000	6799	6580	6347	5844	5261	4602				
			BHP	1.85	1.89	1.93	1.97	2.02	2.05	2.07	2.11	2.11	2.07				
			Sones	25	25	24	24	23	23	22	20	19.0	18.6				

MAXIMUM BHP AT A GIVEN RPM = (RPM/743)³
 MAXIMUM RPM = 955
 TIP SPEED (ft/min) = RPM x 6.413
 MAXIMUM MOTOR FRAME SIZE = 184T
 AVERAGE DISCHARGE VELOCITY (FPM) = CFM/3.76

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-220HP: CUBE



CUBE

- Damper Size = 24 x 24 (610 x 610)
- Roof Opening = 26½ x 26½ (673 x 673)
- Windband Thickness = 0.064 (1.6)
- Motor Cover Thickness = 0.051 (1.3)
- Curb Cap Thickness = 0.064 (1.6)
- ^Approximate Unit Weight = 174 lb (79 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0.5	0.75	1	1.25	1.5	1.75	2	2.25	2.5	2.75										
220HP-5	1/2	650	CFM	2909	1940																	
			BHP	0.45	0.42																	
			Sones	8.6	7.5																	
		680	CFM	3151	2405																	
			BHP	0.51	0.51																	
			Sones	9.6	8.6																	
220HP-7	3/4	735	CFM	3582	3006																	
			BHP	0.63	0.65																	
			Sones	11.7	10.8																	
		780	CFM	3902	3427	2716																
			BHP	0.74	0.78	0.77																
			Sones	13.2	12.2	11.9																
220HP-10	1	860	CFM	4459	4075	3578	2863															
			BHP	0.96	1.02	1.05	1.01															
			Sones	14.8	14.1	13.7	12.9															
220HP-15	1½	985	CFM	5281	4988	4642	4220	3674	2825													
			BHP	1.39	1.48	1.54	1.57	1.56	1.46													
			Sones	18.8	17.6	17.2	16.9	16.2	14.6													
		1035	CFM	5602	5335	5033	4659	4209	3630													
			BHP	1.60	1.69	1.77	1.81	1.82	1.79													
			Sones	21	19.5	18.6	18.5	18.1	17.0													
220HP-20	2	1085	CFM	5920	5678	5390	5061	4679	4210	3573												
			BHP	1.82	1.92	2.00	2.06	2.10	2.09	2.03												
			Sones	23	21	20	20	19.8	19.3	17.8												
		1135	CFM	6236	6006	5743	5456	5114	4708	4215	3518											
			BHP	2.06	2.17	2.26	2.34	2.39	2.40	2.38	2.28											
			Sones	24	23	22	21	21	21	20	19.4											
220HP-30	3	1188	CFM	6570	6350	6111	5848	5540	5202	4792	4286	3563										
			BHP	2.34	2.46	2.56	2.65	2.71	2.75	2.76	2.72	2.59										
			Sones	25	24	24	23	23	22	22	22	22	22									
		1240	CFM	6895	6684	6469	6217	5950	5637	5283	4885	4374	3633									
			BHP	2.64	2.76	2.88	2.97	3.05	3.10	3.13	3.13	3.08	2.92									
			Sones	26	25	25	25	25	25	24	23	24	25	27								

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-240: CUBE • S-CUBE



CUBE • S-CUBE

Damper Size = 18 x 18 (457 x 457)
 Roof Opening = 20½ x 20½ (521 x 521)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 142 lb (64 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.



Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg														
			0	0.125	0.25	0.375	0.5	0.625	0.75	1	1.25	1.5					
240-4	1/4	410	CFM	3717	3170	2471											
			BHP	0.16	0.18	0.18											
			Sones	6.4	5.8	5.3											
		465	CFM	4216	3768	3188	2162										
			BHP	0.23	0.25	0.26	0.23										
			Sones	7.6	7.0	6.3	5.9										
240-3	1/3	510	CFM	4623	4243	3717	3134										
			BHP	0.31	0.33	0.34	0.34										
			Sones	8.9	8.1	7.3	6.9										
240-5	1/2	585	CFM	5303	4961	4540	4093	3565									
			BHP	0.46	0.49	0.51	0.52	0.51									
			Sones	11.5	10.5	9.5	8.8	8.4									
240-7	3/4	628	CFM	5693	5368	5010	4590	4141	3600								
			BHP	0.57	0.61	0.63	0.64	0.65	0.63								
			Sones	12.9	11.9	11.1	10.4	9.8	9.4								
		670	CFM	6074	5763	5461	5052	4659	4202	3524							
			BHP	0.69	0.74	0.76	0.78	0.79	0.78	0.73							
			Sones	14.3	13.4	12.8	12.2	11.5	11.0	10.6							
240-10	1	735	CFM	6663	6370	6133	5764	5409	5037	4618							
			BHP	0.92	0.97	0.99	1.01	1.03	1.04	1.03							
			Sones	16.6	15.9	15.5	15.1	14.6	13.9	13.4							
240-15	1½	790	CFM	7162	6883	6661	6361	6011	5693	5332	4453						
			BHP	1.14	1.20	1.22	1.25	1.27	1.28	1.29	1.24						
			Sones	18.2	17.5	17.2	16.8	16.3	15.7	15.0	14.3						
		845	CFM	7660	7400	7184	6947	6615	6304	6002	5282						
			BHP	1.39	1.46	1.49	1.51	1.54	1.56	1.57	1.56						
			Sones	19.6	19.0	18.6	18.2	17.6	17.0	16.4	15.4						
240-20	2	888	CFM	8050	7802	7590	7394	7083	6772	6489	5854	5088					
			BHP	1.62	1.69	1.72	1.75	1.78	1.81	1.82	1.83	1.77					
			Sones	21	21	21	20	19.5	18.7	18.0	17.0	16.4					
		930	CFM	8431	8194	7985	7798	7536	7233	6953	6375	5706	4324				
			BHP	1.86	1.93	1.98	2.00	2.03	2.06	2.08	2.10	2.07	1.83				
			Sones	24	23	23	22	22	21	19.9	18.7	17.8	17.9				

MAXIMUM BHP AT A GIVEN RPM = (RPM/725)³
 MAXIMUM RPM = 930
 TIP SPEED (ft/min) = RPM x 6.413
 MAXIMUM MOTOR FRAME SIZE = 184T
 AVERAGE DISCHARGE VELOCITY (FPM) = CFM/3.76

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-240HP: CUBE



CUBE

Damper Size = 24 x 24 (610 x 610)
 Roof Opening = 26½ x 26½ (673 x 673)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.051 (1.3)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 175 lb (79 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0.5	0.625	0.75	1	1.25	1.5	1.75	2	2.25	2.5										
240HP-5	1/2	635	CFM	3046	2673																	
			BHP	0.43	0.43																	
			Sones	8.1	7.4																	
		675	CFM	3405	3070	2607																
			BHP	0.51	0.52	0.51																
			Sones	9.4	8.8	8.4																
240HP-7	3/4	725	CFM	3824	3547	3222																
			BHP	0.62	0.64	0.65																
			Sones	11.3	10.7	10.3																
		775	CFM	4233	3979	3704	2940															
			BHP	0.75	0.77	0.78	0.77															
			Sones	13.1	12.5	12.1	11.8															
240HP-10	1	850	CFM	4812	4599	4367	3846	3025														
			BHP	0.96	0.99	1.01	1.04	1.00														
			Sones	14.5	14.0	13.8	13.4	12.6														
240HP-15	1½	913	CFM	5286	5094	4890	4448	3932														
			BHP	1.16	1.20	1.23	1.28	1.29														
			Sones	16.4	15.8	15.4	15.2	14.7														
		975	CFM	5737	5567	5387	4988	4539	4006													
			BHP	1.39	1.43	1.48	1.53	1.56	1.56													
			Sones	18.4	17.9	17.3	16.9	16.6	15.9													
240HP-20	2	1023	CFM	6075	5927	5756	5389	4995	4533	3854												
			BHP	1.59	1.63	1.68	1.75	1.80	1.81	1.77												
			Sones	20	19.6	19.0	18.3	18.1	17.7	16.4												
		1070	CFM	6404	6272	6112	5775	5407	4990	4550	3625											
			BHP	1.80	1.84	1.89	1.98	2.04	2.07	2.08	1.95											
			Sones	22	22	21	19.7	19.7	19.4	18.8	16.6											
240HP-30	3	1150	CFM	6960	6836	6711	6406	6077	5735	5335	4925	4212										
			BHP	2.21	2.26	2.30	2.40	2.48	2.55	2.57	2.58	2.49										
			Sones	24	24	23	22	22	22	21	21	20										
		1230	CFM	7513	7395	7280	7016	6730	6410	6090	5709	5326	4722									
			BHP	2.68	2.73	2.77	2.88	2.98	3.05	3.13	3.14	3.16	3.09									
			Sones	26	25	25	25	25	24	24	23	23	25									

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-240XP: CUBE



CUBE

Damper Size = 24 x 24 (610 x 610)
 Roof Opening = 26½ x 26½ (673 x 673)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.051 (1.3)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 175 lb (79 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.



Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg														
			1	1.25	1.5	2	2.5	3	3.5	4	4.5	5					
240XP-5	1/2	1100	CFM	1292	789												
			BHP	0.40	0.34												
			Sones	10.9	11.9												
		1195	CFM	1613	1321	792											
			BHP	0.53	0.51	0.43											
			Sones	11.6	12.1	13.4											
240XP-7	3/4	1365	CFM	2079	1886	1645											
			BHP	0.77	0.78	0.77											
			Sones	13.6	13.4	13.7											
		1421	CFM	2223	2042	1837	1209										
			BHP	0.86	0.88	0.88	0.79										
			Sones	14.4	14.2	14.2	15.3										
240XP-10	1	1500	CFM	2424	2256	2079	1630										
			BHP	1.00	1.03	1.04	1.01										
			Sones	15.9	15.3	15.1	15.5										
		1635	CFM	2743	2604	2450	2101	1631									
			BHP	1.28	1.31	1.33	1.34	1.28									
			Sones	18.6	18.0	17.5	17.0	17.7									
240XP-15	1½	1720	CFM	2939	2815	2671	2366	1975	1336								
			BHP	1.48	1.51	1.53	1.57	1.53	1.35								
			Sones	21	19.8	19.2	18.4	18.4	20								
		1895	CFM	3333	3222	3109	2847	2566	2202	1706							
			BHP	1.94	1.98	2.01	2.07	2.10	2.05	1.92							
			Sones	24	23	22	21	21	21	22							
240XP-30	3	1956	CFM	3469	3361	3252	3006	2739	2414	2032	1326						
			BHP	2.13	2.16	2.20	2.26	2.30	2.28	2.21	1.89						
			Sones	25	24	23	22	22	21	22	25						
			2030	CFM	3632	3529	3423	3197	2945	2667	2319	1852					
				BHP	2.37	2.40	2.44	2.51	2.56	2.58	2.51	2.38					
				Sones	26	25	25	24	23	23	23	25					
		2165	CFM	3927	3830	3733	3535	3305	3063	2787	2461	2048	1324				
			BHP	2.85	2.89	2.93	3.01	3.07	3.12	3.11	3.05	2.93	2.47				
			Sones	29	28	28	27	26	25	25	25	27	31				

MAXIMUM BHP AT A GIVEN RPM = (RPM/1478)³
 MAXIMUM RPM = 2165
 TIP SPEED (ft/min) = RPM x 4.778
 MAXIMUM MOTOR FRAME SIZE = 184T
 AVERAGE DISCHARGE VELOCITY (FPM) = CFM/3.76

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-300: CUBE • S-CUBE



CUBE • S-CUBE



Damper Size = 30 x 30 (762 x 762)
 Roof Opening = 32½ x 32½ (826 x 826)
 Windband Thickness = 0.080 (2.0)
 Motor Cover Thickness = 0.051 (1.3)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 313 lb (142 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0	0.125	0.25	0.5	0.75	1	1.25	1.5	1.75	2										
300-3	1/3	355	CFM	5777	5132	4227																
			BHP	0.27	0.30	0.31																
			Sones	6.9	6.3	5.3																
		365	CFM	5939	5316	4463																
			BHP	0.29	0.33	0.34																
			Sones	7.2	6.5	5.7																
300-5	1/2	420	CFM	6835	6314	5660																
			BHP	0.45	0.49	0.52																
			Sones	9.0	8.2	7.5																
300-7	3/4	480	CFM	7811	7377	6844	5440															
			BHP	0.67	0.72	0.76	0.77															
			Sones	11.0	10.5	9.9	8.5															
300-10	1	530	CFM	8625	8231	7772	6636															
			BHP	0.90	0.95	1.00	1.05															
			Sones	13.3	12.7	12.2	11.2															
300-15	1½	605	CFM	9845	9501	9127	8226	7084														
			BHP	1.34	1.40	1.46	1.54	1.55														
			Sones	17.0	16.4	15.7	14.8	13.5														
300-20	2	665	CFM	10822	10508	10193	9411	8495	7271													
			BHP	1.77	1.85	1.92	2.02	2.07	2.04													
			Sones	20	19.7	18.6	17.5	16.7	15.1													
300-30	3	765	CFM	12449	12176	11904	11273	10554	9743	8756	7352											
			BHP	2.70	2.78	2.86	3.00	3.09	3.15	3.14	2.98											
			Sones	24	24	23	22	21	20	18.7	17.0											
300-50	5	795	CFM	12937	12675	12413	11818	11145	10404	9479	8302											
			BHP	3.03	3.12	3.20	3.35	3.46	3.53	3.53	3.43											
			Sones	26	25	24	23	22	22	21	18.5											
		850	CFM	13832	13587	13342	12808	12207	11521	10771	9883	8694										
			BHP	3.71	3.80	3.89	4.05	4.19	4.27	4.32	4.31	4.16										
			Sones	29	28	28	26	25	25	24	22	20										
		905	CFM	14727	14497	14266	13788	13223	12614	11963	11191	10357	9178									
			BHP	4.47	4.57	4.67	4.85	5.00	5.11	5.19	5.21	5.20	5.01									
			Sones	32	32	32	29	28	28	27	26	24	22									

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive Size-300HP: CUBE



CUBE

Damper Size = 30 x 30 (762 x 762)
 Roof Opening = 32½ x 32½ (826 x 826)
 Windband Thickness = 0.080 (2.0)
 Motor Cover Thickness = 0.051 (1.3)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 313 lb (142 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.



Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																				
			0.5	0.75	1	1.25	1.5	1.75	2	2.25	2.5	2.75											
300HP-5	1/2	460	CFM	3125																			
			BHP	0.44																			
			Sones	7.3																			
300HP-7	3/4	555	CFM	4788	3651																		
			BHP	0.77	0.76																		
			Sones	10.4	9.9																		
300HP-10	1	610	CFM	5549	4731																		
			BHP	1.00	1.03																		
			Sones	12.4	11.3																		
300HP-15	1½	700	CFM	6741	6149	5390																	
			BHP	1.47	1.53	1.57																	
			Sones	16.0	15.2	14.0																	
300HP-20	2	770	CFM	7613	7107	6535	5814	4684															
			BHP	1.91	2.00	2.06	2.09	1.99															
			Sones	18.6	18.1	17.4	16.2	16.0															
300HP-30	3	828	CFM	8324	7879	7373	6776	6059															
			BHP	2.34	2.45	2.52	2.57	2.58															
			Sones	21	21	20	19.1	18.3															
300HP-30	3	885	CFM	9014	8603	8150	7678	7062	6353														
			BHP	2.83	2.94	3.03	3.12	3.15	3.14														
			Sones	23	23	23	22	21	21														
300HP-50	5	938	CFM	9649	9262	8859	8413	7923	7331	6624													
			BHP	3.34	3.46	3.57	3.66	3.73	3.76	3.73													
			Sones	26	26	26	25	24	23	23													
300HP-50	5	991	CFM	10275	9913	9546	9133	8711	8201	7641	6946												
			BHP	3.90	4.03	4.16	4.26	4.35	4.41	4.44	4.39												
			Sones	30	29	29	28	28	27	26	25												
300HP-50	5	1045	CFM	10909	10570	10222	9855	9455	9054	8533	8002	7330	6463										
			BHP	4.54	4.68	4.82	4.94	5.04	5.13	5.17	5.21	5.15	4.99										
			Sones	35	34	34	33	32	31	31	30	28	27										

MAXIMUM BHP AT A GIVEN RPM = (RPM/602)³
 MAXIMUM RPM = 1045
 TIP SPEED (ft/min) = RPM x 7.983
 MAXIMUM MOTOR FRAME SIZE = 213T
 AVERAGE DISCHARGE VELOCITY (FPM) = CFM/5.50

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-300XP: CUBE



CUBE

Damper Size = 30 x 30 (762 x 762)
 Roof Opening = 32½ x 32½ (826 x 826)
 Windband Thickness = 0.080 (2.0)
 Motor Cover Thickness = 0.051 (1.3)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 313 lb (142 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			1	1.25	1.5	2	2.5	3	3.5	4	4.5	4.75										
300XP-7	3/4	790	CFM	1776																		
			BHP	0.48																		
			Sones	9.4																		
		900	CFM	2958	2273																	
			BHP	0.79	0.75																	
			Sones	12.2	11.3																	
300XP-10	1	990	CFM	3619	3167	2538																
			BHP	1.04	1.05	1.00																
			Sones	14.6	13.4	12.8																
300XP-15	1½	1060	CFM	4073	3708	3255																
			BHP	1.25	1.28	1.28																
			Sones	16.5	15.3	14.4																
		1130	CFM	4511	4201	3833	2773															
			BHP	1.48	1.53	1.56	1.46															
			Sones	18.9	17.8	16.8	15.6															
300XP-20	2	1245	CFM	5182	4930	4648	3943	2705														
			BHP	1.92	1.99	2.04	2.08	1.86														
			Sones	22	21	20	18.6	17.9														
300XP-30	3	1335	CFM	5695	5465	5220	4648	3905														
			BHP	2.32	2.40	2.47	2.56	2.53														
			Sones	24	24	23	21	19.4														
		1425	CFM	6199	5983	5768	5286	4695	3886													
			BHP	2.78	2.86	2.95	3.07	3.14	3.03													
			Sones	27	26	25	24	22	21													
300XP-50	5	1493	CFM	6574	6369	6164	5722	5200	4550	3646												
			BHP	3.16	3.25	3.34	3.49	3.58	3.57	3.37												
			Sones	29	28	28	26	24	23	22												
		1560	CFM	6941	6746	6549	6143	5684	5134	4441	3049											
			BHP	3.57	3.67	3.76	3.93	4.05	4.12	4.02	3.50											
			Sones	31	30	30	28	27	25	24	24											
1690	CFM	7643	7464	7284	6920	6528	6091	5587	4951	4100	3070											
	BHP	4.47	4.57	4.68	4.87	5.04	5.16	5.24	5.14	4.88	4.32											
	Sones	36	35	34	33	31	30	29	28	28	28											

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-360: CUBE • S-CUBE



CUBE • S-CUBE

Damper Size = 36 x 36 (914 x 914)
 Roof Opening = 38½ x 38½ (978 x 978)
 Windband Thickness = 0.080 (2.0)
 Motor Cover Thickness = 0.064 (1.6)
 Curb Cap Thickness = 0.080 (2.0)
 ^Approximate Unit Weight = 440 lb (200 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0	0.125	0.25	0.375	0.5	0.75	1	1.25	1.5	1.75										
360-5	1/2	300	CFM	8092	7206	6023																
			BHP	0.37	0.42	0.43																
			Sones	6.9	5.9	5.4																
		320	CFM	8631	7820	6755	5256															
			BHP	0.44	0.50	0.52	0.51															
			Sones	7.7	6.8	6.0	6.6															
360-7	3/4	365	CFM	9845	9142	8299	7286	5767														
			BHP	0.66	0.72	0.77	0.78	0.74														
			Sones	10.2	9.4	8.5	8.0	8.3														
360-10	1	400	CFM	10789	10153	9426	8556	7575														
			BHP	0.87	0.94	0.99	1.02	1.02														
			Sones	12.7	11.9	11.1	10.3	9.9														
360-15	1½	460	CFM	12408	11862	11281	10587	9814	7809													
			BHP	1.32	1.40	1.48	1.53	1.55	1.52													
			Sones	16.8	16.5	15.8	15.1	14.5	13.5													
360-20	2	505	CFM	13621	13125	12602	12022	11359	9878													
			BHP	1.74	1.83	1.92	1.99	2.04	2.06													
			Sones	20	20	19.8	19.0	18.6	17.9													
360-30	3	543	CFM	14646	14184	13705	13209	12606	11302	9606												
			BHP	2.17	2.26	2.36	2.45	2.50	2.56	2.52												
			Sones	22	22	21	21	20	19.3	18.2												
		580	CFM	15644	15212	14769	14306	13783	12597	11287	9381											
			BHP	2.64	2.74	2.84	2.94	3.02	3.10	3.13	3.02											
			Sones	23	23	23	22	22	21	20	18.4											
360-50	5	617	CFM	16642	16236	15826	15391	14942	13862	12684	11227											
			BHP	3.18	3.29	3.40	3.50	3.60	3.71	3.76	3.73											
			Sones	25	25	25	24	24	23	22	21											
		654	CFM	17640	17257	16873	16466	16056	15084	14000	12831	11217										
			BHP	3.78	3.90	4.02	4.13	4.24	4.39	4.46	4.48	4.38										
			Sones	27	27	27	26	26	25	23	22	21										
690	CFM	18611	18248	17884	17504	17115	16236	15243	14187	12985	11290											
	BHP	4.44	4.57	4.69	4.81	4.93	5.11	5.21	5.26	5.25	5.09											
	Sones	30	29	28	28	28	27	25	24	23	22											

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-360XP: CUBE only



CUBE

Damper Size = 36 x 36 (914 x 914)
 Roof Opening = 38 1/2 x 38 1/2 (978 x 978)
 Windband Thickness = 0.080 (2.0)
 Motor Cover Thickness = 0.064 (1.6)
 Curb Cap Thickness = 0.080 (2.0)
 ^Approximate Unit Weight = 440 lb (200 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see page 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			1	1.25	1.5	2	2.5	3	3.5	4	4.5	5										
360XP-10	1	700	CFM	3210																		
			BHP	0.81																		
			Sones	10.5																		
		760	CFM	4020	3225																	
			BHP	1.05	1.01																	
			Sones	11.1	11.1																	
360XP-15	1 1/2	870	CFM	5243	4740	4112																
			BHP	1.53	1.57	1.55																
			Sones	13.6	12.7	12.3																
360XP-20	2	955	CFM	6081	5679	5216	3949															
			BHP	1.97	2.04	2.08	1.98															
			Sones	15.4	15.4	14.2	13.0															
360XP-30	3	1025	CFM	6722	6396	6001	5035	3264														
			BHP	2.38	2.47	2.54	2.55	2.18														
			Sones	17.1	16.5	16.2	14.5	13.4														
		1095	CFM	7351	7050	6724	5930	4905														
			BHP	2.85	2.95	3.03	3.13	3.07														
			Sones	19.2	18.4	17.8	16.4	15.4														
360XP-50	5	1163	CFM	7945	7669	7386	6712	5867	4700													
			BHP	3.36	3.47	3.57	3.73	3.75	3.54													
			Sones	21	21	19.9	18.6	17.3	16.5													
		1231	CFM	8528	8278	8011	7422	6711	5824	4551												
			BHP	3.91	4.05	4.15	4.35	4.45	4.40	4.04												
			Sones	23	23	22	21	19.4	18.5	18.0												
1300	CFM	9113	8881	8635	8125	7502	6764	5867	4286													
	BHP	4.54	4.69	4.82	5.04	5.21	5.24	5.15	4.52													
	Sones	26	25	24	23	22	21	20	20													
360XP-75	7 1/2	1395	CFM	9910	9693	9477	9009	8490	7905	7193	6348	5143										
			BHP	5.50	5.67	5.83	6.08	6.30	6.48	6.48	6.37	5.87										
			Sones	29	28	27	26	25	24	23	23	23	23									
		1490	CFM	10699	10496	10294	9871	9429	8907	8340	7673	6881	5830									
			BHP	6.61	6.78	6.96	7.27	7.52	7.73	7.89	7.90	7.78	7.34									
			Sones	33	32	31	30	29	27	26	26	26	26									

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-420: CUBE • S-CUBE



CUBE • S-CUBE

- Damper Size = 42 x 42 (1067 x 1067)
- Roof Opening = 44½ x 44½ (1130 x 1130)
- Windband Thickness = 0.080 (2.0)
- Motor Cover Thickness = 0.064 (1.6)
- Curb Cap Thickness = 0.100 (2.5)
- ^Approximate Unit Weight = 578 lb (262 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg														
			0	0.125	0.25	0.375	0.5	0.75	1	1.25	1.5	1.75					
420-5	1/2	220	CFM	9353	7846	5075											
			BHP	0.31	0.37	0.35											
			Sones	6.5	6.0	5.5											
		245	CFM	10416	9104	7304											
			BHP	0.43	0.50	0.53											
			Sones	7.2	6.7	6.1											
420-7	3/4	280	CFM	11904	10785	9418	7419										
			BHP	0.64	0.73	0.78	0.77										
			Sones	8.3	7.7	7.1	6.6										
420-10	1	305	CFM	12966	11959	10781	9272										
			BHP	0.82	0.94	1.00	1.02										
			Sones	9.4	8.8	8.0	7.3										
420-15	1½	350	CFM	14879	14037	13050	11925	10562									
			BHP	1.24	1.38	1.46	1.52	1.54									
			Sones	11.9	11.2	10.1	9.4	8.6									
420-20	2	385	CFM	16367	15629	14731	13791	12701	9246								
			BHP	1.65	1.81	1.91	1.99	2.05	1.92								
			Sones	14.4	13.5	12.4	11.7	10.7	8.5								
420-30	3	415	CFM	17643	16982	16148	15303	14363	12028								
			BHP	2.07	2.24	2.37	2.45	2.53	2.56								
			Sones	17.2	16.1	14.9	13.8	13.0	10.9								
		440	CFM	18706	18103	17316	16532	15691	13652	10151							
			BHP	2.47	2.65	2.81	2.89	2.98	3.07	2.82							
			Sones	17.7	17.1	16.0	14.7	14.6	12.8	10.6							
420-50	5	525	CFM	22319	21817	21220	20560	19904	18497	16795	14802						
			BHP	4.19	4.41	4.61	4.78	4.88	5.10	5.20	5.16						
			Sones	23	22	22	21	20	19.1	18.1	17.6						
420-75	7½	565	CFM	24020	23553	23030	22417	21806	20544	19112	17437	15398					
			BHP	5.23	5.46	5.68	5.88	6.02	6.25	6.43	6.5	6.38					
			Sones	26	25	25	25	24	23	21	21	21	21				
		600	CFM	25508	25069	24604	24027	23451	22295	21023	19561	17884	15479				
			BHP	6.26	6.51	6.75	6.96	7.15	7.38	7.63	7.75	7.77	7.47				
			Sones	29	29	29	28	28	27	25	24	24	24	26			

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Belt Drive

Size-480: CUBE • S-CUBE



CUBE • S-CUBE

- Damper Size = 48 x 48 (1219 x 1219)
- Roof Opening = 50½ x 50½ (1283 x 1283)
- Windband Thickness = 0.080 (2.0)
- Motor Cover Thickness = 0.064 (1.6)
- Curb Cap Thickness = 0.100 (2.5)
- ^Approximate Unit Weight = 675 lb (306 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																	
			0	0.125	0.25	0.375	0.5	0.625	0.75	1	1.25	1.5								
480-5	1/2	180	CFM	11016	8924															
			BHP	0.33	0.39															
			Sones	5.5	4.9															
		200	CFM	12240	10490	7688														
			BHP	0.45	0.53	0.52														
			Sones	6.3	5.8	5.3														
480-7	3/4	225	CFM	13770	12261	10132														
			BHP	0.65	0.73	0.76														
			Sones	7.5	7.0	6.6														
480-10	1	250	CFM	15300	13988	12248	9988													
			BHP	0.88	0.98	1.04	1.03													
			Sones	9.0	8.5	8.2	7.9													
480-15	1½	285	CFM	17442	16332	14991	13240	11154												
			BHP	1.31	1.43	1.52	1.55	1.52												
			Sones	11.1	10.6	10.0	9.6	9.2												
480-20	2	315	CFM	19278	18274	17116	15719	14033	11996											
			BHP	1.77	1.90	2.01	2.08	2.09	2.03											
			Sones	12.9	12.5	11.8	11.3	10.4	10.2											
480-30	3	360	CFM	22032	21153	20222	19142	17848	16410	14749										
			BHP	2.64	2.79	2.93	3.05	3.10	3.12	3.08										
			Sones	16.8	16.5	16.1	15.3	14.7	13.7	12.7										
480-50	5	395	CFM	24174	23373	22572	21605	20621	19343	18035	14722									
			BHP	3.49	3.65	3.81	3.94	4.07	4.11	4.13	3.97									
			Sones	21	20	20	19.2	18.5	17.6	16.6	14.9									
		425	CFM	26010	25266	24521	23679	22764	21766	20556	17922									
			BHP	4.35	4.52	4.69	4.85	4.98	5.09	5.12	5.09									
			Sones	22	21	21	20	19.4	18.7	17.7	15.6									
480-75	7½	460	CFM	28152	27464	26776	26064	25219	24373	23399	21163	18582								
			BHP	5.51	5.70	5.89	6.07	6.22	6.37	6.46	6.52	6.42								
			Sones	25	24	24	23	22	22	21	18.5	18.7								
		490	CFM	29988	29342	28697	28051	27291	26497	25704	23674	21437	18846							
			BHP	6.66	6.86	7.06	7.26	7.43	7.59	7.75	7.85	7.84	7.67							
			Sones	28	27	27	26	25	25	24	22	20	24							

MAXIMUM BHP AT A GIVEN RPM = (RPM/246)³
 MAXIMUM RPM = 490
 TIP SPEED (ft/min) = RPM x 12.63
 MAXIMUM MOTOR FRAME SIZE = 213T
 AVERAGE DISCHARGE VELOCITY (FPM) = CFM/11.72

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Direct Drive Sizes-060 and 065: CUE



CUE



Damper Size = 8 x 8 (203 x 203)
 Roof Opening = 10½ x 10½ (267 x 267)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.051 (1.3)
 Curb Cap Thickness = 0.051 (1.3)
 ^Approximate Unit Weight = 29 lb (13 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg										
				0	0.05	0.1	0.125	0.15	0.2	0.25	0.3	0.35	0.375	
060-E	1/200	1050	CFM	133	113	94	81	65						
			BHP	0.01	0.01	0.01	0.01	0.01						
			Sones	1.7	1.7	1.7	1.7	1.7						
060-G	1/100	1300	CFM	165	148	134	126	117	96	70				
			BHP	0.01	0.01	0.01	0.01	0.01	0.01	0.01				
			Sones	2.8	2.6	2.5	2.5	2.5	2.5	2.5				
060-D	1/60	1550	CFM	197	183	169	164	158	143	128	107	85		
			BHP	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	
			Sones	4.2	3.9	3.9	3.9	3.9	4.0	4.0	4.0	4.0	4.0	
065-E	1/100	1050	CFM	180	154	126	109	89						
			BHP	0.01	0.01	0.01	0.01	0.01						
			Sones	2.2	2.0	1.9	2.0	2.2						
065-G	1/60	1300	CFM	223	202	181	170	158	129	97				
			BHP	0.02	0.02	0.02	0.02	0.02	0.02	0.02				
			Sones	3.2	3.2	3.1	3.1	3.0	3.0	2.9				
065-D	1/30	1550	CFM	266	249	231	222	214	194	172	145	119	95	
			BHP	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	
			Sones	4.7	4.2	4.2	4.2	4.2	4.1	4.1	4.0	4.0	3.9	

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Direct Drive Sizes-070 and 075: CUE



CUE



Damper Size = 8 x 8 (203 x 203)
 Roof Opening = 10½ x 10½ (267 x 267)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.051 (1.3)
 Curb Cap Thickness = 0.051 (1.3)
 ^Approximate Unit Weight = 29 lb (13 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg										
				0	0.05	0.1	0.125	0.15	0.2	0.25	0.3	0.35	0.375	
070-E	1/100	1050	CFM	250	224	193	171	143						
			BHP	0.01	0.01	0.01	0.01	0.01						
			Sones	2.6	2.1	1.6	1.4	1.2						
070-G	1/60	1300	CFM	309	288	267	255	241	205	152				
			BHP	0.01	0.01	0.02	0.02	0.02	0.02	0.01				
			Sones	4.0	3.7	3.4	3.3	3.1	2.8	2.4				
070-D	1/30	1550	CFM	369	351	333	325	316	293	269	234	187	160	
			BHP	0.02	0.02	0.03	0.03	0.03	0.03	0.03	0.03	0.02	0.02	
			Sones	5.5	5.4	5.2	5.1	5.1	4.9	4.7	4.4	4.1	3.9	
075-E	1/80	1050	CFM	287	249	210	188	165						
			BHP	0.01	0.01	0.01	0.01	0.01						
			Sones	3.4	3.0	2.8	2.7	2.6						
075-G	1/50	1300	CFM	356	324	294	279	262	227	185				
			BHP	0.02	0.02	0.02	0.02	0.02	0.02	0.02				
			Sones	4.0	3.8	3.7	3.7	3.7	3.6	3.4				
075-D	1/25	1550	CFM	424	398	372	359	347	320	291	261	225	204	
			BHP	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	
			Sones	6.0	5.7	5.4	5.3	5.1	5.0	4.9	4.8	4.8	4.8	

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Direct Drive Sizes-080 and 085: CUE



CUE

Damper Size = 10 x 10 (254 x 254)
 Roof Opening = 12½ x 12½ (318 x 318)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.051 (1.3)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 40 lb (18 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg											
				0	0.1	0.125	0.15	0.2	0.25	0.3	0.375	0.5	0.625		
080-E	1/40	1050	CFM	325	265	247	230	189	133						
			BHP	0.01	0.01	0.02	0.02	0.02	0.02						
			Sones	3.8	3.7	3.6	3.7	3.9	4.2						
080-G	1/30	1300	CFM	403	356	343	330	302	272	239	173				
			BHP	0.02	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03			
			Sones	5.4	5.4	5.4	5.4	5.4	5.5	5.6	5.9				
080-D	1/20	1550	CFM	480	441	431	421	400	376	352	314	235			
			BHP	0.04	0.04	0.04	0.04	0.05	0.05	0.05	0.05	0.05	0.05		
			Sones	7.3	7.3	7.3	7.3	7.3	7.2	7.3	7.3	7.3	7.6		
085-E	1/40	1050	CFM	389	323	305	286	242	182						
			BHP	0.01	0.02	0.02	0.02	0.02	0.02						
			Sones	4.0	3.9	3.9	3.9	4.1	4.3						
085-G	1/30	1300	CFM	481	430	416	402	373	340	305	235				
			BHP	0.02	0.03	0.03	0.03	0.03	0.03	0.04	0.04				
			Sones	5.4	5.3	5.3	5.3	5.3	5.3	5.4	5.5				
085-D	1/20	1550	CFM	574	532	520	509	486	461	437	395	312	161		
			BHP	0.04	0.04	0.05	0.05	0.05	0.05	0.06	0.06	0.06	0.06		
			Sones	7.5	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.6	8.1	

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Direct Drive

Size-090: CUE



CUE

Damper Size = 10 x 10 (254 x 254)
 Roof Opening = 12¹/₂ x 12¹/₂ (318 x 318)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.051 (1.3)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 40 lb (18 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg										
				0	0.1	0.125	0.15	0.2	0.25	0.3	0.375	0.5	0.625	
090-E	1/40	1050	CFM	549	470	451	429	381	306	204				
			BHP	0.02	0.02	0.02	0.03	0.03	0.03	0.03				
			Sones	4.1	3.9	3.9	3.9	4.0	4.2	4.5				
090-G	1/25	1300	CFM	680	616	600	584	553	517	479	391			
			BHP	0.04	0.04	0.04	0.04	0.05	0.05	0.05	0.05			
			Sones	5.5	5.4	5.4	5.4	5.4	5.4	5.5	5.6			
090-D	1/15	1550	CFM	811	757	744	731	704	677	651	604	501	347	
			BHP	0.06	0.07	0.07	0.07	0.07	0.08	0.08	0.08	0.08	0.09	0.08
			Sones	7.8	7.6	7.6	7.5	7.5	7.5	7.5	7.4	7.4	7.4	7.8

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Direct Drive

Size-095: CUE



CUE



Damper Size = 10 x 10 (254 x 254)
 Roof Opening = 12 1/2 x 12 1/2 (318 x 318)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.051 (1.3)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 40 lb (18 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg										
				0	0.1	0.125	0.15	0.2	0.25	0.3	0.375	0.5	0.625	
095-E	1/30	1050	CFM	711	603	570	536	468	381	265				
			BHP	0.03	0.04	0.04	0.04	0.04	0.04	0.03				
			Sones	5.3	4.5	4.5	4.5	4.4	4.5	4.6				
095-G	1/12	1300	CFM	880	797	774	750	696	641	587	484	199		
			BHP	0.06	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.05		
			Sones	7.5	6.8	6.7	6.6	6.5	6.4	6.4	6.4	6.8		
095-D	1/8	1550	CFM	1049	983	964	944	905	861	816	747	616	442	
			BHP	0.10	0.11	0.11	0.11	0.11	0.12	0.12	0.12	0.12	0.11	
			Sones	9.6	9.3	9.3	9.2	8.8	8.5	8.4	8.3	8.1	7.8	

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Direct Drive Size-098 and 101: CUE



CUE



Damper Size = 12 x 12 (305 x 305)
 Roof Opening = 14½ x 14½ (368 x 368)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 53 lb (24 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg											
				0	0.1	0.125	0.25	0.3	0.375	0.5	0.625	0.75	1		
098-C	1/8	860	CFM	588	453	409	MAXIMUM MOTOR FRAME SIZE = 56								
			BHP	0.02	0.02	0.02									
			Sones	8.4	8.5	8.7									
098-B	1/6	1140	CFM	780	682	656	502	431	294						
			BHP	0.05	0.05	0.06	0.06	0.06	0.06						
			Sones	9.1	8.7	8.7	8.3	8.1	7.9						
098-A	1/4	1725	CFM	1180	1109	1094	1017	984	929	824	712	586			
			BHP	0.18	0.18	0.18	0.18	0.19	0.20	0.20	0.20	0.20			
			Sones	13.8	13.5	13.4	13.0	12.9	12.7	12.2	12.1	12.3			
101-C	1/8	860	CFM	732	649	625	481								
			BHP	0.03	0.03	0.04	0.04								
			Sones	4.6	8.5	11.7	11.1								
101-B	1/6	1140	CFM	970	913	897	806	768	707						
			BHP	0.07	0.08	0.08	0.08	0.09	0.09						
			Sones	7.2	7.0	7.0	6.5	6.2	6.0						
101-A	1/4	1725	CFM	1468	1431	1422	1373	1350	1315	1255	1195	1129	970		
			BHP	0.24	0.25	0.26	0.27	0.27	0.28	0.29	0.29	0.29	0.29		
			Sones	13.3	12.9	12.9	12.5	12.3	12.0	11.7	11.3	10.8	9.7		

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Direct Drive Sizes-121 and 131: CUE



CUE



Damper Size = 12 x 12 (305 x 305)
 Roof Opening = 14½ x 14½ (368 x 368)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 64 lb (29 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg																	
				0	0.125	0.25	0.375	0.5	0.625	0.75	1	1.25	1.5								
121-C	1/8	860	CFM	1015	905	781	581	MAXIMUM MOTOR FRAME SIZE = 56													
			BHP	0.05	0.05	0.06	0.06														
			Sones	5.3	5.7	5.6	5.7														
121-B	1/6	1140	CFM	1346	1261	1180	1091	981	833												
			BHP	0.11	0.12	0.13	0.13	0.14	0.14												
			Sones	7.4	7.9	8.2	8.2	8.0	8.1												
121-A	1/2	1725	CFM	2037	1979	1923	1869	1816	1763	1710	1571	1406	1176								
			BHP	0.39	0.40	0.41	0.43	0.44	0.45	0.46	0.47	0.48	0.46								
			Sones	15.6	16.1	16.7	17.3	17.9	18.2	18.4	18.7	18.6	18.4								
131-C	1/8	860	CFM	1180	1057	914	675														
			BHP	0.06	0.07	0.07	0.07														
			Sones	8.5	8.3	7.7	6.9														
131-B	1/6	1140	CFM	1564	1471	1379	1280	1144	964												
			BHP	0.14	0.15	0.16	0.17	0.17	0.17												
			Sones	12.5	12.2	11.8	11.2	10.3	9.7												
131-A	3/4	1725	CFM	2366	2305	2244	2183	2122	2061	1994	1838	1646	1365								
			BHP	0.50	0.51	0.53	0.54	0.56	0.57	0.58	0.60	0.60	0.57								
			Sones	18.8	18.6	18.4	18.2	18.0	17.6	17.2	16.4	15.3	14.1								

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Roof Upblast - Direct Drive Sizes-180, 180HP and 200: CUE



CUE



Damper Size = 18 x 18 (457 x 457)
 Roof Opening = 20½ x 20½ (521 x 521)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.040 (1.0)
 Curb Cap Thickness = 0.064 (1.6)
 ^Approximate Unit Weight = 142 lb (64 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of each model, please see pages 82-87.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg										
				0	0.25	0.5	0.75	1	1.25	1.5	2	2.5	3	
180-C	1/2	860	CFM	3249	2922	2474	MAXIMUM MOTOR FRAME SIZE = 184T							
			BHP	0.34	0.39	0.40								
			Sones	12.3	11.1	10.2								
180-B	1	1140	CFM	4307	4045	3822	3470	3072	2477					
			BHP	0.80	0.86	0.91	0.93	0.92	0.85					
			Sones	17.6	16.5	16.1	15.4	14.6	13.6					
180HP-A	2	1725	CFM	4850	4732	4613	4493	4353	4215	4078	3740	3265	2695	
			BHP	1.77	1.84	1.92	1.99	2.06	2.12	2.18	2.23	2.25	2.16	
			Sones	30	29	28	27	26	26	25	24	23	21	
200-C	3/4	860	CFM	4837	4346	3815	3084							
			BHP	0.71	0.74	0.75	0.73							
			Sones	15.7	14.6	12.9	11.9							
200-B	2	1140	CFM	6412	6036	5674	5283	4837	4276	3445				
			BHP	1.65	1.70	1.74	1.74	1.74	1.73	1.63				
			Sones	24	23	22	21	20	19.2	19.9				

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-098



CWB



- Damper Size = 12 x 12 (305 x 305)
- Damper Frame Size = 14 x 14 (356 x 356)
- Wall Opening = 12½ x 12½ (318 x 318)
- Windband Thickness = 0.051 (1.3)
- Motor Cover Thickness = 0.040 (1.0)
- ^Approximate Unit Weight = 58 lb (26 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																						
			0	0.05	0.1	0.125	0.2	0.25	0.375	0.5	0.625	0.75													
CWB- 098-4	1/4	650	CFM	445	357	239																		MAXIMUM BHP AT A GIVEN RPM = (RPM/3099) ³ MAXIMUM RPM = 1725 TIP SPEED (ft/min) = RPM x 2.846 MAXIMUM MOTOR FRAME SIZE = 56 AVERAGE DISCHARGE VELOCITY (FPM) = CFM/1.28	
			BHP	0.01	0.01	0.01																			
			Sones	8.1	8.5	9.9																			
		755	CFM	516	442	352	301																		
			BHP	0.02	0.02	0.02	0.02																		
			Sones	8.3	8.4	8.9	9.3																		
		860	CFM	588	523	453	409	258																	
			BHP	0.02	0.02	0.02	0.02	0.02																	
			Sones	8.4	8.4	8.5	8.7	9.1																	
		965	CFM	660	600	543	509	392	294																
			BHP	0.03	0.03	0.03	0.04	0.04	0.04																
			Sones	8.7	8.6	8.6	8.5	8.6	8.6																
		1070	CFM	732	677	627	600	500	428																
			BHP	0.04	0.04	0.04	0.05	0.05	0.05																
			Sones	8.9	8.8	8.6	8.6	8.4	8.4																
		1175	CFM	804	752	708	684	603	537	350															
			BHP	0.06	0.06	0.06	0.06	0.06	0.06	0.06															
			Sones	9.3	9.2	9.0	8.9	8.7	8.6	8.2															
		1280	CFM	875	828	787	766	696	642	488															
			BHP	0.07	0.07	0.07	0.07	0.08	0.08	0.08															
			Sones	10.2	10.1	9.9	9.8	9.7	9.5	9.3															
		1385	CFM	947	903	864	845	785	738	603	448														
			BHP	0.09	0.09	0.09	0.09	0.10	0.10	0.10	0.10														
			Sones	11.2	11.1	10.9	10.8	10.7	10.6	10.4	10.3														
1490	CFM	1019	978	940	923	868	829	710	578	409															
	BHP	0.12	0.12	0.12	0.12	0.12	0.13	0.13	0.13	0.13															
	Sones	12.3	12.2	11.9	12.0	11.8	11.8	11.5	11.5	11.6															
1595	CFM	1091	1053	1016	1000	950	914	813	692	560															
	BHP	0.14	0.14	0.14	0.14	0.14	0.15	0.16	0.16	0.16															
	Sones	13.2	13.1	12.8	12.8	12.5	12.5	12.3	12.1	12.2															
1725	CFM	1180	1144	1109	1094	1049	1017	929	824	712	586														
	BHP	0.18	0.18	0.18	0.18	0.18	0.18	0.20	0.20	0.20	0.20														
	Sones	13.8	13.6	13.5	13.4	13.1	13.0	12.7	12.2	12.1	12.3														

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-101



CWB



- Damper Size = 12 x 12 (305 x 305)
- Damper Frame Size = 14 x 14 (356 x 356)
- Wall Opening = 12½ x 12½ (318 x 318)
- Windband Thickness = 0.051 (1.3)
- Motor Cover Thickness = 0.040 (1.0)
- ^Approximate Unit Weight = 58 lb (26 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg															
				0	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1	1.25						
CWB- 101-4	1/4	860	CFM	732	625	481													
			BHP	0.03	0.04	0.04													
			Sones	4.6	2.4	0.6													
		958	CFM	815	722	609													
			BHP	0.04	0.05	0.05													
			Sones	5.5	4.5	3.3													
		1056	CFM	899	817	718	593												
			BHP	0.06	0.06	0.07	0.07												
			Sones	6.6	6.3	5.7	5.4												
		1154	CFM	982	910	821	724	574											
			BHP	0.07	0.08	0.09	0.09	0.08											
			Sones	7.3	7.1	6.6	6.1	5.8											
		1252	CFM	1066	1000	920	834	732											
			BHP	0.09	0.10	0.11	0.11	0.11											
			Sones	8.0	8.0	7.6	6.9	6.5											
		1350	CFM	1149	1089	1016	940	856	745										
			BHP	0.12	0.13	0.13	0.14	0.14	0.14										
			Sones	8.9	8.9	8.6	8.1	7.5	7.0										
1448	CFM	1233	1176	1112	1040	966	886	763											
	BHP	0.14	0.15	0.16	0.17	0.17	0.17	0.17											
	Sones	10.3	10.2	9.9	9.5	9.0	8.3	8.0											
1546	CFM	1316	1264	1206	1139	1072	999	915	820										
	BHP	0.17	0.19	0.20	0.20	0.21	0.21	0.21	0.21										
	Sones	11.8	11.5	11.3	10.9	10.5	9.8	9.3	9.0										
1660	CFM	1413	1365	1313	1251	1189	1125	1056	974	861									
	BHP	0.22	0.23	0.24	0.25	0.26	0.26	0.26	0.26	0.26	0.25								
	Sones	12.7	12.3	12.0	11.6	11.3	10.8	10.2	9.6	9.4									
CWB- 101-3	1/3	1740	CFM	1481	1435	1386	1329	1270	1210	1146	1093	991							
			BHP	0.25	0.26	0.27	0.28	0.29	0.30	0.30	0.30	0.30							
			Sones	13.4	13.0	12.6	12.1	11.8	11.4	10.9	10.5	9.7							
		1820	CFM	1549	1505	1459	1406	1350	1293	1234	1184	1106	900						
			BHP	0.28	0.30	0.31	0.32	0.33	0.34	0.35	0.35	0.35	0.33						
			Sones	14.3	13.7	13.4	12.7	12.4	12.0	11.6	11.3	10.6	10.1						

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-101HP



CWB



Damper Size = 12 x 12 (305 x 305)
 Damper Frame Size = 14 x 14 (356 x 356)
 Wall Opening = 12½ x 12½ (318 x 318)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 ^Approximate Unit Weight = 58 lb (26 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0.5	0.625	0.75	1	1.25	1.5	1.75	2	2.25	2.5										
CWB- 101HP-4	1/4	1300	CFM	335	182																	
			BHP	0.07	0.06																	
			Sones	6.0	6.3																	
		1420	CFM	419	350	191																
			BHP	0.09	0.09	0.07																
			Sones	6.8	6.6	6.9																
		1540	CFM	491	438	371																
			BHP	0.11	0.11	0.11																
			Sones	7.8	7.5	7.3																
		1660	CFM	560	512	461	262															
			BHP	0.14	0.14	0.14	0.12															
			Sones	8.9	8.6	8.4	8.3															
1780	CFM	627	583	538	430																	
	BHP	0.17	0.17	0.17	0.17																	
	Sones	10.3	9.9	9.6	9.1																	
1900	CFM	688	651	610	520	382																
	BHP	0.20	0.21	0.21	0.21	0.19																
	Sones	12.1	11.4	11.0	10.5	10.2																
2045	CFM	761	729	693	615	522	346															
	BHP	0.24	0.26	0.26	0.26	0.26	0.23															
	Sones	13.9	13.5	12.7	12.1	11.5	11.4															
CWB- 101HP-3	1/3	2150	CFM	812	782	752	678	600	500													
			BHP	0.28	0.29	0.30	0.30	0.30	0.30													
			Sones	14.1	14.1	13.5	12.5	12.0	11.5													
		2250	CFM	860	832	804	737	665	579	456												
			BHP	0.32	0.33	0.34	0.35	0.35	0.35	0.32												
			Sones	14.4	14.4	14.2	13.2	12.5	11.9	11.6												
CWB- 101HP-5	1/2	2415	CFM	938	914	887	831	765	697	614	498											
			BHP	0.39	0.39	0.41	0.43	0.43	0.43	0.43	0.43	0.40										
			Sones	15.1	15.0	15.0	14.5	13.7	12.9	12.2	12.0											
		2580	CFM	1014	992	969	919	861	799	735	655	550	323									
			BHP	0.48	0.48	0.49	0.52	0.53	0.53	0.53	0.53	0.53	0.49	0.43								
			Sones	16.8	16.4	16.0	15.7	15.1	14.4	13.7	13.2	12.9	12.5									

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-121



CWB



- Damper Size = 12 x 12 (305 x 305)
- Damper Frame Size = 14 x 14 (356 x 356)
- Wall Opening = 12½ x 12½ (318 x 318)
- Windband Thickness = 0.051 (1.3)
- Motor Cover Thickness = 0.040 (1.0)
- ^Approximate Unit Weight = 66 lb (30 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																				
			0	0.125	0.25	0.375	0.5	0.625	0.75	1	1.25	1.5											
CWB- 121-4	1/4	685	CFM	809	670																		
			BHP	0.02	0.03																		
			Sones	4.4	4.4																		
		798	CFM	942	824	680																	
			BHP	0.04	0.04	0.05																	
			Sones	5.0	5.2	5.2																	
		911	CFM	1076	971	861	703																
			BHP	0.06	0.06	0.07	0.07																
			Sones	5.6	6.0	6.0	6.0																
		1024	CFM	1209	1115	1025	910	755															
			BHP	0.08	0.09	0.10	0.10	0.10															
			Sones	6.4	6.8	7.0	6.9	6.9															
1137	CFM	1343	1257	1176	1087	976	825																
	BHP	0.11	0.12	0.13	0.13	0.14	0.13																
	Sones	7.3	7.8	8.1	8.2	8.0	8.1																
1250	CFM	1476	1397	1323	1250	1159	1053	916															
	BHP	0.15	0.16	0.17	0.17	0.18	0.18	0.18															
	Sones	8.8	9.3	9.9	9.9	10.0	9.8	9.8															
1410	CFM	1665	1595	1528	1463	1398	1315	1224	965														
	BHP	0.21	0.22	0.23	0.24	0.25	0.26	0.26	0.25														
	Sones	11.1	11.6	12.2	12.5	12.6	12.7	12.7	12.3														
CWB- 121-3	1/3	1480	CFM	1748	1681	1617	1555	1493	1421	1338	1132												
			BHP	0.25	0.26	0.27	0.28	0.29	0.29	0.30	0.30												
			Sones	11.9	12.4	13.1	13.5	13.7	13.8	13.8	13.6												
		1545	CFM	1824	1760	1699	1639	1580	1518	1441	1262	990											
			BHP	0.28	0.29	0.30	0.31	0.32	0.33	0.34	0.34	0.33											
			Sones	12.8	13.4	14.0	14.5	14.7	14.8	14.9	14.9	14.6											
CWB- 121-5	1/2	1635	CFM	1931	1870	1811	1755	1699	1643	1577	1424	1226											
			BHP	0.33	0.34	0.36	0.37	0.38	0.39	0.40	0.41	0.40											
			Sones	14.1	14.7	15.2	15.9	16.2	16.4	16.6	16.7	16.5											
		1725	CFM	2037	1979	1923	1869	1816	1763	1710	1571	1406	1176										
			BHP	0.39	0.40	0.41	0.43	0.44	0.45	0.46	0.47	0.48	0.46										
			Sones	15.6	16.1	16.7	17.3	17.9	18.2	18.4	18.7	18.6	18.4										

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-131



CWB



- Damper Size = 12 x 12 (305 x 305)
- Damper Frame Size = 14 x 14 (356 x 356)
- Wall Opening = 12½ x 12½ (318 x 318)
- Windband Thickness = 0.051 (1.3)
- Motor Cover Thickness = 0.040 (1.0)
- ^Approximate Unit Weight = 66 lb (30 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1	1.25										
CWB- 131-4	1/4	650	CFM	892	724																	
			BHP	0.03	0.03																	
			Sones	6.2	6.0																	
		780	CFM	1070	935	756																
			BHP	0.05	0.05	0.06																
			Sones	7.5	7.3	6.6																
		910	CFM	1248	1133	1007	819															
			BHP	0.07	0.08	0.09	0.09															
			Sones	9.3	9.1	8.5	7.7															
		1040	CFM	1426	1325	1222	1094	919														
			BHP	0.11	0.12	0.13	0.13	0.13														
			Sones	11.3	11.0	10.5	9.8	9.0														
1170	CFM	1605	1515	1425	1329	1204	1045															
	BHP	0.16	0.17	0.18	0.18	0.19	0.18															
	Sones	12.9	12.6	12.2	11.7	10.8	10.1															
1305	CFM	1790	1709	1629	1547	1458	1340	1201	1003													
	BHP	0.22	0.23	0.24	0.25	0.26	0.26	0.26	0.24													
	Sones	14.6	14.3	13.9	13.5	13.0	12.0	11.5	10.8													
CWB- 131-3	1/3	1435	CFM	1968	1895	1822	1749	1671	1586	1479	1358	1198										
			BHP	0.29	0.30	0.31	0.32	0.33	0.34	0.35	0.34	0.34	0.33									
			Sones	15.7	15.5	15.1	14.8	14.3	13.8	13.1	12.5	11.9										
CWB- 131-5	1/2	1487	CFM	2039	1969	1898	1828	1754	1677	1579	1471	1339										
			BHP	0.32	0.33	0.34	0.36	0.37	0.38	0.38	0.39	0.38										
			Sones	16.2	15.9	15.7	15.4	14.9	14.5	13.9	13.2	12.7										
		1540	CFM	2112	2044	1976	1908	1838	1764	1678	1577	1465										
			BHP	0.35	0.37	0.38	0.39	0.41	0.42	0.42	0.43	0.43										
			Sones	16.7	16.5	16.2	16.0	15.6	15.2	14.6	14.0	13.4										
		1592	CFM	2183	2117	2052	1986	1920	1848	1774	1678	1578	1301									
			BHP	0.39	0.41	0.42	0.43	0.44	0.46	0.47	0.47	0.47	0.45									
			Sones	17.3	17.0	16.8	16.6	16.2	15.8	15.3	14.8	14.3	13.0									
		1645	CFM	2256	2192	2128	2065	2001	1933	1864	1778	1684	1455									
			BHP	0.43	0.45	0.46	0.47	0.49	0.50	0.51	0.52	0.52	0.51									
			Sones	17.9	17.6	17.4	17.2	16.9	16.5	16.1	15.6	15.1	13.9									

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-141



CWB



- Damper Size = 15 x 15 (381 x 381)
- Damper Frame Size = 17 x 17 (432 x 432)
- Wall Opening = 15½ x 15½ (394 x 394)
- Windband Thickness = 0.051 (1.3)
- Motor Cover Thickness = 0.040 (1.0)
- ^Approximate Unit Weight = 84 lb (38 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0	0.125	0.25	0.375	0.5	0.75	1	1.25	1.5	1.75										
CWB- 141-4	1/4	590	CFM	1069	851																	
			BHP	0.04	0.04																	
			Sones	5.0	4.5																	
		840	CFM	1295	1130	885																
			BHP	0.06	0.07	0.07																
			Sones	6.0	6.0	5.1																
	965	CFM	1521	1387	1217	969																
		BHP	0.10	0.11	0.11	0.11																
		Sones	7.1	7.3	6.8	6.2																
		CFM	1748	1635	1499	1333	1103															
		BHP	0.15	0.16	0.17	0.17	0.17															
		Sones	8.6	8.7	8.5	8.1	7.7															
1105	CFM	2001	1906	1793	1667	1515	998															
	BHP	0.23	0.24	0.25	0.26	0.26	0.23															
	Sones	10.9	10.8	10.6	10.3	10.0	9.6															
CWB- 141-3	1/3	1210	CFM	2192	2106	2006	1896	1773	1443													
			BHP	0.30	0.31	0.32	0.33	0.34	0.34													
			Sones	12.2	12.2	11.7	11.6	11.2	10.9													
CWB- 141-5	1/2	1290	CFM	2337	2258	2166	2065	1957	1691	1221												
			BHP	0.36	0.38	0.39	0.40	0.41	0.42	0.37												
			Sones	13.2	13.3	12.7	12.6	12.3	12.0	11.3												
		1390	CFM	2518	2445	2362	2271	2174	1949	1643												
			BHP	0.45	0.47	0.48	0.50	0.51	0.52	0.51												
			Sones	14.9	14.7	14.2	13.2	12.9	12.1	11.0												
CWB- 141-7	3/4	1495	CFM	2708	2640	2565	2483	2396	2202	1967	1617											
			BHP	0.56	0.58	0.60	0.61	0.62	0.64	0.65	0.61											
			Sones	17.2	16.5	16.3	15.6	13.9	12.5	12.2	10.8											
		1595	CFM	2889	2826	2757	2683	2602	2430	2225	1968	1568										
			BHP	0.69	0.70	0.72	0.74	0.75	0.77	0.79	0.78	0.72										
			Sones	20	19.0	18.5	19.5	16.1	13.3	12.3	12.6	11.6										
CWB- 141-10	1	1725	CFM	3125	3066	3005	2936	2865	2711	2539	2339	2085	1704									
			BHP	0.87	0.88	0.90	0.92	0.94	0.97	0.99	1.00	0.98	0.91									
			Sones	26	23	22	24	24	15.1	13.4	14.3	13.8	13.8									

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-141HP



CWB

- Damper Size = 15 x 15 (381 x 381)
- Damper Frame Size = 17 x 17 (432 x 432)
- Wall Opening = 15 1/2 x 15 1/2 (394 x 394)
- Windband Thickness = 0.051 (1.3)
- Motor Cover Thickness = 0.040 (1.0)
- ^Approximate Unit Weight = 84 lb (38 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0.5	0.75	1	1.25	1.5	1.75	2	2.25	2.5	2.75										
CWB- 141HP-4	1/4	895	CFM	331																		
			BHP	0.06																		
			Sones	6.1																		
		1037	CFM	566																		
			BHP	0.10																		
			Sones	6.7																		
	1179	CFM	733	563																		
		BHP	0.13	0.14																		
		Sones	8.9	9.2																		
	1321	CFM	878	756	591																	
		BHP	0.18	0.19	0.19																	
		Sones	12.1	11.6	13.6																	
1465	CFM	1016	920	798	642																	
	BHP	0.24	0.26	0.26	0.26																	
	Sones	14.2	13.5	13.2	15.5																	
CWB- 141HP-3	1/3	1605	CFM	1146	1063	965	846	704														
			BHP	0.31	0.33	0.34	0.34	0.34														
			Sones	15.2	14.4	14.2	14.0	15.2														
CWB- 141HP-5	1/2	1725	CFM	1256	1178	1098	999	879	747													
			BHP	0.38	0.40	0.42	0.43	0.43	0.42													
			Sones	16.1	15.4	15.0	14.9	14.7	15.7													
		1845	CFM	1363	1292	1219	1137	1042	924	800												
			BHP	0.46	0.48	0.50	0.52	0.52	0.52	0.51												
			Sones	17.0	16.6	16.2	16.0	15.9	15.6	16.1												
CWB- 141HP-7	3/4	1960	CFM	1463	1399	1330	1260	1176	1086	970	854											
			BHP	0.54	0.57	0.59	0.61	0.62	0.62	0.62	0.62											
			Sones	18.1	17.7	17.4	17.2	17.1	17.0	16.8	16.9											
		2035	CFM	1528	1468	1402	1335	1261	1175	1077	965	826										
			BHP	0.60	0.63	0.66	0.68	0.69	0.70	0.70	0.69	0.67										
			Sones	18.9	18.5	18.2	18.0	18.0	17.8	17.7	17.5	17.8										
		2110	CFM	1592	1536	1473	1409	1341	1262	1178	1073	965	804									
			BHP	0.67	0.70	0.72	0.75	0.77	0.78	0.78	0.78	0.77	0.73									
			Sones	19.8	19.3	19.1	19.0	18.9	18.8	18.6	18.5	18.3	20									

MAXIMUM BHP AT A GIVEN RPM = (RPM/2285)³
 MAXIMUM RPM = 2110
 TIP SPEED (ft/min) = RPM x 3.829
 MAXIMUM MOTOR FRAME SIZE = 145T
 AVERAGE DISCHARGE VELOCITY (FPM) = CFM/1.72

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-161



CWB



- Damper Size = 15 x 15 (381 x 381)
- Damper Frame Size = 17 x 17 (432 x 432)
- Wall Opening = 15 1/2 x 15 1/2 (394 x 394)
- Windband Thickness = 0.051 (1.3)
- Motor Cover Thickness = 0.040 (1.0)
- ^Approximate Unit Weight = 87 lb (39 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0	0.125	0.25	0.375	0.5	0.625	0.75	1	1.25	1.5										
CWB- 161-4	1/4	730	CFM	2098	1905	1669	1389															
			BHP	0.13	0.15	0.15	0.15															
			Sones	8.1	8.0	7.8	7.8															
		826	CFM	2236	2058	1843	1596															
			BHP	0.16	0.18	0.19	0.18															
			Sones	8.9	8.7	8.5	8.4															
	875	CFM	2374	2209	2010	1790	1512															
		BHP	0.20	0.22	0.22	0.22	0.21															
		Sones	9.9	9.6	9.3	9.1	9.0															
CWB- 161-3	1/3	965	CFM	2515	2362	2177	1974	1744	1365													
			BHP	0.23	0.26	0.26	0.26	0.26	0.24													
			Sones	11.0	10.6	10.1	9.9	9.7	9.7													
CWB- 161-5	1/2	1038	CFM	2774	2637	2477	2300	2109	1893	1584												
			BHP	0.31	0.34	0.35	0.35	0.35	0.34	0.33												
			Sones	12.4	12.0	11.5	11.2	10.8	10.6	10.5												
CWB- 161-7	3/4	1188	CFM	2984	2857	2712	2552	2382	2199	1992												
			BHP	0.39	0.42	0.43	0.44	0.44	0.43	0.43												
			Sones	13.7	13.3	12.8	12.4	12.1	11.8	11.6												
		1265	CFM	3191	3072	2941	2796	2641	2475	2297	1770											
			BHP	0.47	0.51	0.53	0.53	0.54	0.53	0.52	0.49											
			Sones	15.0	14.6	14.2	13.8	13.5	13.1	12.9	12.2											
CWB- 161-10	1	1328	CFM	3415	3304	3186	3053	2911	2764	2606	2246											
			BHP	0.58	0.62	0.64	0.65	0.65	0.66	0.65	0.64											
			Sones	16.7	16.3	15.8	15.4	15.0	14.7	14.5	14.0											
		1390	CFM	3636	3532	3426	3301	3172	3036	2894	2583	2163										
			BHP	0.70	0.74	0.77	0.78	0.79	0.79	0.79	0.78	0.75										
			Sones	18.5	18.1	17.7	17.2	16.8	16.5	16.3	15.8	15.2										
1390	CFM	3817	3718	3619	3502	3383	3253	3124	2843	2510												
	BHP	0.81	0.85	0.89	0.90	0.91	0.91	0.92	0.90	0.89												
	Sones	20	19.6	19.2	18.7	18.3	18.0	17.8	17.4	16.9												
1390	CFM	3996	3901	3806	3698	3584	3464	3340	3078	2785	2394											
	BHP	0.93	0.97	1.01	1.03	1.04	1.04	1.05	1.04	1.03	1.00											
	Sones	22	21	21	20	19.9	19.6	19.4	19.0	18.6	18.0											

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-161HP



CWB



Damper Size = 15 x 15 (381 x 381)
 Damper Frame Size = 17 x 17 (432 x 432)
 Wall Opening = 15½ x 15½ (394 x 394)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 ^Approximate Unit Weight = 85 lb (39 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0.5	0.625	0.75	0.875	1	1.25	1.5	1.75	2	2.25										
CWB- 161HP-4	1/4	825	CFM	889																		
			BHP	0.12																		
			Sones	7.0																		
		910	CFM	1129	956																	
			BHP	0.16	0.16																	
			Sones	8.3	7.8																	
		995	CFM	1331	1208	1042																
			BHP	0.21	0.21	0.21																
			Sones	9.6	9.3	8.8																
1065	CFM	1487	1377	1252	1093																	
	BHP	0.25	0.26	0.26	0.26																	
	Sones	11.0	10.6	10.2	9.8																	
CWB- 161HP-3	1/3	1165	CFM	1697	1608	1504	1395	1252														
			BHP	0.32	0.33	0.34	0.34	0.34														
			Sones	12.8	12.7	12.2	11.7	11.3														
CWB- 161HP-5	1/2	1255	CFM	1882	1799	1715	1617	1519	1218													
			BHP	0.40	0.41	0.42	0.43	0.43	0.42													
			Sones	13.1	12.8	12.5	12.0	11.5	10.6													
		1340	CFM	2053	1975	1897	1816	1724	1513													
			BHP	0.48	0.49	0.50	0.51	0.52	0.52													
			Sones	14.4	13.8	13.3	12.8	12.3	11.3													
CWB- 161HP-7	3/4	1441	CFM	2253	2180	2108	2036	1961	1790	1577												
			BHP	0.59	0.60	0.61	0.63	0.64	0.65	0.65												
			Sones	16.3	15.8	15.2	14.7	14.3	13.5	12.3												
		1535	CFM	2433	2368	2301	2233	2165	2015	1855	1638											
			BHP	0.70	0.72	0.73	0.74	0.76	0.78	0.79	0.78											
			Sones	18.1	17.7	17.2	16.8	16.4	15.7	14.9	13.5											
CWB- 161HP-10	1	1610	CFM	2573	2516	2452	2387	2322	2190	2037	1863	1651										
			BHP	0.80	0.82	0.83	0.85	0.86	0.89	0.90	0.91	0.90										
			Sones	19.6	19.2	18.8	18.4	18.1	17.5	16.9	15.8	14.3										
		1690	CFM	2722	2671	2611	2550	2488	2365	2228	2082	1899	1664									
			BHP	0.92	0.94	0.95	0.97	0.98	1.01	1.03	1.05	1.05	1.03									
			Sones	21	21	21	20	20	19.5	19.1	18.6	16.9	15.0									

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-180



CWB



- Damper Size = 17 x 17 (432 x 432)
- Damper Frame Size = 19 x 19 (483 x 483)
- Wall Opening = 17 1/2 x 17 1/2 (445 x 445)
- Windband Thickness = 0.051 (1.3)
- Motor Cover Thickness = 0.040 (1.0)
- ^Approximate Unit Weight = 126 lb (57 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg													
			0	0.125	0.25	0.5	0.75	1	1.25	1.5	1.75	2				
CWB- 180-4	1/4	630	CFM	2380	2154	1861										
			BHP	0.13	0.15	0.16										
			Sones	7.1	6.4	5.5										
		745	CFM	2815	2617	2448	1763									
			BHP	0.22	0.24	0.26	0.25									
			Sones	9.2	8.6	8.1	7.1									
CWB- 180-3	1/3	820	CFM	3098	2916	2759	2257									
			BHP	0.30	0.32	0.34	0.34									
			Sones	11.2	10.4	10.0	9.0									
CWB- 180-5	1/2	940	CFM	3551	3389	3243	2879	2363								
			BHP	0.45	0.47	0.49	0.52	0.50								
			Sones	13.8	13.5	13.1	12.4	11.2								
CWB- 180-7	3/4	1010	CFM	3816	3664	3526	3242	2799	2105							
			BHP	0.56	0.58	0.61	0.65	0.64	0.58							
			Sones	15.4	15.2	14.9	14.7	13.7	11.8							
		1075	CFM	4061	3919	3786	3554	3141	2652							
			BHP	0.67	0.70	0.73	0.78	0.78	0.75							
			Sones	16.5	16.2	15.8	15.5	14.7	13.3							
CWB- 180-10	1	1185	CFM	4477	4348	4224	4005	3703	3336	2841						
			BHP	0.90	0.93	0.96	1.01	1.04	1.04	0.99						
			Sones	18.5	17.9	17.1	16.5	16.0	15.2	14.4						
CWB- 180-15	1 1/2	1275	CFM	4817	4697	4578	4369	4163	3799	3437	2930					
			BHP	1.12	1.15	1.19	1.24	1.30	1.30	1.28	1.22					
			Sones	21	20	19.5	18.7	18.2	17.5	16.7	15.9					
		1360	CFM	5138	5026	4913	4710	4532	4232	3912	3537	3023				
			BHP	1.36	1.39	1.43	1.49	1.56	1.58	1.58	1.54	1.46				
			Sones	23	23	22	21	21	20	19.2	18.3	17.3				
CWB- 180-20	2	1430	CFM	5402	5296	5189	4993	4819	4593	4270	3968	3567	3001			
			BHP	1.58	1.62	1.66	1.72	1.79	1.83	1.83	1.83	1.76	1.66			
			Sones	25	25	25	24	23	22	22	21	19.5	18.2			
		1495	CFM	5648	5546	5443	5254	5082	4921	4598	4313	3983	3564			
			BHP	1.80	1.84	1.89	1.96	2.02	2.10	2.10	2.10	2.06	1.99			
			Sones	28	27	27	26	25	25	24	23	22	21			

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-180HP



CWB

Damper Size = 17 x 17 (432 x 432)
 Damper Frame Size = 19 x 19 (483 x 483)
 Wall Opening = 17½ x 17½ (445 x 445)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 ^Approximate Unit Weight = 126 lb (57 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0.5	0.75	1	1.25	1.5	1.75	2	2.25	2.5	2.75										
CWB- 180HP-4	1/4	795	CFM	1570																		
			BHP	0.22																		
			Sones	8.3																		
		845	CFM	1799																		
			BHP	0.26																		
			Sones	9.5																		
CWB- 180HP-3	1/3	925	CFM	2104	1688																	
			BHP	0.34	0.35																	
			Sones	10.8	9.8																	
CWB- 180HP-5	1/2	1065	CFM	2581	2323	1933																
			BHP	0.50	0.52	0.53																
			Sones	13.8	12.5	12.4																
CWB- 180HP-7	3/4	1215	CFM	3063	2868	2626	2286	1854														
			BHP	0.72	0.76	0.78	0.79	0.75														
			Sones	15.0	14.5	14.0	13.4	12.9														
CWB- 180HP-10	1	1275	CFM	3253	3066	2853	2566	2209														
			BHP	0.82	0.87	0.89	0.91	0.89														
			Sones	16.7	15.8	15.4	14.9	14.3														
		1335	CFM	3441	3261	3075	2839	2523	2156													
			BHP	0.93	0.98	1.02	1.04	1.04	1.04													
			Sones	18.7	17.4	17.0	16.6	16.1	15.6													
CWB- 180HP-15	1½	1430	CFM	3735	3566	3401	3206	2964	2669	2320												
			BHP	1.13	1.19	1.23	1.26	1.27	1.28	1.24												
			Sones	22	21	19.7	19.3	18.9	18.4	17.9												
		1530	CFM	4005	3853	3696	3538	3338	3089	2807	2479											
			BHP	1.34	1.40	1.46	1.50	1.52	1.53	1.54	1.49											
			Sones	23	22	21	21	20	19.7	19.1	18.4											
CWB- 180HP-20	2	1610	CFM	4273	4136	3986	3840	3674	3485	3233	2965	2656										
			BHP	1.58	1.64	1.70	1.76	1.79	1.81	1.82	1.82	1.78										
			Sones	25	24	23	23	22	21	21	20	19.2										
		1685	CFM	4495	4369	4226	4085	3945	3768	3575	3325	3061	2766									
			BHP	1.79	1.86	1.93	1.99	2.04	2.07	2.08	2.09	2.08	2.04									
			Sones	27	26	25	26	24	23	22	21	21	20									

MAXIMUM BHP AT A GIVEN RPM = (RPM/1315)³
 MAXIMUM RPM = 1685
 TIP SPEED (ft/min) = RPM x 4.843
 MAXIMUM MOTOR FRAME SIZE = 184T
 AVERAGE DISCHARGE VELOCITY (FPM) = CFM/2.92

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-200



CWB



- Damper Size = 17 x 17 (432 x 432)
- Damper Frame Size = 19 x 19 (483 x 483)
- Wall Opening = 17½ x 17½ (445 x 445)
- Windband Thickness = 0.051 (1.3)
- Motor Cover Thickness = 0.040 (1.0)
- ^Approximate Unit Weight = 142 lb (64 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg														
			0	0.125	0.25	0.375	0.5	0.75	1	1.25	1.5	1.75					
CWB- 200-4	1/4	500	CFM	2812	2386	1822											
			BHP	0.14	0.15	0.15											
			Sones	6.2	5.4	4.6											
		605	CFM	3403	3054	2675	2144										
			BHP	0.25	0.26	0.26	0.25										
			Sones	8.1	7.4	6.7	6.1										
CWB- 200-3	1/3	665	CFM	3740	3422	3096	2699	2073									
			BHP	0.33	0.34	0.35	0.35	0.33									
			Sones	9.4	8.8	8.1	7.5	7.0									
CWB- 200-5	1/2	760	CFM	4275	3994	3718	3413	3048									
			BHP	0.49	0.51	0.52	0.52	0.51									
			Sones	12.1	11.7	10.9	10.1	9.4									
CWB- 200-7	3/4	820	CFM	4612	4350	4098	3828	3523	2606								
			BHP	0.61	0.63	0.65	0.65	0.65	0.61								
			Sones	14.1	14.1	13.0	12.2	11.4	10.7								
		875	CFM	4922	4676	4439	4192	3922	3240								
			BHP	0.75	0.77	0.78	0.79	0.79	0.78								
			Sones	16.3	16.3	15.2	14.7	13.5	12.4								
CWB- 200-10	1	960	CFM	5400	5176	4958	4742	4508	3985	3169							
			BHP	0.98	1.01	1.03	1.04	1.04	1.04	1.00							
			Sones	18.7	18.4	17.7	17.0	16.4	15.0	14.4							
CWB- 200-15	1½	1030	CFM	5793	5585	5380	5179	4968	4503	3917	2972						
			BHP	1.22	1.24	1.26	1.28	1.29	1.29	1.27	1.18						
			Sones	21	21	20	19.2	18.7	17.5	16.4	16.8						
		1100	CFM	6187	5992	5798	5610	5421	5006	4529	3861						
			BHP	1.48	1.51	1.53	1.55	1.57	1.57	1.57	1.53						
			Sones	23	23	23	22	21	20	19.3	18.6						
CWB- 200-20	2	1155	CFM	6496	6311	6125	5946	5767	5383	4948	4410	3629					
			BHP	1.72	1.74	1.77	1.79	1.81	1.81	1.81	1.80	1.71					
			Sones	24	24	23	23	22	21	20	19.2	19.9					
		1210	CFM	6806	6628	6451	6279	6108	5748	5350	4892	4289	3365				
			BHP	1.97	2.00	2.03	2.05	2.07	2.09	2.09	2.08	2.04	1.88				
			Sones	25	24	23	23	22	21	21	19.8	19.7	21				

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-200HP



CWB

- Damper Size = 17 x 17 (432 x 432)
- Damper Frame Size = 19 x 19 (483 x 483)
- Wall Opening = 17 1/2 x 17 1/2 (445 x 445)
- Windband Thickness = 0.051 (1.3)
- Motor Cover Thickness = 0.040 (1.0)
- ^Approximate Unit Weight = 142 lb (64 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0.5	0.625	0.75	0.875	1	1.25	1.5	1.625	1.75	2										
CWB- 200HP-5	1/2	740	CFM	2024																		
			BHP	0.31																		
			Sones	8.1																		
		810	CFM	2431	2156																	
			BHP	0.40	0.41																	
			Sones	9.3	8.7																	
880	CFM	2779	2578	2317	1922																	
	BHP	0.51	0.52	0.52	0.50																	
	Sones	10.5	10.1	9.5	8.7																	
CWB- 200HP-7	3/4	945	CFM	3094	2915	2711	2468	2092														
			BHP	0.62	0.64	0.64	0.64	0.62														
			Sones	12.2	11.8	11.5	11.1	10.6														
		1010	CFM	3397	3235	3067	2865	2637														
			BHP	0.75	0.77	0.78	0.79	0.79														
			Sones	14.5	14.1	13.7	13.5	13.2														
CWB- 200HP-10	1	1060	CFM	3625	3476	3316	3157	2944	2370													
			BHP	0.86	0.88	0.89	0.91	0.91	0.88													
			Sones	16.0	15.7	15.3	15.1	14.9	14.6													
		1110	CFM	3851	3710	3561	3409	3242	2806													
			BHP	0.98	1.00	1.02	1.03	1.04	1.04													
			Sones	16.9	16.5	16.2	15.9	15.7	15.5													
CWB- 200HP-15	1 1/2	1190	CFM	4207	4075	3944	3803	3661	3321	2850												
			BHP	1.20	1.22	1.24	1.25	1.27	1.29	1.26												
			Sones	19.0	18.5	18.1	17.7	17.5	17.3	17.5												
		1270	CFM	4558	4435	4312	4188	4055	3789	3433	3237	2944										
			BHP	1.44	1.47	1.49	1.51	1.53	1.56	1.56	1.56	1.53										
			Sones	22	21	21	20	20	19.7	19.3	19.4	19.8										
CWB- 200HP-20	2	1335	CFM	4837	4724	4606	4489	4369	4116	3826	3654	3482	2946									
			BHP	1.67	1.69	1.71	1.74	1.76	1.79	1.82	1.82	1.82	1.82	1.75								
			Sones	23	23	23	22	22	21	21	21	21	21	21	22							
		1400	CFM	5110	5009	4898	4786	4674	4436	4195	4044	3880	3515									
			BHP	1.91	1.94	1.96	1.98	2.01	2.05	2.09	2.09	2.09	2.09	2.08								
			Sones	24	24	24	24	24	24	23	21	22	22	23								

MAXIMUM BHP AT A GIVEN RPM = (RPM/1093)³
 MAXIMUM RPM = 1400
 TIP SPEED (ft/min) = RPM x 5.595
 MAXIMUM MOTOR FRAME SIZE = 184T
 AVERAGE DISCHARGE VELOCITY (FPM) = CFM/2.92

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-220



CWB



- Damper Size = 20 x 20 (508 x 508)
- Damper Frame Size = 22 x 22 (559 x 559)
- Wall Opening = 20½ x 20½ (521 x 521)
- Windband Thickness = 0.064 (1.6)
- Motor Cover Thickness = 0.051 (1.3)
- ^Approximate Unit Weight = 174 lb (79 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																	
			0	0.125	0.25	0.375	0.5	0.625	0.75	1	1.25	1.5								
CWB- 220-4	1/4	450	CFM	3585	3155	2624														
			BHP	0.19	0.21	0.22														
			Sones	7.3	6.6	6.0														
		475	CFM	3784	3377	2896	2268													
			BHP	0.23	0.25	0.26	0.25													
			Sones	7.9	7.2	6.5	6.1													
CWB- 220-3	1/3	520	CFM	4142	3771	3357	2845													
			BHP	0.30	0.32	0.34	0.34													
			Sones	9.3	8.4	7.6	7.1													
CWB- 220-5	1/2	600	CFM	4779	4457	4124	3736	3279												
			BHP	0.46	0.48	0.51	0.52	0.52												
			Sones	12.0	11.0	10.0	9.3	8.8												
CWB- 220-7	3/4	645	CFM	5138	4838	4539	4194	3811	3346											
			BHP	0.57	0.60	0.63	0.64	0.65	0.64											
			Sones	13.4	12.6	11.8	11.1	10.4	9.9											
		685	CFM	5457	5174	4893	4581	4234	3836	3383										
			BHP	0.68	0.71	0.74	0.76	0.78	0.78	0.77										
			Sones	14.8	14.0	13.4	12.9	12.1	11.6	11.1										
CWB- 220-10	1	755	CFM	6014	5758	5502	5239	4944	4620	4258										
			BHP	0.91	0.94	0.98	1.01	1.03	1.04	1.04										
			Sones	17.3	16.7	16.3	16.0	15.5	14.8	14.3										
CWB- 220-15	1½	810	CFM	6452	6213	5975	5737	5470	5185	4883	4156									
			BHP	1.13	1.16	1.20	1.24	1.26	1.28	1.29	1.27									
			Sones	18.7	18.1	17.7	17.3	16.9	16.2	15.6	14.7									
		865	CFM	6890	6667	6443	6220	5987	5729	5453	4835	4111								
			BHP	1.37	1.41	1.45	1.49	1.52	1.54	1.56	1.57	1.53								
			Sones	20	19.9	19.3	18.9	18.5	17.8	17.2	16.3	15.9								
CWB- 220-20	2	910	CFM	7249	7036	6823	6612	6400	6158	5909	5365	4704								
			BHP	1.60	1.64	1.68	1.72	1.76	1.78	1.81	1.83	1.81								
			Sones	23	22	22	21	21	19.9	19.1	18.0	17.1								
		955	CFM	7607	7405	7202	7000	6799	6580	6347	5844	5261	4602							
			BHP	1.85	1.89	1.93	1.97	2.02	2.05	2.07	2.11	2.11	2.07							
			Sones	25	25	24	24	23	23	22	20	19.0	18.6							

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-220HP



CWB



Damper Size = 20 x 20 (508 x 508)
 Damper Frame Size = 22 x 22 (559 x 559)
 Wall Opening = 20½ x 20½ (521 x 521)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.051 (1.3)
 ^Approximate Unit Weight = 174 lb (79 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																
			0.5	0.625	0.75	0.875	1	1.25	1.5	1.625	1.75	2							
CWB- 220HP-5	1/2	650	CFM	2909	2534	1940													
			BHP	0.45	0.45	0.42													
			Sones	8.6	7.9	7.5													
		680	CFM	3151	2830	2405													
			BHP	0.51	0.52	0.51													
			Sones	9.6	9.0	8.6													
CWB- 220HP-7	3/4	730	CFM	3545	3279	2958	2545												
			BHP	0.62	0.64	0.64	0.63												
			Sones	11.5	10.9	10.6	10.3												
		780	CFM	3902	3680	3427	3114	2716											
			BHP	0.74	0.76	0.78	0.78	0.77											
			Sones	13.2	12.6	12.2	12.1	11.9											
CWB- 220HP-10	1	820	CFM	4182	3992	3757	3493	3181											
			BHP	0.85	0.88	0.90	0.91	0.90											
			Sones	13.8	13.4	13.1	12.9	12.7											
		860	CFM	4459	4277	4075	3850	3578	2863										
			BHP	0.96	1.00	1.02	1.04	1.05	1.01										
			Sones	14.8	14.2	14.1	13.9	13.7	12.9										
CWB- 220HP-15	1½	902	CFM	4743	4573	4400	4188	3969	3386										
			BHP	1.10	1.13	1.17	1.19	1.20	1.20										
			Sones	16.1	15.5	15.1	15.0	14.9	14.2										
		944	CFM	5016	4865	4699	4521	4315	3834	3169									
			BHP	1.24	1.28	1.32	1.35	1.37	1.38	1.34									
			Sones	17.4	16.8	16.2	16.2	16.1	15.6	14.6									
985	CFM	5281	5146	4988	4829	4642	4220	3674	3340	2825									
	BHP	1.39	1.44	1.48	1.51	1.54	1.57	1.56	1.53	1.46									
	Sones	18.8	18.3	17.6	17.3	17.2	16.9	16.2	15.5	14.6									
CWB- 220HP-20	2	1035	CFM	5602	5476	5335	5184	5033	4659	4209	3937	3630							
			BHP	1.60	1.65	1.69	1.73	1.77	1.81	1.82	1.81	1.79							
			Sones	21	20	19.5	18.7	18.6	18.5	18.1	17.7	17.0							
		1085	CFM	5920	5800	5678	5534	5390	5061	4679	4454	4210	3573						
			BHP	1.82	1.87	1.92	1.96	2.00	2.06	2.10	2.10	2.09	2.03						
			Sones	23	22	21	21	20	20	19.8	19.6	19.3	17.8						

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-240



CWB



Damper Size = 20 x 20 (508 x 508)
 Damper Frame Size = 22 x 22 (559 x 559)
 Wall Opening = 20½ x 20½ (521 x 521)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.051 (1.3)
 ^Approximate Unit Weight = 175 lb (79 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																	
			0	0.125	0.25	0.375	0.5	0.625	0.75	1	1.25	1.5								
CWB- 240-4	1/4	410	CFM	3717	3170	2471														
			BHP	0.16	0.18	0.18														
			Sones	6.4	5.8	5.3														
		465	CFM	4216	3768	3188	2162													
			BHP	0.23	0.25	0.26	0.23													
			Sones	7.6	7.0	6.3	5.9													
CWB- 240-3	1/3	510	CFM	4623	4243	3717	3134													
			BHP	0.31	0.33	0.34	0.34													
			Sones	8.9	8.1	7.3	6.9													
CWB- 240-5	1/2	585	CFM	5303	4961	4540	4093	3565												
			BHP	0.46	0.49	0.51	0.52	0.51												
			Sones	11.5	10.5	9.5	8.8	8.4												
CWB- 240-7	3/4	628	CFM	5693	5368	5010	4590	4141	3600											
			BHP	0.57	0.61	0.63	0.64	0.65	0.63											
			Sones	12.9	11.9	11.1	10.4	9.8	9.4											
		670	CFM	6074	5763	5461	5052	4659	4202	3524										
			BHP	0.69	0.74	0.76	0.78	0.79	0.78	0.73										
			Sones	14.3	13.4	12.8	12.2	11.5	11.0	10.6										
CWB- 240-10	1	735	CFM	6663	6370	6133	5764	5409	5037	4618										
			BHP	0.92	0.97	0.99	1.01	1.03	1.04	1.03										
			Sones	16.6	15.9	15.5	15.1	14.6	13.9	13.4										
		790	CFM	7162	6883	6661	6361	6011	5693	5332	4453									
			BHP	1.14	1.20	1.22	1.25	1.27	1.28	1.29	1.24									
			Sones	18.2	17.5	17.2	16.8	16.3	15.7	15.0	14.3									
CWB- 240-15	1½	845	CFM	7660	7400	7184	6947	6615	6304	6002	5282									
			BHP	1.39	1.46	1.49	1.51	1.54	1.56	1.57	1.56									
			Sones	19.6	19.0	18.6	18.2	17.6	17.0	16.4	15.4									
CWB- 240-20	2	888	CFM	8050	7802	7590	7394	7083	6772	6489	5854	5088								
			BHP	1.62	1.69	1.72	1.75	1.78	1.81	1.82	1.83	1.77								
			Sones	21	21	21	20	19.5	18.7	18.0	17.0	16.4								
		930	CFM	8431	8194	7985	7798	7536	7233	6953	6375	5706	4324							
			BHP	1.86	1.93	1.98	2.00	2.03	2.06	2.08	2.10	2.07	1.83							
			Sones	24	23	23	22	22	21	19.9	18.7	17.8	17.9							

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-240HP



CWB



Damper Size = 20 x 20 (508 x 508)
 Damper Frame Size = 22 x 22 (559 x 559)
 Wall Opening = 20½ x 20½ (521 x 521)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.051 (1.3)
 ^Approximate Unit Weight = 175 lb (79 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																		
			0.5	0.625	0.75	0.875	1	1.25	1.5	1.625	1.75	2									
CWB-240HP-5	1/2	635	CFM	3046	2673																
			BHP	0.43	0.43																
			Sones	8.1	7.4																
		675	CFM	3405	3070	2607															
			BHP	0.51	0.52	0.51															
			Sones	9.4	8.8	8.4															
CWB- 240HP-7	3/4	725	CFM	3824	3547	3222	2751														
			BHP	0.62	0.64	0.65	0.63														
			Sones	11.3	10.7	10.3	10.1														
		775	CFM	4233	3979	3704	3400	2940													
			BHP	0.75	0.77	0.78	0.79	0.77													
			Sones	13.1	12.5	12.1	12.0	11.8													
CWB- 240HP-10	1	813	CFM	4529	4295	4054	3771	3481													
			BHP	0.85	0.88	0.90	0.91	0.91													
			Sones	13.7	13.2	13.0	12.7	12.5													
		850	CFM	4812	4599	4367	4123	3846	3025												
			BHP	0.96	0.99	1.01	1.03	1.04	1.00												
			Sones	14.5	14.0	13.8	13.7	13.4	12.6												
CWB- 240HP-15	1½	892	CFM	5129	4932	4717	4497	4250	3687												
			BHP	1.09	1.13	1.16	1.18	1.20	1.20												
			Sones	15.7	15.1	14.9	14.8	14.6	14.0												
		934	CFM	5443	5255	5061	4850	4640	4140	3359											
			BHP	1.23	1.28	1.31	1.34	1.37	1.38	1.33											
			Sones	17.1	16.5	16.0	15.9	15.8	15.3	14.2											
CWB- 240HP-20	2	975	CFM	5737	5567	5387	5190	4988	4539	4006	3542										
			BHP	1.39	1.43	1.48	1.51	1.53	1.56	1.56	1.52										
			Sones	18.4	17.9	17.3	17.0	16.9	16.6	15.9	15.0										
		1023	CFM	6075	5927	5756	5581	5389	4995	4533	4296	3854									
			BHP	1.59	1.63	1.68	1.72	1.75	1.80	1.81	1.82	1.77									
			Sones	20	19.6	19.0	18.3	18.3	18.1	17.7	17.3	16.4									
1070	CFM	6404	6272	6112	5949	5775	5407	4990	4770	4550	3625										
	BHP	1.80	1.84	1.89	1.94	1.98	2.04	2.07	2.07	2.08	1.95										
	Sones	22	22	21	20	19.7	19.7	19.4	19.1	18.8	16.6										

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-300



CWB



- Damper Size = 25 x 25 (635 x 635)
- Damper Frame Size = 27 x 27 (686 x 686)
- Wall Opening = 25½ x 25½ (648 x 648)
- Windband Thickness = 0.064 (1.6)
- Motor Cover Thickness = 0.051 (1.3)
- ^Approximate Unit Weight = 313 lb (142 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																		
			0	0.125	0.25	0.375	0.5	0.625	0.75	1	1.25	1.5									
CWB-300-3	1/3	355	CFM	5777	5132	4227															
			BHP	0.27	0.30	0.31															
			Sones	6.9	6.3	5.3															
		365	CFM	5940	5316	4464															
			BHP	0.29	0.33	0.34															
			Sones	7.2	6.5	5.7															
CWB-300-5	1/2	420	CFM	6835	6314	5660	4820														
			BHP	0.45	0.49	0.52	0.52														
			Sones	9.0	8.2	7.5	6.9														
CWB-300-7	3/4	480	CFM	7811	7377	6844	6231	5440													
			BHP	0.67	0.72	0.76	0.78	0.77													
			Sones	11.0	10.5	9.9	9.3	8.5													
CWB-300-10	1	530	CFM	8625	8231	7772	7245	6636	5879												
			BHP	0.90	0.95	1.00	1.03	1.05	1.04												
			Sones	13.3	12.7	12.2	11.7	11.2	10.2												
CWB-300-15	1½	568	CFM	9243	8876	8463	7996	7477	6842	6052											
			BHP	1.11	1.17	1.22	1.26	1.28	1.29	1.26											
			Sones	15.2	14.6	14.0	13.6	13.2	12.4	11.5											
		605	CFM	9845	9501	9127	8705	8226	7708	7084											
			BHP	1.34	1.40	1.46	1.51	1.54	1.56	1.55											
			Sones	17.0	16.4	15.7	15.2	14.8	14.3	13.5											
CWB-300-20	2	635	CFM	10334	10005	9662	9259	8823	8359	7798	6334										
			BHP	1.55	1.61	1.68	1.73	1.77	1.79	1.80	1.72										
			Sones	18.5	17.9	17.1	16.6	16.1	15.7	15.1	13.4										
		665	CFM	10822	10508	10193	9808	9411	8968	8495	7271										
			BHP	1.77	1.85	1.92	1.97	2.02	2.05	2.07	2.04										
			Sones	20	19.7	18.6	18.0	17.5	17.1	16.7	15.1										
CWB-300-30	3	715	CFM	11635	11344	11052	10713	10356	9963	9551	8572	7241									
			BHP	2.21	2.28	2.36	2.42	2.48	2.52	2.55	2.57	2.47									
			Sones	22	22	21	19.9	19.3	18.9	18.5	17.8	15.8									
		765	CFM	12449	12176	11904	11607	11273	10939	10554	9743	8756	7352								
			BHP	2.70	2.78	2.86	2.94	3.00	3.06	3.09	3.15	3.14	2.98								
			Sones	24	24	23	22	22	21	21	20	18.7	17.0								

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Belt Drive CWB-300HP



CWB

Damper Size = 25 x 25 (635 x 635)
 Damper Frame Size = 27 x 27 (686 x 686)
 Wall Opening = 25½ x 25½ (648 x 648)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.051 (1.3)
 ^Approximate Unit Weight = 313 lb (142 kg)



All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg																			
			0.5	0.625	0.75	0.875	1	1.125	1.25	1.5	1.625	1.75										
CWB-300HP-5	1/2	460	CFM	3125																		
			BHP	0.44																		
			Sones	7.3																		
		485	CFM	3639																		
			BHP	0.52																		
			Sones	7.9																		
CWB-300HP-7	3/4	555	CFM	4788	4288	3651																
			BHP	0.77	0.78	0.76																
			Sones	10.4	9.8	9.9																
		583	CFM	5180	4751	4233																
			BHP	0.88	0.90	0.90																
			Sones	11.3	10.8	10.2																
CWB-300HP-10	1	610	CFM	5549	5187	4731	4165															
			BHP	1.00	1.02	1.03	1.02															
			Sones	12.4	11.9	11.3	10.9															
		655	CFM	6154	5835	5470	5046	4513														
			BHP	1.22	1.25	1.27	1.28	1.26														
			Sones	14.3	13.8	13.3	12.7	12.2														
CWB-300HP-15	1½	700	CFM	6741	6448	6149	5787	5390	4896													
			BHP	1.47	1.50	1.53	1.55	1.57	1.55													
			Sones	16.0	15.6	15.2	14.7	14.0	13.5													
		770	CFM	7613	7377	7107	6835	6535	6175	5814	4684											
			BHP	1.91	1.96	2.00	2.03	2.06	2.07	2.09	1.99											
			Sones	18.6	18.3	18.1	17.8	17.4	16.7	16.2	16.0											
CWB-300HP-30	3	809	CFM	8092	7867	7628	7369	7110	6808	6465	5668	5206										
			BHP	2.19	2.25	2.29	2.33	2.37	2.39	2.41	2.39	2.35										
			Sones	20	19.9	19.7	19.6	19.2	18.8	18.1	17.5	17.5										
		848	CFM	8567	8352	8138	7895	7648	7401	7100	6445	6023	5582									
			BHP	2.50	2.56	2.61	2.66	2.70	2.74	2.76	2.79	2.76	2.72									
			Sones	22	21	21	21	21	20	19.1	19.1	19.1	19.1									
		885	CFM	9014	8808	8603	8387	8150	7914	7678	7062	6748	6353									
			BHP	2.83	2.88	2.94	2.99	3.03	3.08	3.12	3.15	3.17	3.14									
			Sones	23	23	23	23	23	23	23	22	21	21									

MAXIMUM BHP AT A GIVEN RPM = (RPM/602)³
 MAXIMUM RPM = 885
 TIP SPEED (ft/min) = RPM x 7.983
 MAXIMUM MOTOR FRAME SIZE = 213T
 AVERAGE DISCHARGE VELOCITY (FPM) = CFM/5.50

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Direct Drive CW-060 and CW- 065



CW



Damper Size = 8 x 8 (203 x 203)
 Damper Frame Size = 10 x 10 (254 x 254)
 Wall Opening = 20½ x 20½ (521 x 521)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.051 (1.3)
 ^Approximate Unit Weight = 26 lb (12kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 84.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg										
				0	0.05	0.1	0.125	0.15	0.2	0.25	0.3	0.35	0.375	
CW-060-E	1/200	1050	CFM	133	113	94	81	65						
			BHP	0.01	0.01	0.01	0.01	0.01						
			Sones	1.7	1.7	1.7	1.7	1.7						
CW-060-G	1/100	1300	CFM	165	148	134	126	117	96	70				
			BHP	0.01	0.01	0.01	0.01	0.01	0.01	0.01				
			Sones	2.8	2.6	2.5	2.5	2.5	2.5	2.5				
CW-060-D	1/60	1550	CFM	197	183	169	164	158	143	128	107	85		
			BHP	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.02	
			Sones	4.2	3.9	3.9	3.9	3.9	4.0	4.0	4.0	4.0	4.0	
CW-065-E	1/100	1050	CFM	180	154	126	109	89						
			BHP	0.01	0.01	0.01	0.01	0.01						
			Sones	2.2	2.0	1.9	2.0	2.2						
CW-065-G	1/60	1300	CFM	223	202	181	170	158	129	97				
			BHP	0.02	0.02	0.02	0.02	0.02	0.02	0.02				
			Sones	3.2	3.2	3.1	3.1	3.0	3.0	2.9				
CW-065-D	1/30	1550	CFM	266	249	231	222	214	194	172	145	119	95	
			BHP	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	
			Sones	4.7	4.2	4.2	4.2	4.2	4.1	4.1	4.0	4.0	3.9	

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Direct Drive CW-070 and CW-075



CW



Damper Size = 8 x 8 (203 x 203)
 Damper Frame Size = 10 x 10 (254 x 254)
 Wall Opening = 8 1/2 x 8 1/2 (216 x 216)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.051 (1.3)
 ^Approximate Unit Weight = 26 lb (12 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 85.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg										
				0	0.05	0.1	0.125	0.15	0.2	0.25	0.3	0.35	0.375	
CW-070-E	1/100	1050	CFM	250	224	193	171	143						
			BHP	0.01	0.01	0.01	0.01	0.01						
			Sones	2.6	2.1	1.6	1.4	1.2						
CW-070-G	1/60	1300	CFM	309	288	267	255	241	205	152				
			BHP	0.01	0.01	0.02	0.02	0.02	0.02	0.01				
			Sones	4.0	3.7	3.4	3.3	3.1	2.8	2.4				
CW-070-D	1/30	1550	CFM	369	351	333	325	316	293	269	234	187	160	
			BHP	0.02	0.02	0.03	0.03	0.03	0.03	0.03	0.03	0.02	0.02	
			Sones	5.5	5.4	5.2	5.1	5.1	4.9	4.7	4.4	4.1	3.9	
CW-075-E	1/80	1050	CFM	287	249	210	188	165						
			BHP	0.01	0.01	0.01	0.01	0.01						
			Sones	3.4	3.0	2.8	2.7	2.6						
CW-075-G	1/50	1300	CFM	356	324	294	279	262	227	185				
			BHP	0.02	0.02	0.02	0.02	0.02	0.02	0.02				
			Sones	4.0	3.8	3.7	3.7	3.7	3.6	3.4				
CW-075-D	1/25	1550	CFM	424	398	372	359	347	320	291	261	225	204	
			BHP	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	
			Sones	6.0	5.7	5.4	5.3	5.1	5.0	4.9	4.8	4.8	4.8	

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Direct Drive CW-080 and CW-085



CW



Damper Size = 10 x 10 (254 x 254)
 Damper Frame Size = 12 x 12 (305 x 305)
 Wall Opening = 10½ x 10½ (267 x 267)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.051 (1.3)
 ^Approximate Unit Weight = 40 lb (18 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 85.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg											
				0	0.1	0.125	0.15	0.2	0.25	0.3	0.375	0.5	0.625		
CW-080-E	1/40	1050	CFM	325	265	247	230	189	133						
			BHP	0.01	0.01	0.02	0.02	0.02	0.02						
			Sones	3.8	3.7	3.6	3.7	3.9	4.2						
CW-080-G	1/30	1300	CFM	403	356	343	330	302	272	239	173				
			BHP	0.02	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03			
			Sones	5.4	5.4	5.4	5.4	5.4	5.5	5.6	5.9				
CW-080-D	1/20	1550	CFM	480	441	431	421	400	376	352	314	235			
			BHP	0.04	0.04	0.04	0.04	0.05	0.05	0.05	0.05	0.05	0.05		
			Sones	7.3	7.3	7.3	7.3	7.3	7.2	7.3	7.3	7.3	7.6		
CW-085-E	1/40	1050	CFM	389	323	305	286	242	182						
			BHP	0.01	0.02	0.02	0.02	0.02	0.02						
			Sones	4.0	3.9	3.9	3.9	4.1	4.3						
CW-085-G	1/30	1300	CFM	481	430	416	402	373	340	305	235				
			BHP	0.02	0.03	0.03	0.03	0.03	0.03	0.04	0.04				
			Sones	5.4	5.3	5.3	5.3	5.3	5.3	5.4	5.5				
CW-085-D	1/20	1550	CFM	574	532	520	509	486	461	437	395	312	161		
			BHP	0.04	0.04	0.05	0.05	0.05	0.05	0.06	0.06	0.06	0.06	0.05	
			Sones	7.5	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.6	8.1	

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Direct Drive CW-090



CW



Damper Size = 10 x 10 (254 x 254)
 Damper Frame Size = 12 x 12 (305 x 305)
 Wall Opening = 10½ x 10½ (267 x 267)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.051 (1.3)
 ^Approximate Unit Weight = 40 lb (18 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 85.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg										
				0	0.1	0.125	0.15	0.2	0.25	0.3	0.375	0.5	0.625	
CW-090-E	1/40	1050	CFM	549	470	451	429	381	306	204				
			BHP	0.02	0.02	0.02	0.03	0.03	0.03	0.03				
			Sones	4.1	3.9	3.9	3.9	4.0	4.2	4.5				
CW-090-G	1/25	1300	CFM	680	616	600	584	553	517	479	391			
			BHP	0.04	0.04	0.04	0.04	0.05	0.05	0.05	0.05			
			Sones	5.5	5.4	5.4	5.4	5.4	5.4	5.5	5.6			
CW-090-D	1/15	1550	CFM	811	757	744	731	704	677	651	604	501	347	
			BHP	0.06	0.07	0.07	0.07	0.07	0.08	0.08	0.08	0.09	0.08	
			Sones	7.8	7.6	7.6	7.5	7.5	7.5	7.5	7.4	7.4	7.4	

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Direct Drive CW-095



CW



- Damper Size = 10 x 10 (254 x 254)
- Damper Frame Size = 12 x 12 (305 x 305)
- Wall Opening = 10½ x 10½ (267 x 267)
- Windband Thickness = 0.051 (1.3)
- Motor Cover Thickness = 0.051 (1.3)
- ^Approximate Unit Weight = 40 lb (18 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 85.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg											
				0	0.1	0.125	0.15	0.2	0.25	0.3	0.375	0.5	0.625		
CW-095-E	1/30	1050	CFM	711	603	570	536	468	381	265					
			BHP	0.03	0.04	0.04	0.04	0.04	0.04	0.04	0.03				
			Sones	5.3	4.5	4.5	4.5	4.4	4.5	4.6					
CW-095-G	1/12	1300	CFM	880	797	774	750	696	641	587	484	199			
			BHP	0.06	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.05		
			Sones	7.5	6.8	6.7	6.6	6.5	6.4	6.4	6.4	6.4	6.8		
CW-095-D	1/8	1550	CFM	1049	983	964	944	905	861	816	747	616	442		
			BHP	0.10	0.11	0.11	0.11	0.11	0.12	0.12	0.12	0.12	0.12	0.11	
			Sones	9.6	9.3	9.3	9.2	8.8	8.5	8.4	8.3	8.3	8.1	7.8	

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Direct Drive CW-098 and CW-101



CW



Damper Size = 12 x 12 (305 x 305)
 Damper Frame Size = 14 x 14 (356 x 356)
 Wall Opening = 12½ x 12½ (318 x 318)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 ^Approximate Unit Weight = 53 lb (24 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 85.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg											
				0	0.1	0.125	0.25	0.3	0.375	0.5	0.625	0.75	1		
CW-098-C	1/8	860	CFM	588	453	409	MAXIMUM MOTOR FRAME SIZE = 56								
			BHP	0.02	0.02	0.02									
			Sones	8.4	8.5	8.7									
CW-098-B	1/6	1140	CFM	780	682	656	502	431	294						
			BHP	0.05	0.05	0.06	0.06	0.06	0.06						
			Sones	9.1	8.7	8.7	8.3	8.1	7.9						
CW-098-A	1/4	1725	CFM	1180	1109	1094	1017	984	929	824	712	586			
			BHP	0.18	0.18	0.18	0.18	0.19	0.20	0.20	0.20	0.20			
			Sones	13.8	13.5	13.4	13.0	12.9	12.7	12.2	12.1	12.3			
CW-101-C	1/8	860	CFM	732	649	625	481								
			BHP	0.03	0.03	0.04	0.04								
			Sones	4.6	8.5	11.7	11.1								
CW-101-B	1/6	1140	CFM	970	913	897	806	768	707						
			BHP	0.07	0.08	0.08	0.08	0.09	0.09						
			Sones	7.2	7.0	7.0	6.5	6.2	6.0						
CW-101-A	1/4	1725	CFM	1468	1431	1422	1373	1350	1315	1255	1195	1129	970		
			BHP	0.24	0.25	0.26	0.27	0.27	0.28	0.29	0.29	0.29	0.29		
			Sones	13.3	12.9	12.9	12.5	12.3	12.0	11.7	11.3	10.8	9.7		

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Direct Drive CW-121 and CW-131



CW



Damper Size = 12 x 12 (305 x 305)
 Damper Frame Size = 14 x 14 (356 x 356)
 Wall Opening = 12½ x 12½ (318 x 318)
 Windband Thickness = 0.051 (1.3)
 Motor Cover Thickness = 0.040 (1.0)
 ^Approximate Unit Weight = 53 lb (24 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 85.

Model Size	Motor HP	Fan RPM		CFM / Static Pressure in Inches wg									
				0	0.125	0.25	0.375	0.5	0.625	0.75	1	1.25	1.5
CW-121-C	1/8	860	CFM	1015	905	781	581	MAXIMUM MOTOR FRAME SIZE = 56					
			BHP	0.05	0.05	0.06	0.06						
			Sones	5.3	5.7	5.6	5.7						
CW-121-B	1/6	1140	CFM	1346	1261	1180	1091	981	833				
			BHP	0.11	0.12	0.13	0.13	0.14	0.14				
			Sones	7.4	7.9	8.2	8.2	8.0	8.1				
CW-121-A	1/2	1725	CFM	2037	1979	1923	1869	1816	1763	1710	1571	1406	1176
			BHP	0.39	0.40	0.41	0.43	0.44	0.45	0.46	0.47	0.48	0.46
			Sones	15.6	16.1	16.7	17.3	17.9	18.2	18.4	18.7	18.6	18.4
CW-131-C	1/8	860	CFM	1180	1057	914	675						
			BHP	0.06	0.07	0.07	0.07						
			Sones	8.5	8.3	7.7	6.9						
CW-131-B	1/6	1140	CFM	1564	1471	1379	1280	1144	964				
			BHP	0.14	0.15	0.16	0.17	0.17	0.17				
			Sones	12.5	12.2	11.8	11.2	10.3	9.7				
CW-131-A	3/4	1725	CFM	2366	2305	2244	2183	2122	2061	1994	1838	1646	1365
			BHP	0.50	0.51	0.53	0.54	0.56	0.57	0.58	0.60	0.60	0.57
			Sones	18.8	18.6	18.4	18.2	18.0	17.6	17.2	16.4	15.3	14.1

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Sidewall - Direct Drive CW-180, CW-180HP and CW-200



CW

Damper Size = 17 x 17 (432 x 432)
 Damper Frame Size = 19 x 19 (483 x 483)
 Wall Opening = 17½ x 17½ (445 x 445)
 Windband Thickness = 0.064 (1.6)
 Motor Cover Thickness = 0.040 (1.0)
 ^Approximate Unit Weight = 142 lb (64 kg)

All dimensions in inches (millimeters). *May be greater depending on motor. ^Weight shown is largest cataloged Open Drip-Proof motor. For specification information and image of model, please see page 85.

Model Size	Motor HP	Fan RPM	CFM / Static Pressure in Inches wg										
			0	0.25	0.5	0.75	1	1.25	1.5	2	2.5	3	
CW-180-C	1/2	860	CFM	3249	2922	2474	MAXIMUM MOTOR FRAME SIZE = 184T						
			BHP	0.34	0.39	0.40							
			Sones	12.3	11.1	10.2							
CW-180-B	1	1140	CFM	4307	4045	3822	3470	3072	2477				
			BHP	0.80	0.86	0.91	0.93	0.92	0.85				
			Sones	17.6	16.5	16.1	15.4	14.6	13.6				
CW-180HP-A	2	1725	CFM	4850	4732	4613	4493	4353	4215	4078	3740	3265	2695
			BHP	1.77	1.84	1.92	1.99	2.06	2.12	2.18	2.23	2.25	2.16
			Sones	30	29	28	27	26	26	25	24	23	21
CW-200-C	3/4	860	CFM	4837	4346	3815	3084						
			BHP	0.71	0.74	0.75	0.73						
			Sones	15.7	14.6	12.9	11.9						
CW-200-B	2	1140	CFM	6412	6036	5674	5283	4837	4276	3445			
			BHP	1.65	1.70	1.74	1.74	1.74	1.73	1.63			
			Sones	24	23	22	21	20	19.2	19.9			

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.

Belt Drive Specifications

Model CUBE



Spun aluminum exhaust fans shall be centrifugal belt-driven type. The fan wheel shall be centrifugal backward-inclined, constructed of aluminum and shall include a wheel cone carefully matched to the inlet cone for precise running tolerances. Wheels shall be statically and dynamically balanced. The fan housing shall be constructed of heavy-gauge aluminum with a rigid internal support structure. The windband shall be welded to the one-piece curb cap and on all sizes with UL/cUL 762.

Motors shall be heavy-duty ball bearing type, carefully matched to the fan load, and furnished at the specified voltage, phase and enclosure. Drive frame assembly shall be constructed of heavy-gauge steel.

Motors and drives shall be mounted on vibration isolators, out of the airstream where no steel-to-steel contact between rotating components and the base shall occur. Fresh air for motor cooling shall be drawn into the motor compartment through a ten-square-inch tube free of discharge contaminants. Motors and drives shall be readily accessible for maintenance.

Precision ground and polished fan shafts shall be mounted in permanently sealed, lubricated pillow block ball bearings. Bearings shall be selected for a minimum L_{10} life in excess of 100,000 hours (L_{50} life of 500,000 hours) at maximum cataloged operating speed. Drives shall be sized for a minimum of 150% of driven horsepower. Pulleys shall be of the cast type, keyed and securely attached to the wheel and motor shafts.

Motor pulleys shall be adjustable for final system balancing. A disconnect switch shall be factory installed and wired from the fan motor to a junction box installed within the motor compartment. A conduit chase shall be provided through the base to the motor compartment for ease of electrical wiring.

All fans shall bear the AMCA Sound and Air Performance seal.

Each fan shall bear a permanently affixed manufacturer's engraved metal nameplate containing the model number and individual serial number for future identification.

A leakproof fan housing shall be constructed with a one-piece windband with an integral rolled bead for added strength and shall be joined to the curb cap with a continuously welded seam.

Fans shall be model CUBE, CUBE-HP or CUBE-XP as manufactured by Greenheck Fan Corporation in Schofield, Wisconsin, USA.

Options and Accessories For Belt Drives

UL/cUL Listed

- Fans shall be Listed by Underwriters Laboratory for UL/cUL 705 for all electrical components.
- Fans shall be Listed by Underwriters Laboratory for UL/cUL 762 for all electrical components and grease removal.

Curb Extensions

- Shall be mounted between roof curb and roof mounted fans to meet NFPA requirements of 40 inches (1016 mm) minimum discharge above the roof when mounted on a minimum 8-inch (203 mm) high roof curb.

Grease Containers

- Drain connection shall be constructed of aluminum and allow for single-point drainage of grease, water or other residues.
- Grease trap shall include the drain connection and shall be constructed from aluminum. The unit shall collect grease and water from the fan and extract the grease from the water for ease of grease disposal.

Easy Clean Options

- Hinge kit shall be constructed of heavy-gauge aluminum hinges and shall include hold-open cables for field installation.
- Non-stick wheel shall be constructed of aluminum with a non-stick coating similar to Teflon[®] as manufactured by DuPont[™].
- Clean-Out Port shall have a hole on the outside of the windband and a grease repellent compression rubber fit, allowing access to entire wheel for cleaning.

Windband Extension

- Shall be constructed from heavy-gauge aluminum tube that raises the discharge an additional 36 inches (914 mm).



Direct Drive Specifications

Model CUE



Spun aluminum exhaust fans shall be upblast centrifugal direct drive type. The fan wheel shall be centrifugal backward-inclined, constructed of aluminum and shall include a wheel cone carefully matched to the inlet cone for precise running tolerances. Wheels shall be statically and dynamically balanced. The fan housing shall be constructed of heavy-gauge aluminum with a rigid internal support structure. The windband shall be one-piece and 100% continuously robotically welded to the one-piece aluminum curb cap.

Motors shall be mounted out of the airstream on vibration isolators. Fresh air for motor cooling shall be drawn into the motor compartment through a ten-square-inch tube free of discharge contaminants. Motors and drives shall be readily accessible for maintenance.

A disconnect switch shall be factory installed and wired from the fan motor to a junction box within the motor compartment. A conduit chase shall be provided through the curb cap to the motor compartment for ease of electrical wiring.

All fans shall bear the AMCA Sound and Air Performance seal.

Each fan shall bear a permanently affixed manufacturer's engraved metal nameplate containing the model number and individual serial number for future identification.

A leakproof fan housing shall be constructed with a one-piece windband with an integral rolled bead for added strength.

Fans shall be model CUE or CUE-HP as manufactured by Greenheck Fan Corporation in Schofield, Wisconsin, USA.

Options and Accessories For Direct Drives

UL/cUL Listed

- Fans shall be Listed by Underwriters Laboratory for UL/cUL 705 for all electrical components.
- Fans shall be Listed by Underwriters Laboratory for UL/cUL 762 for all electrical components and grease removal.

Curb Extensions

- Shall be mounted between roof curb and roof mounted fans to meet NFPA requirements of 40 inches (1016 mm) minimum discharge above the roof when mounted on a minimum 8-inch (203 mm) high roof curb.

Grease Containers

- Drain connection shall be constructed of aluminum and allow for single-point drainage of grease, water or other residues.
- Grease trap shall include the drain connection and shall be constructed from aluminum. The unit shall collect grease and water from the fan and extract the grease from the water for ease of grease disposal.

Easy Clean Options

- Hinge kit shall be constructed of heavy-gauge aluminum hinges and shall include hold-open cables for field installation.
- Non-stick wheel shall be constructed of aluminum with a non-stick coating similar to Teflon[®] as manufactured by DuPont[™].
- Clean-Out Port shall have a hole on the outside of the windband and a grease repellent compression rubber fit, allowing access to entire wheel for cleaning.



Windband Extension

- Shall be constructed from heavy-gauge aluminum tube that raises the discharge an additional 36 inches (914 mm).

Belt Drive Specifications

Model CWB



Spun aluminum exhaust fans shall be centrifugal belt-driven type. The fan wheel shall be centrifugal backward-inclined, constructed of aluminum and shall include a wheel cone carefully matched to the inlet cone for precise running tolerances. Wheels shall be statically and dynamically balanced. The fan housing shall be constructed of heavy-gauge aluminum with a rigid internal support structure. The windband shall be welded to the one-piece curb cap and on all sizes with UL/cUL 762.

Motors shall be heavy-duty ball bearing type, carefully matched to the fan load, and furnished at the specified voltage, phase and enclosure. Drive frame assembly shall be constructed of heavy-gauge steel. Motors and drives shall be mounted on vibration isolators, out of the airstream where no steel-to-steel contact between rotating components and the base shall occur. Fresh air for motor cooling shall be drawn into the motor compartment through a ten-square-inch tube free of discharge contaminants. Motors and drives shall be readily accessible for maintenance.

Precision ground and polished fan shafts shall be mounted in permanently sealed, lubricated pillow block ball bearings. Bearings shall be selected for a minimum L_{10} life in excess of 100,000 hours (L_{50} life of 500,000 hours) at maximum catalogued operating speed. Drives shall be sized for a minimum of 150% of driven horsepower. Pulleys shall be of the cast type, keyed and securely attached to the wheel and motor shafts.

Motor pulleys shall be adjustable for final system balancing. A disconnect switch shall be factory installed and wired from the fan motor to a junction box installed within the motor compartment. A conduit chase shall be provided through the base to the motor compartment for ease of electrical wiring.

All fans shall bear the AMCA Sound and Air Performance seal.

Each fan shall bear a permanently affixed manufacturer's engraved metal nameplate containing the model number and individual serial number for future identification.

A leakproof fan housing shall be constructed with a one-piece windband with an integral rolled bead for added strength. Fan shall be provided with a mounting plate, which is attached and sealed to the wall prior to locating the entire unit.

Fans shall be model CWB or CWB-HP as manufactured by Greenheck Fan Corporation in Schofield, Wisconsin, USA.

Options and Accessories For Belt Drives

UL/cUL Listed

- Fans shall be Listed by Underwriters Laboratory for UL/cUL 705 for all electrical components.
- Fans shall be Listed by Underwriters Laboratory for UL/cUL 762 for all electrical components and grease removal.

Easy Clean Options

- Non-stick wheel shall be constructed of aluminum with a non-stick coating similar to Teflon® as manufactured by DuPont™.

Direct Drive Specifications

Model CW



Spun aluminum exhaust fans shall be upblast centrifugal direct drive type. The fan wheel shall be centrifugal backward-inclined, constructed of aluminum and shall include a wheel cone carefully matched to the inlet cone for precise running tolerances. Wheels shall be statically and dynamically balanced. The fan housing shall be constructed of heavy-gauge aluminum with a rigid internal support structure.

Motors shall be mounted out of the airstream on vibration isolators. Fresh air for motor cooling shall be drawn into the motor compartment through a ten-square-inch tube free of discharge contaminants. Motors and drives shall be readily accessible for maintenance.

A disconnect switch shall be factory installed and wired from the fan motor to a junction box within the motor compartment. A conduit chase shall be provided through the curb cap to the motor compartment for ease of electrical wiring.

All fans shall bear the AMCA Sound and Air Performance seal.

Each fan shall bear a permanently affixed manufacturer's engraved metal nameplate containing the model number and individual serial number for future identification.

A leakproof fan housing shall be constructed with a one-piece windband with an integral rolled bead for added strength. Fan shall be provided with a mounting plate, which is to be attached and sealed to the wall prior to locating the entire unit.

Fans shall be model CW or CW-HP as manufactured by Greenheck Fan Corporation in Schofield, Wisconsin, USA.

Options and Accessories For Direct Drives

UL/cUL Listed

- Fans shall be Listed by Underwriters Laboratory for UL/cUL 705 for all electrical components.
- Fans shall be Listed by Underwriters Laboratory for UL/cUL 762 for all electrical components and grease removal.

Easy Clean Options

- Non-stick wheel shall be constructed of aluminum with a non-stick coating similar to Teflon® as manufactured by DuPont™.

Belt Drive Specifications

Model USGF

Ultimate Steel Grease Fan



Spun steel exhaust fans shall be centrifugal belt-driven type. Fan wheel shall be centrifugal backward-inclined type. The wheel shall be constructed of steel and coated with a non-stick coating similar to Teflon[®] as manufactured by DuPont[™]. Wheel shall include a wheel cone carefully matched to the inlet cone for precise running tolerances. Wheels shall be statically and dynamically balanced.

The fan housing shall be constructed of 16-gauge galvaneal steel with a rigid internal support structure and shall be leakproof. The fan housing shall be constructed with a one-piece windband with an integral rolled bead for added strength and shall be joined to the curb cap with a continuously welded seam.

The fan windband shall have a Clean-Out Port, a 4-inch diameter hole on the outside of the fan's windband with a grease repellent compression rubber fit, allowing access to entire wheel for cleaning.

Motors shall be heavy-duty ball bearing type, carefully matched to the fan load, and furnished at the specified voltage, phase and enclosure. Drive frame assembly shall be constructed of heavy-gauge galvanized steel. Motors and drives shall be mounted on heavy-duty true vibration isolators, out of the airstream. Fresh air for motor cooling shall be drawn into the motor compartment through a ten-square-inch tube free of discharge contaminants. Motors and drives shall be readily accessible for maintenance.

Precision ground and polished 1-inch minimum diameter fan shafts shall be mounted in cast pillow block lubricatable ball bearings. Bearings shall be selected for a minimum L_{10} life in excess of 100,000 hours (L_{50} life of 500,000 hours) at maximum cataloged operating speed. Dual drives shall be sized for a minimum of 150% of driven horsepower. Pulleys shall be of the cast type, keyed and securely attached to the wheel and motor shafts.

Motor pulleys shall be adjustable for final system balancing. All fans shall have a dual belt and pulley system. A NEMA-3R disconnect switch shall be factory installed and wired from the fan motor to a junction box installed outside the motor compartment.

All fans shall bear the AMCA Sound and Air Performance seal.

Each fan shall bear a permanently affixed manufacturer's engraved metal nameplate containing the model number and individual serial number for future identification.

Fans shall be Listed by Underwriters Laboratory for UL/cUL 762 Listed for all electrical components and grease removal.

Hinged base shall be constructed of heavy-gauge hinges and shall include hold-open cables for field installation.

Grease trap shall include the drain connection. The unit shall collect grease and water from the fan and extract the grease from the water for ease of grease disposal.

Fans shall be model USGF as manufactured by Greenheck Fan Corporation in Schofield, Wisconsin, USA.

Belt Drive Specifications

Model S-CUBE

Emergency Smoke Control



Spun aluminum exhaust fans shall be centrifugal belt-driven type. The fan wheel shall be centrifugal backward-inclined, constructed of steel and shall include a wheel cone carefully matched to the inlet cone for precise running tolerances. Wheels shall be statically and dynamically balanced. The fan housing shall be constructed of heavy-gauge aluminum with a rolled bead and a rigid internal support structure. A leakproof fan housing shall be constructed with a one-piece windband with an integral rolled bead for added strength and shall be joined to the curb cap with a continuously welded seam.

Motors shall be heavy-duty ball bearing type, carefully matched to the fan load, and furnished at the specified voltage, phase and enclosure. Drive frame assembly shall be constructed of heavy-gauge steel. Motors and drives shall be mounted on safety flange vibration isolators, out of the airstream. Fresh air for positive motor cooling shall be drawn into the motor compartment through a ten-square-inch tube free of discharge contaminants. Motors and drives shall be readily accessible for maintenance.

Precision ground and polished fan shafts shall be mounted in permanently sealed, lubricated pillow block ball bearings. Bearings shall be selected for a minimum L_{10} life in excess of 100,000 hours (L_{50} life of 500,000 hours) at maximum cataloged operating speed.

Dual drives shall be sized for a minimum of 150% of driven horsepower. Pulleys shall be of the cast type, keyed and securely attached to the wheel and motor shafts.

Motor pulleys shall be adjustable for final system balancing. A NEMA-3R disconnect switch shall be factory installed and wired from the fan motor to a junction box installed outside the motor compartment.

All fans shall bear the AMCA Sound and Air Performance seal.

Each fan shall bear a permanently affixed manufacturer's engraved metal nameplate containing the model number and individual serial number for future identification.

Fans shall be Listed by Underwriters Laboratory for UL/cUL 705 for electrical components and UL/cUL Listed for Emergency Smoke Control Systems [500°F (260°C) for 4 hours and 1,000°F (538°C) for 15 minutes].

Fans shall be model S-CUBE as manufactured by Greenheck Fan Corporation in Schofield, Wisconsin, USA.

Quick Delivery and Quick Build Programs

QUICK
DELIVERY




Greenheck Fan Corporation offers an extensive selection of Quick Delivery (QD) and Quick Build (QB) offerings. The QD program is Greenheck's stock program and the QB program offers configurable fans in one, three, five, or ten days.

Hundreds of in-stock ventilation products and accessories are available for shipment to your jobsite in less than 24 hours from our strategically located warehouses throughout the world.

Please see the chart below for model size and availability for QD and QB programs. The Greenheck Stock & Quick Build Catalog is a great resource for specific options and accessories available with QD and QB fans.

Quick Delivery & Quick Build Availability by Model Size					
SIZE	CUBE	CUE	CWB	CW	USGF
060 - 095		1-3-10		QD-1-3-10	
098	QD-1-3-10	1-3-10	1-3-10	QD-1-3-10	
101	QD-1-3-10	QD-1-3-10	1-3-10	QD-1-3-10	
101HP	1-3-10		1-3-10		
121	QD-1-3-10	QD-1-3-10	1-3-10	QD-1-3-10	
131	1-3-10	1-3-10	1-3-10	1-3-10	
140					10
140HP					10
141	QD-1-3-10	1-3-10	QD-1-3-10	1-3-10	
141HP	QD-1-3-10	1-3-10	1-3-10	1-3-10	
160					10
160HP					10
160XP					10
161	QD-1-3-10	QD-1-3-10	QD-1-3-10	1-3-10	
161HP	QD-1-3-10	1-3-10	1-3-10	1-3-10	
161XP	1-3-10				
180	QD-1-3-10	1-3-10	QD-1-3-10	1-3-10	10
180HP	QD-1-3-10	1-3-10	1-3-10	1-3-10	10
200	QD-1-3-10	1-3-10	1-3-10	1-3-10	10
200HP	1-3-10		1-3-10		10
220	QD-1-3-10		1-3-10		
220HP	1-3-10		1-3-10		
240	QD-1-3-10		1-3-10		
240HP	QD-1-3-10		1-3-10		
240XP	1-3-10				
300	QD-1-3-10		1-3-10		
300HP	1-3-10		1-3-10		
300XP	1-3-10				
360	1-3-10				
360HP	1-3-10				
360XP	1-3-10				
420	1-3-10				
480	1-3-10				

Model S-CUBE fans are not available on a Quick Delivery or Quick Build Program.



Our Warranty

Greenheck warrants this equipment to be free from defects in material and workmanship for a period of one year from the purchase date. Any units or parts which prove defective during the warranty period will be replaced at our option when returned to our factory, transportation prepaid. Motors are warranted by the motor manufacturer for a period of one year. Should motors furnished by Greenheck prove defective during this period, they should be returned to the nearest authorized motor service station. Greenheck will not be responsible for any removal or installation costs.

As a result of our commitment to continuous improvement, Greenheck reserves the right to change specifications without notice.



Prepared to Support
Green Building Efforts



Centrifugal Upblast and Sidewall Exhaust Fans

Rev. 2 May 2009 R

Copyright © 2009 Greenheck Fan Corp.