

Job _____

Type _____

Catalog # _____



20 SS



15 SS



12 SS



19 DS



14 DS



11 DS



LUMAX INDUSTRIES, INC. Chestnut Avenue & Fourth Street
Altoona, PA 16603-0991 814-944-2537 Fax 814-944-6413
www.lumaxlighting.com

SP SERIES

Mini

Mini-Stratolume Surface Luminaires

APPLICATION

- Luminous square or round diffusers for comfortable, soft lighting in residences and commercial interiors. Ceiling or wall mount.
- Frameless design for floating appearance. Compliments full size SP Stratolume Luminaires for matching style in the same application.
- Efficient PL, Circline, Double D or Quad light sources.
- All models are American with Disabilities Act (ADA) compliant except for the 19 and 20 inch models.



CONSTRUCTION

- Ultra shallow, die-formed code gauge cold rolled steel housing. Knockouts, holes and key hole slots provided on housing for mounting and electrical connections. Integrated brass lens retainer bushings.
- Fully luminous, translucent white molded .080" (round) and .187" (square) acrylic lens for uniform, low brightness lighting. Decorative white finish, knurled set screws secure diffuser to housing providing tool-free relamping.
- Optional tamperproof hardware.
- Optional polycarbonate diffusers for impact resistance in public facilities.

FINISH

- All metal parts pretreated with a phosphate bonding process and post-painted with an electrostatically-applied high temperature baked white enamel for superior quality and durability.
- Optional non-reflective matte black exterior housing finish available.

ELECTRICAL

- Standard ballast is electronic, HPF, class P, and UL listed for universal voltage.
-  listed and  listed.
- Suitable for damp locations.
- I.B.E.W. labeled.



SP SERIES

Mini-Stratolume

Surface Luminaires

ORDERING GUIDE

SP							
Series	No. Lamps	Lamp Style	Fixture Size	Ballast	Volts	Lens	Options
SP	1	13	12	PC	9	SS	
SP	1	26	12	QE	9	SS	
SP	2	26	15	QE	9	SS	
SP	1	38	15	DD	9	SS	
SP	1	38	20	DD	9	SS	
SP	1	13	11	PC	9	DS	
SP	1	26	11	QE	9	DS	
SP	2	26	14	QE	9	DS	
SP	2	32	14	TE	9	DS	
SP	1	38	14	DD	9	DS	
SP	1	38	19	DD	9	DS	
SP	3	26	19	QE	9	DS	

LAMPS:

13 - 13 Watt Twin Tube
22 - 22 Watt Circline
26 - 26 Watt Quad
32 - 32 Watt Triple Tube
38 - 38 Watt Double D

BALLASTS:

DD - Electronic Double D
PC - Electronic - 4 Pin
TE - Electronic - Triple
QE - Electronic Quad - 4 Pin

Note: Consult factory for additional lamp and ballast options.

VOLTS:

1 - 120 Volts
4 - 277 Volts
9 - Universal Voltage (120-277)

OPTIONS:

Use the following suffix for:

PRS - Programmed Rapid Start Ballast (STD on T5)

IS - Instant Start Ballast (STD on T8)

TP - Tamperproof Hardware

BK - Black Finish Housing (white standard)

P - Polycarbonate impact-resistant lens

Emergency Ballast - Please consult Options page for complete listings.

Dimming Ballast - Please consult the factory.

LENS:


SS - Square translucent white .187" acrylic

DS - Round translucent white .080" acrylic



DIMENSIONS

specifications and dimensional data subject to change without notice



SS Style Lens




SP 20
No. 214




SP 15
No. 178





SP 12
No. 179





DS Style Lens




SP 19
No. 215



SP 14
No. 181



SP 11
No. 180



Number shown indicates mounting / knockouts diagram - see Options & Accessories section of catalog.

LUMAX INDUSTRIES, INC.
SPMini.0611