

The Whitney Museum A Building Envelope Case Study

Georgia Ewen-Campen / Heintges Consulting Architect & Engineers



Whitney Museum of American Art

Architect:

and the second state

01 1101 1011 1111

Structural Engineer: MEP Engineer: Facade Consultant: Roofing Consultant: Energy Consultant: Renzo Piano Building Workshop in collaboration with Cooper Robertson Robert Silman Associates Jaros Baum & Bolles Heintges Henshell & Buccellato

Construction Manager: Turner Construction Curtain Wall: Gartner Precast Fabricator: BPDL

Facade Design

Massing / Materiality

Light / Transparency







Facade Design

Massing / Materiality

Light / Transparency













Natural Light Control

Interior Environment

Condensation Mitigation



Natural Light Control

Interior Environment

Condensation Mitigation



Natural Light Control

Interior Environment

Condensation Mitigation



Wall Type 1: Precast concrete panels

<u>Wall Type 2:</u> Unitized curtain wall with steel plate rain screen

<u>Wall Types 3, 4, 5, 8 + 10:</u> Large insulating glass units capture-glazed onto custom steel framing

<u>Wall Type 6:</u> Tension cable wall with monolithic glazing

Wall Type 7: Steel sawtooth monitors with north-facing clerestory windows.



SOUTH ELEVATION





WEST ELEVATION



NORTH ELEVATION

Wall Type 1: Precast concrete panels

<u>Wall Type 2:</u> Unitized curtain wall wit steel plate rain screen

<u>Wall Types 3, 4, 5, 8 + 10:</u> Large insulating glass units capture-glazed onto custom steel framing

<u>Wall Type 6:</u> Tension cable wall with monolithic glazing

<u>Wall Type 7:</u> Steel sawtooth monitors with north-facing clerestory windows.



SOUTH ELEVATION





WEST ELEVATION



NORTH ELEVATION

Wall Type 2: Unitized curtain wall with steel plate rain screen





WEST ELEVATION



NORTH ELEVATION

Wall Type 1: Precast concrete panels

<u>Wall Type 2:</u> Unitized curtain wall with steel plate rain screen

<u>Wall Types 3, 4, 5, 8 + 10:</u> Large insulating glass units capture-glazed onto custom steel framing

<u>Wall Type 6:</u> Tension cable wall with monolithic glazing

<u>Wall Type 7:</u> Steel sawtooth monitors with north-facing clerestory windows.



SOUTH ELEVATION



WEST ELEVATION



NORTH ELEVATION

Wall Type 1: Precast concrete panels

<u>Wall Type 2:</u> Unitized curtain wall with steel plate rain screen

<u>Wall Types 3, 4, 5, 8 + 10:</u> Large insulating glass units capture-glazed onto custom steel framing

<u>Wall Type 6:</u> Tension cable wall with monolithic glazing

<u>Wall Type 7:</u> Steel sawtooth monitors with north-facing clerestory windows.



SOUTH ELEVATION







NORTH ELEVATION

Wall Type 1: Precast concrete panels

<u>Wall Type 2:</u> Unitized curtain wall with steel plate rain screen

<u>Wall Types 3, 4, 5, 8 + 10:</u> Large insulating glass units capture-glazed onto custom steel framing

<u>Wall Type 6:</u> Tension cable wall with monolithic glazing

Wall Type 7: Steel sawtooth monitors with north-facing clerestory windows.



SOUTH ELEVATION







NORTH ELEVATION

Condensation Mitigation

Quality Control



Unitized curtain wall with steel plate rain screen

Thermal Performance Condensation Mitigation Quality Control



Unitized curtain wall with steel plate rain screen

Thermal Performance Condensation Mitigation Quality Control







Unitized curtain wall with steel plate rain screen

Thermal Performance

Condensation Mitigation

Quality Control



Thermal Insulation

Thermal Performance

Condensation Mitigation

Quality Control



Wintertime Design Conditions:

Exterior Temperature:	13 °F
Interior Temperature:	72 °F
Interior Relative Humidity:	45%
Dewpoint:	49 °F

Thermal Performance

Condensation Mitigation



Thermal Performance

Condensation Mitigation







Thermal Performance

Condensation Mitigation







Thermal Performance

Condensation Mitigation







Thermal Performance

Condensation Mitigation



Thermal Performance

Condensation Mitigation



Thermal Performance

Condensation Mitigation







Thermal Performance

Condensation Mitigation



Thermal Performance

Condensation Mitigation



Thermal Performance

Condensation Mitigation



Thermal Performance Condensation Mitigation





Thermal Performance

Condensation Mitigation

Quality Control



L-shaped precast panels

Thermal Performance

Condensation Mitigation

Quality Control





L-shaped precast panels

Thermal Performance

Condensation Mitigation

Quality Control



Precast panels

Thermal Performance

Condensation Mitigation

Quality Control



L-shaped precast panels

Thermal Performance

Condensation Mitigation

Quality Control



Closed cell spray foam insulation

Thermal Performance

Condensation Mitigation

Quality Control



Closed cell spray foam insulation

30

Thermal Performance

Condensation Mitigation

Quality Control



Interface conditions

GARTNER: 02-086

KEY INTERFACE CONDITION #12 heintges

Thermal Performance

Condensation Mitigation

Quality Control



KEY INTERFACE CONDITION #12 heintges

Thermal Performance

Condensation Mitigation

Quality Control



Interface conditions

GARTNER: 02-086

KEY INTERFACE CONDITION #12 heintges

Thermal Performance

Condensation Mitigation

Quality Control



Thermal Performance

Condensation Mitigation

Quality Control



Thermal Performance

Condensation Mitigation

Quality Control



Thermal Performance

Condensation Mitigation

Quality Control



Natural Light Control Condensation Mitigation



Natural Light Control Condensation Mitigation





Natural Light Control Condensation Mitigation



Natural Light Control

Condensation Mitigation

Quality Control



Controlling light levels

Natural Light Control

Condensation Mitigation

Quality Control



Glazing from outside to inside

Low Iron <u>Pilkington Optiwhite</u> 10 mm with combi neutral 70/40 12 mm argon Laminated glass: Low iron <u>Pilkington Optiwhite</u> 5 mm 1,52 mm PVB- interlayer (Trosifol BG R20) Low-iron <u>Pilkington Optiwhite</u> 5 mm

light transmittance	: approx. 73%
light reflectance (outside)	: approx. 13%
light reflectance (inside)	: approx. 13%
solar direct transmittance	: approx. 36%
solar direct reflectance (outside)	: approx. 38%
solar direct reflectance (inside)	: approx. 37%
solar factor (g-value)	: approx. 39%
shading coefficient	: approx. 45%
UV-transmittance	: approx. 0%
UV-reflectance	: approx. 8%
UV-absorption	: approx. 92%
color rendering index	: approx. 97

thermal transmittance (NFRC) Ug: approx. 1,36 W/m²K



UV transmittance by wave length

Natural Light Control

Condensation Mitigation

Quality Control



Mechanical Shades

Natural Light Control

Condensation Mitigation

Quality Control



Mechanical Shades

Natural Light Control

Condensation Mitigation

Quality Control



Blocking direct solar penetration

Natural Light Control

Condensation Mitigation



Natural Light Control Condensation Mitigation



Natural Light Control Condensation Mitigation



Natural Light Control

Condensation Mitigation



Natural Light Control

Condensation Mitigation



Natural Light Control

Condensation Mitigation

Quality Control



Daylighting

Natural Light Control

Condensation Mitigation

Quality Control



Rooftop monitors

Natural Light Control

Condensation Mitigation

Quality Control



Glazing U-value: 0.12 Btu/hr ft² °F System U-Value: 0.11 Btu/hr ft² °F



Dew Point: 49 °F (9.5 °C)

Triple glazing

Natural Light Control

Condensation Mitigation





Natural Light Control

Quality Control





thermocouples locations (inside and outside) T2

Τ4

Τ6

vertical glass side

T1 mullion outside Т3 center of glass outside T5 transom outside upper edge of glass inside

T14

- inclined panel side center of metal panel outside T7 **T9** edge of metal panel outside
- center of metal panel outside T8 T10 edge of metal panel inside

mullion inside

T15 upper transom inside

center of glass inside transom inside

gutter

T13 gutter inside



Min Interior Surface Temp: 60.9 F

Natural Light Control

Condensation Mitigation

Quality Control





Flood testing and vector mapping

Natural Light Control Condensation Mitigation



Natural Light Control

Condensation Mitigation







Natural Light Control

Condensation Mitigation





Natural Light Control

Condensation Mitigation

Quality Control





Tension measurement

Natural Light Control Condensation Mitigation



Natural Light Control Condensation Mitigation



